



# Aerothatch 83 & Seeder 93

Provides relief from troublesome thatch and compaction and slit seeds all in one pass.



	AEROTHATCH 83, MODELS 44830		SEEDER 93, MODEL 44835 <sup>[1]</sup>
<b>SWATH</b>	48" (122 cm), 45" (114 cm) blade tip to blade tip.	<b>DRIVE</b>	Ground powered.
<b>SPACING</b>	Model 44830: 3" (7.6 cm)	<b>SEED HOPPER</b>	100 lbs. (45.4 kg) capacity.
<b>HITCH</b>	Standard 3 point hitch, Category 1.	<b>HOPPER AUGER</b>	Metal cogs on a steel shaft.
<b>DRIVE</b>	Std. 1 <sup>3</sup> / <sub>8</sub> " splined Ag. type drive shaft. PTO to gearbox, sealed bearing and sprocket, #H80 chain to blade shaft.	<b>SEED SHUT OFF</b>	Remote from the operator's position.
<b>GEARBOX</b>	Heavy duty 1:1 right angle reversible gearbox.	<b>SEED TUBES</b>	Delivers seed to 16 discs.
<b>BLADES</b>	(16) 12 ga./10 pt. (Optional: 7 ga. & 10 ga./10 pt.).	<b>FEED OPENINGS</b>	Adjustable to the desired rate.
<b>BLADE SHAFT</b>	1.5" (38 mm) square high carbon steel.	<b>DIMENSIONS</b>	Height: 33" (84 cm). Length: 13" (33 cm) Width: 56" (142 cm)
<b>BLADE DEPTH</b>	0-3" (7.6 cm) in 1/4" (6.3 mm) increments.	<b>SHIPPING WEIGHT</b>	300 lbs. (136 kg)
<b>FRAME</b>	All welded steel construction.	<b>OPTIONAL</b>	Drag Mat, 72-002-0021.
<b>ROLLER</b>	Full width, 3.5" (8.9 cm) dia. roller with sealed bearings. Roller is integral with the skid shoes and spring loaded wiper for full width of roller.		
<b>DIMENSIONS</b>	Height: 36" (91 cm) (with 3 pt. hitch). Length: 57" (145 cm). Width: 60" (152 cm).		
<b>SHIPPING WEIGHT</b>	550 lbs. (250 kg)		

\* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

[1] Must be used with 44830 Aerothatch.

