

TORO Count on it.

4800 Turf Sweeper



The quick and easy way to pick up leaves, sticks, and other debris.



COMFORTABLE AND SAFE TO OPERATE Self-propelled and ergonomically designed, the 4800 Turf Sweeper makes cleanup of the biggest spring and fall jobs a breeze. It features a convenient, hand-operated rear-drum brake system and safety interlocks, requiring the operator to be in position before engaging.

MORE POWER TO YOU The 4800 Turf Sweeper is powered by a CARB Certified, Kohler® Command™ 18 hp engine, which runs cooler, quieter, and more efficiently for longer life. Its 48" sweeping width and 1.25 cubic yards of hopper capacity helps you get the job done faster. And because the 4800 Turf Sweeper is from Toro, you are assured years of performance and productivity when it comes to debris management.

4800 Turf Sweeper

| | |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine | 18 hp, twin cylinder, Kohler Command, EPA & CARB Certified. |
| Air Cleaner | Standard: A Kohler 2-stage system with rotating screen (pre-cleaner). |
| Fuel System | 5 gallon (18.93 liters) capacity polyethylene tank. |
| Ground Speed | While sweeping: up to 5 mph (8 km/h). In transport: up to 6.5 mph (10.4 km/h). |
| Traction/Drive | Sundstrand 15 pump w/Parker/Ross hydraulic wheel motors. |
| Reel Pick Up | Belt-driven, counter-rotating, dual rubber finger reels. Reels rotate between 1,100 and 1,200 rpm with staggered overlapping sweeping fingers. |
| Reel Engagement | 2-position reel height adjustment with slack/tight belt engagement. |
| Sweeping Width | 48" (122 cm) |
| Hopper Lift & Lower | Stationary hopper with gas cylinder assisted, lever operated hopper door. Includes removable grass baffle. |
| Dust Control | Internal hopper design directs discharged exhaust dust down and to the rear of the sweeper, away from the operator. |
| Hopper Capacity | 1.25 cu. yd. (.96 cu. meters) capacity. |
| Operator's Seat | High back cushion seat with slide adjust. |
| Tires | Front: 18 x 8.5-8" (45.7 x 21.5-20.3 cm) ribbed tread Rear: 18 x 9.5-8" (45.7 x 24.1-20.3 cm) turf tread (4-ply). |
| Maintenance | The engine oil drain plug, oil filter and battery are all located behind a front access panel. All reel bearings are greaseable. |
| Tie Downs | 4 tie downs – one at each corner of the machine. |
| Safety Features | Parking brake (6" rear drums), protective interlock switches and shielding of hydraulic hoses. |
| Dimensions | Overall Width: 69" (175 cm) Overall Length: 113" (287 cm) |
| Curb Clearance | 4" (10.2 cm) |
| Weight | 1,600 lbs. (726 kgs) |
| Options | ROPS, Donaldson Air Cleaner*, Spark Arrestor* |