



Debris Blower 400

The Toro® Debris Blower 400 generates considerable wind power to quickly clear areas of debris.



DEBRIS BLOWER 400, MODEL 44523	
POWER SOURCE	Category one 3-point hitch of any tractor in the 25 PTO hp range with a 3-point hitch and 540 PTO.
AIR FLOW	6002 cfm.
FAN SPEED	1850 rpm @ 540 PTO input.
OUTLET AREA	70 square inches (452 cm ²).
DIRECTIONAL CONTROL	Deflector chute for 180° diversion as standard. Spring compensated lever control just behind 3-point hitch.
CASTER WHEELS	Two 13 x 5-6 pneumatic rubber tires.
HEIGHT ADJUSTMENT	0-1.5" (0-4 cm) by .5" (1.3 cm) increments.
TURF PROTECTION	16" (41 cm) long, 4" (10 cm) diameter turf roller behind fan housing. Beveled skid plate under fan housing to prevent damage from high centering. Floating directional deflector chute.
GROUND CLEARANCE	Determined by turf tractor 3-point hitch and caster wheels.
FAN	Radial design with 16" (41 cm) diameter center disc, 8 blades. Outer diameter 24" (61 cm).
FAN HOUSING	Split house - upper housing and lower housing. Upper Housing - 12-gauge steel front and rear plates flanged at separation seam with 12-gauge steel rolled and flanged blower band. Lower housing - 10-gauge steel front and rear plates flanged at separation seam with 12-gauge steel roller and flanged blower band.
DRIVE	Belt drive 4 - 3VX. Power source: 25 PTO hp turf tractor with 3-point hitch and 540 PTO.
WEIGHT	475 lbs. (216 kg)
DIMENSIONS	Length: 32" (81 cm), Width: 54" (137 cm), Height: 42" (107 cm).

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

