



ProCore® 660 & 880 Specifications

PROCORE 660 & 880		
	ProCore 660 #09701	ProCore 880 #09702
WORKING SPEED	0.62-2.5 mph (1-4 km/hr)	0.62-2.5 mph (1-4 km/hr)
TRACTOR SIZE	24-35 hp (17.9-26.1 kW) (use proper ballast) 1,950 lbs. (885 kg) tractor weight min.* 1,150 lbs. (522 kg) min. 3-point lift capacity**	32-42 hp (23.9-31.3 kW) (use proper ballast) 2,600 lbs. (1179 kg) tractor weight min.* 2,000 lbs. (907 kg) min. 3-point lift capacity**
TRACTOR CONNECTION	Category one, three-point linkage, 540 PTO.	Category one, three-point linkage, 540 PTO.
TRACTOR PTO SPEED	540 rpm	540 rpm
AERATING WIDTH	60" (1.5 m)	80" (2 m)
AERATING DEPTH	Up to 4.25" (10.8 cm)	Up to 4.25" (10.8 cm)
NUMBER OF TINE HEADS	6	8
OVERALL WIDTH	72" (1.83 m)	92" (2.32 m)
HEIGHT	34" (86 cm)	34" (86 cm)
LENGTH	33" (84 cm)	33" (84 cm)
WEIGHT	1,220 lbs. (553 kg)	1,570 lbs. (712 kg)
WARRANTY	Two year or 500 hour limited warranty; 120 days for contract, shared ownership or rental use. Refer to operator's manual for further details.	

PRODUCTIVITY RATES PER HOUR			
Side Spacing	Forward Spacing	ProCore 660	ProCore 880
Four available side spacing options:	1.5" (38 mm)	23,008 ft ² (2,137 m ²)	30,217 ft ² (2,807 m ²)
1.2" (30 mm) - mini tine head	2" (51 mm)	30,769 ft ² (2,858 m ²)	40,410 ft ² (3,754 m ²)
1.6" (40 mm) - needle tine head	2.5" (64 mm)	38,531 ft ² (3,579 m ²)	50,604 ft ² (4,700 m ²)
2.4" (62 mm) - 4 tine head	3" (76 mm)	46,015 ft ² (4,274 m ²)	60,433 ft ² (5,613 m ²)
3.2" (81 mm) - 3 tine head	3.5" (89 mm)	53,777 ft ² (4,995 m ²)	70,627 ft ² (6,560 m ²)
	4" (102 mm)	61,261 ft ² (5,690 m ²)	80,456 ft ² (7,473 m ²)
	4.5" (114 mm)	69,300 ft ² (6,437 m ²)	91,014 ft ² (8,454 m ²)
	5" (127 mm)	76,784 ft ² (7,132 m ²)	100,844 ft ² (9,367 m ²)

Note: Specifications and design subject to change without notice.

* Minimum tractor weights without front end weights

** Must meet all tractor requirements for 3-point lift attachments, including proper front end ballast.

