



Reelmaster® 6500-D & 6700-D Specifications*

	REELMASTER 6500-D MODEL 03806, 2WD OR MODEL 03807, 4WD	REELMASTER 6700-D MODEL 03808, 4WD																																			
ENGINE	Kubota® V1505-T liquid-cooled diesel engine. 4-cylinder, over-head valve. 1.5 liter displacement. Turbo-charged. 46 hp (34.3 kW) gross rated, 42 hp (31.3 kW) net at 3000 rpm. 40 amp alternator. Donaldson two-stage air cleaner with safety filler and restriction indicator.																																				
RADIATOR	Rear mounted, cross-flow agricultural type radiator, 7 fins per inch. Cooling system capacity is 3.5 gallons (13.25 liters). Air to oil cooler with 2 rows, 6 fins per inch, mounted in front of radiator tips outward for cleaning. Removable oil cooler/radiator screen.																																				
ELECTRICAL FEATURES	12 volt, 650 cold cranking amperes at 0°F (-18°C), 105 minute reserve capacity at 80°F (27°C), maintenance free battery. 1.4 kW electric starter. 55 amp alternator with I.C. regulator/rectifier. Automotive type electrical system. Seat switch, reel and traction interlock switches.																																				
FUEL SYSTEM	Bosch® in-line fuel injection pump with energized-to-run (ETR) fuel flow solenoid. Replaceable spin-on fuel filter/water separator. Fuel capacity: 15 gallon (57 liter).																																				
CONTROLS	Foot operated traction and brake pedals. Hand operated throttle, traction speed limiter, parking brake latch, ignition switch, single joystick control for cutting unit on/off and lift/lower. Reel speed and backup controls located under the hood.																																				
GAUGES	Hour meter, speedometer, fuel gauge, engine coolant gauge, and warning light cluster: engine oil pressure, high engine temperature, charge indicator, glow plug, water in fuel indicator, low water indicator. Reel control lamp that lights to indicate the reels are not providing desired clip.																																				
DIAGNOSTICS	The Automatic Control Electronics, ACE™ system allows precision timing and control of machine functions for maximum reliability. Optional diagnostic display connects to an electronic control unit to pinpoint any electrical problems quickly and easily. Available DATA LOG™ system allows mechanic to find intermittent problems. Diagnostic test ports are provided for front and rear cutting unit drive, cutting unit lift, steering, and hydrostatic transmission charge pressure.																																				
TRACTION DRIVE	Power to the front drive wheel is via servo-controlled hydrostatic pump operating individual fixed displacement axial piston wheel motors that operate a planetary gear final drive assembly. Foot pedal control of forward/reverse ground speed. Toro 4-Matic® 4WD System only: couples rear drive axle to hydrostatic transmission via overrunning clutch for full time on-demand 4WD. A Roll Over Protection Structure (ROPS) and seat belt are standard on 4WD models.																																				
GROUND SPEED	0-10 mph (0-16.1 km/hr) forward; 0-4 mph (0-6.4 km/hr) reverse.																																				
TIRES/WHEELS/PRESSURE	Two rear steering tires: 20 x 10-10, tubeless, 6-ply rating. Two front traction drive tires: 29 x 14-15, tubeless, 6-ply rating. Recommended tire pressure: 10-15 psi (59-103 kPa).																																				
MAIN FRAME	All welded steel frame includes tie-down loops.																																				
BRAKES	Wet triple disc brakes on front planetary assemblies may be actuated individually for service brakes or locked together for transport or parking brakes. Dynamic braking through hydrostatic traction drive.																																				
STEERING	Power steering with dedicated power source.																																				
SEAT	Deluxe seat with adjustable suspension and fore-aft location. Optional Armrest Kit, Model 30707.																																				
ROPS	A 4-post ROPS with seat belt and optional canopy; standard on Models 03807 and 03808, optional on Model 03806.																																				
OVERALL DIMENSIONS	<table border="1"> <thead> <tr> <th></th> <th>Height</th> <th>Length</th> <th>Transport Width</th> <th>Operational Width</th> <th>Wheel Tread</th> <th>Wheelbase</th> </tr> </thead> <tbody> <tr> <td>Models 03806/03807:</td> <td>60" (152 cm) w/o ROPS</td> <td>120" (305 cm)</td> <td>84" (213 cm)</td> <td>110" (279 cm)</td> <td>72.25" (178 cm) - front</td> <td>58" (147 cm)</td> </tr> <tr> <td></td> <td>84" (213 cm) w/ ROPS</td> <td></td> <td></td> <td></td> <td>41" (104 cm) - rear</td> <td></td> </tr> <tr> <td>Model 03808:</td> <td>84" (213 cm) w/ ROPS</td> <td>120" (305 cm)</td> <td>84" (213 cm)</td> <td>147" (374 cm)</td> <td>72.25 (178 cm) - front</td> <td>58" (147 cm)</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>41" (104 cm) - rear</td> <td></td> </tr> </tbody> </table>			Height	Length	Transport Width	Operational Width	Wheel Tread	Wheelbase	Models 03806/03807:	60" (152 cm) w/o ROPS	120" (305 cm)	84" (213 cm)	110" (279 cm)	72.25" (178 cm) - front	58" (147 cm)		84" (213 cm) w/ ROPS				41" (104 cm) - rear		Model 03808:	84" (213 cm) w/ ROPS	120" (305 cm)	84" (213 cm)	147" (374 cm)	72.25 (178 cm) - front	58" (147 cm)						41" (104 cm) - rear	
	Height	Length	Transport Width	Operational Width	Wheel Tread	Wheelbase																															
Models 03806/03807:	60" (152 cm) w/o ROPS	120" (305 cm)	84" (213 cm)	110" (279 cm)	72.25" (178 cm) - front	58" (147 cm)																															
	84" (213 cm) w/ ROPS				41" (104 cm) - rear																																
Model 03808:	84" (213 cm) w/ ROPS	120" (305 cm)	84" (213 cm)	147" (374 cm)	72.25 (178 cm) - front	58" (147 cm)																															
					41" (104 cm) - rear																																
NET WEIGHT WET	Model 03806: 3,100 lbs. (1,407 kg) with 5-blade cutting units and full fluid levels. Model 03807: 3,200 lbs. (1,453 kg) with 5-blade cutting units and full fluid levels. Model 03808: 3,850 lbs. (1,748 kg) with 5-blade cutting units and full fluid levels.																																				
SOUND LEVEL	82 dB(A) under normal operating conditions.																																				
WARRANTY	Two year limited warranty. Refer to the Operator's Manual for further details.																																				
CERTIFICATION	The Reelmaster 6000 series complies with American National Standards Institute (ANSI B71.4-1999) and European Community (CE) specifications with required weight kits and ballast installed.																																				

* Specifications and design subject to change without notice.



Reelmaster® 6500-D & 6700-D Specifications* (continued)

HYDRAULIC SYSTEM	
PUMP	A three section gear pump provides hydraulic flow to power the cutting units, power steering and cutting unit lift.
CONTROL BLOCKS	All hydraulic functions are controlled by two integrated hydraulic control blocks utilizing cartridge type relief valves, solenoid controlled proportional valves and solenoid operated directional control valves.
REEL SPEED CONTROL	Reel drive circuit is split into front and rear independent circuits. Each circuit has a manually adjustable control for reel speed and backlap adjustment.
LIFT CYLINDERS	The front right and left units and the rear two units are raised by individual cylinders in separate series circuits. The front center unit and outer rear units on Model 03802 are raised individually. All lift and lower sequences are controlled by the ECU.
HYDRAULIC OIL RESERVOIR	100% of oil from reservoir passes through a 100 mesh suction strainer before entering the reel drive circuit. 8.5 gallon (32 liter) capacity.
HYDRAULIC OIL FILTER	11 gram capacity at 10 gallon (37 liter) per minute flow Average Beta = 20 at 3 micron. Filter head has integral 50 psi (3.4 bars) bypass and a true differential pressure service indicator.

5, 7 AND 11 BLADE CUTTING UNITS		
	Reelmaster 6500-D	Reelmaster 6700-D
TYPE	Five 22" (56 cm) width cutting units; fully interchangeable. Front or rear discharge selectable with movable shield.	Seven 22" (56 cm) width cutting units; fully interchangeable. Front or rear discharge selectable with movable shield.
WIDTH OF CUT	96" (244 cm) total.	133" (338 cm) with 7 cutting units, 114.5" (291 cm) with 6 cutting units, or 96" (244 cm) with 5 cutting units.
HOC RANGE	$\frac{3}{8}$ - $1\frac{3}{4}$ " (9.5-44.5 mm) height of cut range. Recommended use: 5-Blade $1-1\frac{3}{4}$ " (25-44 mm); 7-Blade $\frac{1}{2}$ -1" (12-25 mm); 11-Blade $\frac{3}{8}$ - $\frac{5}{8}$ " (9.5-15 mm).	
REEL CONSTRUCTION	All welded construction. 7" (17.8 cm) diameter reels.	
REEL DRIVE	Reel motors feature quick disconnect for removal or installation onto cutting unit. Cutting units can be driven from either end.	
BEDKNIFE/BEDBAR	Single point adjustment mechanism, .0005" (.0127 mm) adjustment per click.	
CLIP FREQUENCY	.375-1.25" (9.5-31.8 mm). Reel speed is manually adjustable to maintain proper clip.	
ROLLERS	Front roller: 3" (7.6 cm) diameter Wiehle roller standard. Rear roller: 3" (7.6 cm) diameter Full roller. All rollers use the same heavy duty ball bearings with two conventional single lip seals and Toro labyrinth seal to provide four sealing surfaces to protect the bearings. Optional 3" (7.6 cm) diameter Full roller is available for the front position.	

GROOMER KIT, MODELS 03810 AND 03811	
CUTTER WIDTH	20" (50.8 cm).
DEPTH PENETRATION	.188-2" (4.8-51 mm) above ground level, at mowing height-of-cut range of $\frac{3}{8}$ -1.75" (9.5-44 mm). Height of Groom (HOG): .188" (4.8 mm) below height of cut when engaged in grass; .25" (6.4 mm) above height of cut when raised out of grass.
CONSTRUCTION	Shaft: fatigue-proof steel hexagon. Blades: heat-treated steel, .042" (1 mm) thick, 2.5" (6.4 cm) diameter, .5" (1.3 cm) spacing between blades.
WEIGHT	15 lbs. (6.8 kg).

ACCESSORIES							
Model No.	Description	Model No.	Description	Part No.	Description	Part No.	Description
03860	5-Blade Cutting Unit	30707	Armrest Kit	94-2836	Rear Weight Kit	100-9920	Rear Roller Scraper Kit
03861	7-Blade Cutting Unit	03872	Thatching Reel	85-4750	Hand Held Diagnostic Tool	100-9908-03	Front Roller Scraper Kit
03862	11-Blade Cutting Unit	03521	TurfDefender™ Leak Detector Kit	03882	RM 5500/6000 Basket	03876	RM 5500/6000 Powered Rear Roller Brush
				When Using Groomers			
				107-9518	Grass Basket		
				108-6743	Mounting Kit		

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your Toro Distributor.

The Reelmaster 6500-D and 6700-D are manufactured in Tomah, WI ISO 9002 Certified Plant.

