



# Workman® 3000 and 4000 Series Specifications\*

	WORKMAN 3200, 2WD, MODEL 07360 WORKMAN 3200, 2WD, W/BED, MODEL 07361 WORKMAN 4200, 4WD, MODEL 07365 LIQUID-COOLED GAS	WORKMAN 3300-D, 2WD, MODEL 07362 WORKMAN 4300-D, 4WD, MODEL 07364 LIQUID-COOLED DIESEL	WORKMAN 3100, 2WD, MODEL 07363 AIR-COOLED GAS
<b>ENGINE</b>	B&S Daihatsu® 950G, 3-cylinder, 4-cycle, liquid-cooled, overhead camshaft, counterbalanced gasoline engine. 31 hp (23.1 kW); governed to a maximum speed of 3600 rpm by an internal mechanical centrifugal governor. 58.1 cu. in. (952 cc) displacement. Rear engine location, direct coupled to a transaxle. 12 volt electric starter and fuel pump. Full pressure lubrication with spin-on oil filter. Exhaust emissions meet C.A.R.B. for specialty vehicle engines and EPA regulations.	B&S Daihatsu® 950D, 3-cylinder, 4-cycle, liquid-cooled, counterbalanced diesel engine. 26.5 hp (19.8 kW); governed to a maximum speed of 3600 rpm by an internal mechanical centrifugal governor. 58.1 cu. in. (952 cc) displacement. Rear engine location, direct coupled to a transaxle. 12 volt electric starter. Full pressure lubrication with spin-on oil filter. 12 volt electric fuel pump with replaceable filter. Replaceable fuel filter/water separator with 3 micron filtration. Exhaust emissions meet C.A.R.B. for specialty vehicle engines and EPA regulations.	Kohler® Model CH23, 2-cylinder, 4-cycle, air-cooled, counterbalanced gasoline engine. 23 hp (17.2 kW) governed to a maximum speed of 3600 rpm by an internal mechanical centrifugal governor. 41.1 cu. in. (674 cc) displacement. Rear engine location, direct coupled to a transaxle. 12 volt electric starter. Full pressure lubrication with spin-on oil filter. Exhaust emissions meet C.A.R.B. for specialty vehicle engines and EPA regulations.
<b>CLUTCH</b>	6.7" (17 cm) clutch and pressure plate.	6.7" (17 cm) clutch and pressure plate.	6.7" (17 cm) clutch and pressure plate.
<b>INSTRUMENT PANEL</b>	Fuel, coolant temperature and hour meter gauges. Warning light cluster includes engine low oil pressure. Tachometer optional.	Fuel, coolant temperature and hour meter gauges, glow plug switch. Warning light cluster includes engine low oil pressure and glow plug light. Tachometer optional.	Fuel and hour meter gauges. Low oil pressure indicator light. Tachometer optional.
<b>BATTERY</b>	12 volt, 690 cold cranking amps at 0°F (18°C).		12 volt, 525 cold cranking amps at 0°F (-18°C).
<b>BED HEIGHT</b>	30" (76 cm)	30" (76 cm)	30" (76 cm)
<b>WHEELS AND TIRES</b>	Front: 20 x 10-10, 4-ply rating, turf tread. Rear: 24 x 12-12, 6-ply rating, turf tread.		
<b>AIR CLEANER</b>	Remote mounted, heavy-duty 2-stage air cleaner with evacuator valve.		Kohler large capacity dual element air cleaner (filter with foam pre-cleaner).
<b>RADIATOR</b>	Mid-mounted with removable screen, lower clean-out access.		Not applicable.
<b>VEHICLE WEIGHT</b>	Model 07360: 1,565 lbs. (710 kg). Model 07361: 1,893 lbs. (859 kg) Model 07365: 1,993 lbs. (904 kg)	Model 07362: 1,929 lbs. (875 kg) Model 07364: 2,029 lbs. (920 kg)	Model 07363: 1,795 lbs. (814 kg)
<b>RATED CAPACITY &amp; MGWW</b>	2WD w/o bed - 2,685 lbs. (1,218 kg) 2WD - 2,357 lbs. (1,069 kg) 4WD - 2,257 lbs (1,024 kg) 2WD Maximum Gross Vehicle Weight (MGVW): 4,250 lbs. (1,928 kg). 4WD Maximum Gross Vehicle Weight (MGVW): 4,250 lbs. (1,928 kg)		2,530 lbs. (1,148 kg) Max Gross Vehicle Weight (MGVW): 4,250 lbs. (1,928 kg).
<b>SOUND LEVEL</b>	83 dB(A) at operator's ear; 3600 rpm. (Bed and sides installed).	88 dB(A) at operator's ear; 3600 rpm. (Bed and sides installed).	83 dB(A) at operator's ear; 3600 rpm. (Bed and sides installed).

SPECIFICATIONS COMMON TO WORKMAN 3000 & 4000 SERIES VEHICLES	
<b>TRANSMISSION/ DRIVE TRAIN</b>	Rear transaxle configuration, twin axle drive. 3-speed synchromesh (forward speeds only), H-shift pattern with high-low range providing 6 forward speeds, 2 reverse. Manual engage rear differential lock. 4WD: Automatic On Demand. Standard 3 <sup>rd</sup> high gear lockout.
<b>SUSPENSION</b>	Front: Independent A-Frame™ control arm, dual progressive coil springs, and dual shock absorbers with anti-sway bar. Rear: Low suspended-mass, DeDion® axle (weight carrying axle is independent of transaxle), leaf springs, and dual shock absorbers.
<b>FRAME</b>	Welded, high-strength steel channels and tubes.
<b>STEERING</b>	Hydraulic power steering, 3-position tilt steering wheel, 13.5" (35 cm) diameter steering wheel, 4 turns lock-to-lock, 17.5 to 1 ratio, 70° (2WD), 50° (4WD).
<b>2-POST ROPS</b>	2-Post Roll Over Protective Structure.
<b>BRAKES</b>	4-wheel hydraulic, dual safety circuit, self-adjusting drum; 8" (20.3 cm) diameter front, 8" (20.3 cm) diameter rear. Hand actuated parking brake actuates rear brake shoes.

\* Specifications and design subject to change without notice.



