

TORO Count on it.

Greensmaster® Walk Mowers



TORO. Count on it.

The legend continues.

Greensmaster Walk Mowers

- Five distinct models
- 18-26" (46-66 cm) width of cut
- Quiet OHV Kawasaki® engine
- Industry's lowest heights of cut

Helping you maintain perfect greens has always been a top priority at Toro.® And our commitment to you is

nothing less than to build the world's best greensmowers. To ensure you have the tools you need to keep your greens in top condition, Toro offers five unique Greensmaster® models designed for superior performance on any type of green.



Count on Performance

In perfect balance.

A front weight bias on the cutting unit eliminates unwanted operator influence. This allows deeper penetration and straighter lines when mowing. Your greens will receive a more uniform cut for a pristine appearance and a performance your patrons will truly appreciate.





The big five.

Every green is different. Whether you want the legendary cut of the 1000, or need to cut new grass cultivars at extremely low heights with the Flex 21, there's a Toro Greensmaster that delivers the results you require.



500

- Free-floating cutting head
- 21" (53.3 cm) width of cut



800

- Narrow stripe with superior ground-following
- 18" (46 cm) width of cut



1000

- Industry's most popular greens mower
- 21" (53.3 cm) width of cut



1600

- Great for aprons, tees and other formal turf
- 26" (66 cm) width of cut



Flex 21

- Unmatched ground following and cut
- 21" (53.3 cm) width of cut



The revolutionary Flex 21.

No greens mower on the market delivers faster, truer greens than the remarkable Toro® Greensmaster® Flex 21. Its flexible cutting unit mounts on a dual-axis suspension and flexible drive shaft couplers for a full range of motion that follows even the most undulating greens. You'll cut closer than ever before on bent grass, Bermuda grass and newer, ultra-dwarf grasses thanks to this innovative design and a constant bedknife attitude.



We found a better way.

It's never been easier to get the cut you want. A dual-function lever on the Greensmaster Flex 21 controls both the traction and reel, allowing you to engage the reel with a simple twist of the wrist. The tapered drum virtually eliminates overlap marking. The Flex 21 sealed bearings never require greasing and eliminate potential damage to greens.



A simple two-bolt connection makes it easy to remove the cutting unit for service and maintenance.



The cutting unit rollers are tucked closer to the reel and separated by a mere 8.25" (21 cm) to prevent scalping.



The bedknife-to-reel adjusts with a simple click.



Flexible drive shaft couplers allow the cutting unit to flex on the center axis.



The dual-function lever puts exceptional control in the palm of your hand.



Neighborhood friendly.

The whisper-quiet performance of the 3.7 hp (2.8 kW) OHV Kawasaki® engine has found fans in both operators and neighbors. The low noise level is safe on your ears and won't wake the neighborhood when mowing in the morning. And to keep technicians happy, the engine design provides easy access to service points while a sealed gearbox and drive belts require no lubricants that could damage greens.



An ergonomic loop handle adjusts to the operator's height quickly and easily without tools.

Accessories

A variety of accessories are available to customize your Greensmaster for your course.

Bedknives



Rollers



Roller scrapers



Grooming reel and brush



Broom kit



Light kit



Other attachments include: Clip kit, hour meter kit, thatching kit

Easy ride.

Toro TransPro™ trailers safely and easily transport walk greens mowers to and from the green. The unique design protects your investment and keeps adjustments in tact. The TransPro 80 accommodates a single Greensmaster with a Flat Ramp or Rail Ramp Kit. For additional time and productivity gains, transport two greens walk mowers (excluding the 1600) with the TransPro 100.



Specifications for Greensmaster® Walk Mowers

Engine

Model: Kawasaki® 4-cycle
Rating: 3.7 hp (2.8 kW)
Displacement: 7.57 cu. in. (124 cc)
Fuel: Unleaded
Cooling: Air

Ground Speed

Mowing: 3.5 mph (5.6 km/h); GR500: 3.8 mph (6.1 km/h)
Transport: 5.3 mph (8.5 km/h)

Weight

500: 186 lbs. (84 kg)
800: 203 lbs. (92.3 kg)
1000: 208 lbs. (94.3 kg)
1600: 230 lbs. (104 kg) w/o transport tires
Flex 21: 238 lbs. (108 kg)

Cutting Units

500

Construction: Cutting unit independent from traction unit and catcher, 3.5" (8.9 cm) diameter
Reel options: 9-blade
Height of cut: $\frac{1}{8}$ - $\frac{1}{16}$ " (3.2-17.5 mm); optional bedknife to $\frac{5}{64}$ " (2.0 mm)
Width of cut: 21" (53.3 cm)
Clip frequency: .197" (5.0 mm)
Bedknife-to-reel adjust: Reel adjusts down to the bedknife through two threaded bolts
Rear roller: Full, 2" (5.1 cm)
Front roller: Standard cast iron Wiehle®

800

Construction: Carbon steel blades
Reel options: 11-blade
Height of cut: $\frac{5}{64}$ -1" (2.0-25.4 mm)
Width of cut: 18" (45.7 cm)
Clip frequency: .16" (4.1 mm)
Bedknife-to-reel adjust: Dual screw "click" adjustment to reel
Front roller: Aluminum Wiehle, 2" (5.1 cm)

1000

Construction: Carbon steel blades
Reel options: 11-blade, optional 8-blade
Height of cut: $\frac{5}{64}$ -1" (2.0-25.4 mm)
Width of cut: 21" (53.3 cm)
Clip frequency: 11-blade: .16" (4.1 mm); 8-blade: .23" (5.8 mm)
Bedknife-to-reel adjust: Dual screw "click" adjustment to reel
Front roller: Aluminum Wiehle, 2" (5.1 cm)

1600

Construction: Carbon steel blades
Reel options: 8-blade
Height of cut: $\frac{1}{8}$ -1 $\frac{1}{2}$ " (3.2-38.1 mm)
Width of cut: 26" (66 cm)
Clip frequency: .23" (5.8 mm)
Bedknife-to-reel adjust: Dual screw "click" adjustment to reel
Front roller: Aluminum Wiehle, 2" (5.1 cm)

Flex 21

Construction: High-strength, low-alloy steel
Reel options: 11-blade, 8-blade optional
Height of cut: $\frac{1}{16}$ - $\frac{3}{4}$ " (1.6-19.1 mm)
Width of cut: 21" (53.3 cm)
Clip frequency: 11-blade: .16" (4.1 mm); 8-blade: .23" (5.8 mm), w/clip kit: .14" or .21" (3.5 mm or 6.4 mm)
Bedknife-to-reel adjust: Dual screw "click" adjustment to reel
Rear roller: Aluminum full, 2" (5.1 cm)
Front roller: Aluminum Wiehle, 2.5" (6.4 cm)

Certification: Meets ANSI specifications B71.4-2004 and CE specifications with required kits installed
Warranty: Two year limited

TORO® PROFESSIONAL SERVICES

Toro Financing A full service offering for all your equipment and irrigation purchases. Flexible financing options can be tailored to meet your operational needs.

Toro Protection Plus Extended Protection Plan Protect your budget and your equipment investment. Plans are available for both new and used equipment, and you can choose from various terms to fit your financing terms.

Toro Genuine Parts Keep the productivity and performance of your equipment at its peak. Learn about Performance Parts pricing and MVP kits. Find replacement parts online at Toro.com/partsviewer.

Toro Training Toro Factory Service Schools are available. Explore the training and customer care areas of Toro.com and ToroNSN.com for readily available education and training materials.

Toro Controller Repair Provides irrigation controller boards ready for immediate board exchange to assure that downtime is minimal and your turf stays protected. Toro is the choice for reliability.

Toro NSN® An industry-first support network that provides reliable, around-the-clock irrigation central control system trouble-shooting and operation assistance. Call 1-800-ASK-TORO.

Products depicted in this brochure are for demonstration purposes only.

Actual products offered for sale may vary.

©2004 The Toro Company, 8111 Lyndale Ave. S., Bloomington, MN 55420-1196
Part No. 04-050-T. Printed in U.S.A.

Toro.com



Count on it.