



Aerothatch 83 & Seeder 93

Provides relief from troublesome thatch and compaction and slit seeds all in one pass.



	AEROTHATCH 83, MODELS 44830		SEEDER 93, MODEL 44835 ^[1]
SWATH	48" (122 cm), 45" (114 cm) blade tip to blade tip.	DRIVE	Ground powered.
SPACING	Model 44830: 3" (7.6 cm)	SEED HOPPER	100 lbs. (45.4 kg) capacity.
HITCH	Standard 3 point hitch, Category 1.	HOPPER AUGER	Metal cogs on a steel shaft.
DRIVE	Std. 1 ³ / ₈ " splined Ag. type drive shaft. PTO to gearbox, sealed bearing and sprocket, #H80 chain to blade shaft.	SEED SHUT OFF	Remote from the operator's position.
GEARBOX	Heavy duty 1:1 right angle reversible gearbox.	SEED TUBES	Delivers seed to 16 discs.
BLADES	(16) 12 ga./10 pt. (Optional: 7 ga. & 10 ga./10 pt.).	FEED OPENINGS	Adjustable to the desired rate.
BLADE SHAFT	1.5" (38 mm) square high carbon steel.	DIMENSIONS	Height: 33" (84 cm). Length: 13" (33 cm) Width: 56" (142 cm)
BLADE DEPTH	0-3" (7.6 cm) in 1/4" (6.3 mm) increments.	SHIPPING WEIGHT	300 lbs. (136 kg)
FRAME	All welded steel construction.	OPTIONAL	Drag Mat, 72-002-0021.
ROLLER	Full width, 3.5" (8.9 cm) dia. roller with sealed bearings. Roller is integral with the skid shoes and spring loaded wiper for full width of roller.		
DIMENSIONS	Height: 36" (91 cm) (with 3 pt. hitch). Length: 57" (145 cm). Width: 60" (152 cm).		
SHIPPING WEIGHT	550 lbs. (250 kg)		

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.
[1] Must be used with 44830 Aerothatch.

