



Line Painter 1200

Destined to change the way you paint sports fields, the revolutionary new Line Painter 1200 delivers unparalleled productivity and precision.



LINE PAINTER 1200	
ENGINE	Kawasaki® FJ180V, 6.5 hp (4.8 kW), 180 cc, dual-element air cleaner. 1 gallon (3.8 liter) fuel tank.
TRANSAXLE	3-speed gear-drive with neutral and reverse.
WHEELS	Front: 10 x 3.5" (25.4 x 8.9 cm), pneumatic; Rear: 13.5 x 5" (34.3 x 12.7 cm), pneumatic.
FRAME	Welded sheet steel and tube construction, integral trailer tie-downs.
CONTROLS/GAUGES	On/off ignition key switch, 3-speed transaxle shift lever with neutral and reverse, traction drive lever, spray on/off lever, flush/paint lever, parking brake lever, caster unlock lever.
WALKING SPEEDS	1st gear: 1 mph (1.6 km/h); 2nd gear: 2.1 mph (3.4 km/h); 3rd gear, transport: 4 mph (6.4 km/h); Reverse: 1 mph (1.6 km/h).
GROUND PRESSURE	Less than 15 psi (1.0 bar).
FLUSH SYSTEM	Express Clean System.
DIMENSIONS & WEIGHT	Length: 64" (162.6 cm) including handles; Width: 29" (73.7 cm) outside wheels, 36" (91.4 cm) including spray head; Height: 46" (116.8 cm); Wheelbase: 22" (55.9 cm); Weight: 240 pounds (108.9 kg), dry.
PUMP	Belt-driven five chamber diaphragm with welded diaphragm reinforcing shield. Flow: 4.5 gpm (17 liters/min) free-flow, 4 gpm (15 liters/min) @ 30 psi (2.1 bar). Operating pressure range: 20-40 psi (1.4-2.8 bar), 55 psi (3.8 bar) full bypass. Excess spray flow returns to tank for paint agitation.
NOZZLE	Double fan pattern, 2-6" (5.1-15.2 cm) wide.
PAINT PRE-MIX	Dilute with water to suit the application.
FRESH WATER RINSE	On board system, tank capacity: 2 gallons (7.6 liters). Capable of 4 rinse cycles per fill/tank.
PAINT TANK	Roto-molded polyethylene construction, 12 gallon (45 liter) capacity, 18 mesh strainer basket, drain valve located high enough to discharge into a standard 5 gallon (19 liter) pail.
ATHLETIC FIELD MARKING PAINT	Toro Xtreme and Toro XtremePlus are both formulated to be easy to use: pre-mixing not required, dilutes easily with water, and provides brilliant white lines. Xtreme can be diluted up to 5:1, and XtremePlus up to 15:1. Standard colors are white, yellow, red, blue, green and black. Color can be customized to match your team and school logo.
ATTACHMENTS/ACCESSORIES	On-board storage container, selection of spray nozzles, hand-held spray gun, sully.
CERTIFICATION	ANSI B71.4 where applicable, CE compliant, Machinery directive.
WARRANTY	2-year for the machine, excluding wear parts.

* Specifications and design subject to change without notice.

The Line Painter 1200 is manufactured in Tomah, WI ISO 9002 Certified Plant.

