



Multi Pro® 1200 & 1250

Dependable work vehicles featuring Spray Pro™ - the most accurate and precise turf spraying system available for your liquid application requirements. Multi Pro delivers the ultimate in precision, simplicity and convenience.



MULTI PRO 1200, MODEL 41178, MULTI PRO 1250, MODEL 41177					
VEHICLE	4-wheel, rear wheel drive, front steer, single operator turf sprayer.				
ENGINE	20 hp (14.9 kW) Kohler® V-Twin horizontal shafts governed to 3,350 rpm, w/30 amp alternator, accel. pump carburetor.				
BATTERY	12 volt with 540 cold cranking amps @ 0°F (-18°C).				
FUEL CAPACITY	6 gallon (23 liter).				
SUSPENSION	Front: Fully independent rubber torsion swing arm. Rear: Rigid.				
STEERING	Hydraulic power, center pivot linkage, 60° steering angle 8' or 96" (2.4 m) inside turning radius, 77" (2.3 m) rear tire radius.				
TIRES	Front: 18 x 9.5-8 slick. (2) Rear: 24 x 13-12 Multi-Trac. (2)				
BRAKES	4-wheel hydraulic drum type with dual chamber master cylinder.				
LIGHTS	Twin halogen headlights.				
TRANSMISSION	Integrated transaxle with 3 forward speed ranges and reverse.				
GROUNDSPEED	1st speed range: 0-3.1 mph (0-4.9 km/h). 2nd speed range: 0-5.0 mph (0-8 km/h). 3rd speed range: 0-11.0 mph (0-17.6 km/h).				
CLUTCH	Centrifugally engaged variable belt drive (CVT).				
SPRAY BOOM (STANDARD)	Standard 18.5' (5.6 m) working width, 3-section triangular truss open boom. Bi-directional breaks away. Raise criss-cross for storage and transportation. Optional electric boom lift, enclosed boom and Sonic Boom™ for added lift.				
SPRAY NOZZLES	Color-coded, stainless steel, drift reduction mounted on triple nozzle bodies. Quick disconnect with diaphragm check valve.				
SPRAYER TANK	175 gallon (662 liter) polyethylene tank, inductive agitation, includes imbedded 20 gallon (75 liter) rinse tank and 5 gallon (18 liter) fresh water tank. Low profile. Translucent w/fill level gauge.				
SPRAY PUMP	Dual diaphragm pump, proportional ground speed control system. 21.5 gpm (81.3 liter/min) output, capacity range up to 220 psi (15 bar) max.				
SPRAY CONTROLS	Electronic switches on Multi Pro 1250. Manual levers and dial on Multi Pro 1200.				
SPRAY MONITOR	Spray Pro™ fully functional with liquid crystal display. Back lit for late evening/early morning operation.				
DIMENSIONS	Overall Width: 69" (175 cm). Overall Length: 133" (337 cm) w/spray system. Height: 94" (238 cm). Ground Clearance: 4.5" (11.4 cm). Wheelbase: 58" (147 cm).				
WEIGHT	Base unit with standard spray system and operator: (empty vehicle) 2,261 lbs. (1,025 kg); (full w/operator) 3,861 lbs. (1,751 kg). MGWV: 4,136 lbs. (1,888 kg).				
CERTIFICATION	SAE J2258 and machinery directive 98/37 EC.				
WARRANTY	Two year limited warranty. See operations manual for details.				
OPTIONS					
Model	Description	Model	Description	Model	Description
41024	Single Nozzle kit	41133	Spray Gun Kit	41361	ROPS
41135	Elec. Hose Reel Kit	41228	Foam Marker	106-4842	Rinse Kit
41607	Pro-Foam	41157	Pro-Foam Concentrate		

* Specifications and design subject to change without notice.

A Safety Reminder: Prior to any application, know the chemical content and the manufacturer's recommendation for protective clothing. Always wear proper clothing and mask when applying chemicals.

The Multi Pro 1200 & 1250 are manufactured in Tomah, WI ISO 9002 Certified Plant.

