



Workman® 1110 & 2110 Specifications*

	WORKMAN 1100, MODEL 07252	WORKMAN 2110, MODEL 07277
ENGINE	357cc single-cylinder, Kohler® Command Pro™	480cc 2-cylinder, Briggs and Stratton® Vanguard®
TRANSMISSION	Continuously variable belt drive.	
REAR SUSPENSION	Proprietary Active In-Frame.™	
FRONT SUSPENSION	Proprietary torsional independent "A"-Frame.™	
MAX SPEED	14 mph (22.4 km/h) governed.	16 mph (25.6 km/h) governed.
BRAKES	Rear wheel mechanical drum.	Front: 8" (20.3 cm) self-cleaning hydraulic disc brake. Rear: hydraulic drum brake.
FRAME	Steel unibody, dipped e-coat.	
GROUND CLEARANCE	Front: 7.75" (19.7 cm), Rear: 6.5" (16.5 cm)	Front: 9" (22.9 cm), Rear: 7" (17.8 cm)
TIRES	Front: 22 x 9.5-10, 4-ply, Rear: 22 x 9.5-10, 4-ply.	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply.
FUEL CAPACITY	7 gallon (26.5 liters)	
DIMENSIONS	Width 59" (150 cm)	Length 115" (292 cm)
		Wheel Base 79" (201 cm)
STEERING ANGLE	70°	
TURNING CLEARANCE CIRCLE	Inside rear tire: 39" (99 cm), inside front tire: 150" (381 cm), outside rear tire: 158" (401 cm), outside front tire: 227" (577 cm).	
CORROSION RESISTANCE	Body and bed constructed of dent and corrosion resistant polyethylene. Frame is dipped e-coat so internal and external surfaces are treated.	
CARGO BED SIZE	Length: 49" (124 cm), Width: 52" (132 cm), Height: 10" (25 cm), double walled, polyethylene.	
TOTAL CAPACITY	1,250 lbs. (567 kg)	1,650 lbs. (750 kg)
CARGO BED CAPACITY	850 lbs. (386 kg)	1,250 lbs. (567 kg)
TRAILER TOWING CAPACITY	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 800 lbs. (363 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 1200 lbs. (545 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.
OPTIONAL ACCESSORIES	Canopy, solid & folding windshield, electric bed lift, HD bumper, brush guard, Rahn® groomer, roll-over protection, signal light kit, brake/tail light kit, stakes sides, cab, snow plow, deluxe refreshment center, portable refreshment center, slant board, heater kit, vinyl enclosure, heavy duty receiver hitch, rear lift kit.	
WARRANTY	Two year limited warranty. Refer to the Operator's Manual for further details.	

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

The Workman utility vehicle is manufactured in Tomah, WI ISO 9002 Certified Plant.

