



AUTOMATIC TRANSMISSIONS

Choose between an Automatic CVT or Hydrostatic transmission – both come with **cruise control** as standard equipment. **Foot pedal operation** allows you to drive just like a car – and continually vary your mowing speed up to 5.5mph.

POWERFUL ENGINES

Choose between powerful Briggs and Stratton® Intek® or premium Kohler® engines for long life and dependability. Standard features include OHV design with **spin-on oil filter**, **cast iron cylinder** sleeve and **hourmeter** to remind you of important service maintenance intervals.

3-IN-1 CUTTING DECKS

Choose between 42" 2-blade or 46" 3-blade cutting decks which include a convenient **deck washout port** (select models) to make cleaning the underside of the mowing deck easy. Add-on a mulch kit or twin-bagging system for a great looking lawn all season.

2 YEAR LIMITED WARRANTY†

LX Series Lawn Tractors

Power. Performance. Value.



Count on it.

TORO

Count on it.

LX Series Lawn Tractors

Specifications

ATTACHMENTS & ACCESSORIES



Make your lawn tractor a multi-purpose tool with several popular tow-behind attachments. Ask your dealer for more details.



MODEL	LX426	LX425	LX466	LX468
ENGINE*	20 hp* B&S® Intek Single-Cylinder Engine	20 hp* Kohler® Courage Single-Cylinder Engine	22 hp* B&S Intek Twin-Cylinder Engine	22 hp* Kohler® Courage Twin-Cylinder Engine
Construction	OHV, Cast Iron Sleeve, Full Pressure Lube w/ Filter	OHV, Twin Cam, Cast Iron Sleeve, Full Pressure Lube w/ Filter	OHV, Cast Iron Sleeves, Full Pressure Lube w/ Filter	OHV, Cast Iron Sleeves, Full Pressure Lube w/ Filter
TRANSAXLE				
Type	Automatic CVT	Automatic CVT	Hydrostatic	Hydrostatic
Ground Speed - F/R	0 - 5.5 mph / 0 - 2.3 mph	0 - 5.5 mph / 0 - 2.3 mph	0 - 5.5 mph / 0 - 2.3 mph	0 - 5.5 mph / 0 - 2.3 mph
EQUIPMENT				
KeyChoice® System	Standard	Standard	Standard	Standard
Front Axle Construction	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Ignition	Electronic Keystart	Electronic Keystart	Electronic Keystart	Electronic Keystart
Hour Meter	Standard	Standard	Standard	Standard
Cruise Control	Standard	Standard	Standard	Standard
PTO Clutch	Manual	Manual	Manual	Electric
Steering	13" Standard	13" Soft Touch	13" Standard	13" Soft Touch
Mowing Deck	42" / 2-Blade Cutting Deck	42" / 2-Blade Cutting Deck	46" / 3-Blade Cutting Deck	46" / 3-Blade Cutting Deck
Headlights	Standard	Standard	Standard	Standard
Cupholder	Standard	Standard	Standard	Standard
Seat	Medium Back	Medium Back	Medium Back	High Back
Tires	15 x 6 Front 20 x 8 Rear	15 x 6 Front 20 x 8 Rear	15 x 6 Front 20 x 8 Rear	15 x 6 Front 20 x 8 Rear
Bumper	Optional	Optional	Optional	Optional
Grab Handles	N/A	Standard	Standard	Standard
Warranty†	2-Year Limited	2-Year Limited	2-Year Limited	2-Year Limited
SPECIFICATIONS				
Fuel Capacity	3 Gallons	3 Gallons	3 Gallons	3 Gallons
Turning Radius	18"	18"	18"	18"
Height of Cut	1.5" - 4"	1.5" - 4"	1.5" - 4"	1.5" - 4"
Wheel Base	48"	48"	48"	48"
Length, Width, Height	71" x 38" x 42"	71" x 38" x 42"	71" x 38" x 42"	71" x 38" x 42"
Weight (estimated)	575 lbs.	575 lbs.	630 lbs.	630 lbs.
Attachments	42" Mulch Kit 42" Twin Bagger 42" Snowthrower 46" Dozer Blade	42" Mulch Kit 42" Twin Bagger 42" Snowthrower 46" Dozer Blade	42" Mulch Kit 42" Twin Bagger 42" Snowthrower 46" Dozer Blade	42" Mulch Kit 42" Twin Bagger 42" Snowthrower 46" Dozer Blade

➔ = Feature Enhancement

† See owner's manual for details on warranty coverage

Disclaimer: *This engine was manufactured and laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission, and operating requirements, the actual horsepower on this class of mower will be significantly lower.

© 2008 The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

490-7718