

	GrandStand Stand-On	Z Master G3 Base Models	Z Master G3 Deluxe Models	Z Master G3 Deluxe – Big Block				
POWER SYSTEM								
Commercial Engine	19 hp Kawasaki® KAI 23 hp Kawasaki	23 hp Kohler® Command 25 hp Kohler Command 27 hp Kohler Command Pro	23 hp Kawasaki 27 hp Kawasaki 29 hp Kawasaki (60", 72")	34 hp Kawasaki				
Heavy-Duty Canister Air Cleaner	Optional	Optional on 23 and 25 hp Standard on 27 hp	Standard	Standard				
Drive Tires	20" X 10" – 8"	23" x 9.5" – 12" 24" x 12" – 12" (60")	23" x 9.5" – 12" 24" x 12" – 12" (60", 72")	24" x 12" – 12"				
Tread Pattern	Turf Master	Turf Master	Multi Trak	Multi Trak				
Caster Tires	11" X 4" – 5" Flat-Free Semi-Pneumatic	13" X 5" – 6" (48") 13" X 6.5" – 6" (52", 60") Flat-Free Semi-Pneumatic	13" X 5" – 6" (48") 13" X 6.5" – 6" (52", 60", 72") Flat-Free Semi-Pneumatic	13" X 6.5" – 6" Flat-Free Semi-Pneumatic				
Fuel/Capacity	Gas/6.8 gal	Gas/12 gal	Gas/12 gal	Gas/12 gal				
Digital Hour Meter	Standard	Standard	Standard	Standard				
Fuel Gauge	Standard	Standard	Standard	Standard				
Hydraulic Drive System	Independent Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors				
Pump	10cc/rev	12cc/rev (shock valves on 60")	12cc/rev (48", 52") 16cc/rev (60", 72")	16cc/rev				
Wheel Motor	12 cir	14.6 cir	14.6 cir (48", 52") 17.1 cir (60", 72")	17.1 cir				
Maximum Forward Speed	8 mph	10 mph	10 mph (12cc); 11.5 mph (16cc)	11.5 mph				
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic				
MOWING DECKS								
Available Deck Widths	48" 52"	48" 52" 60"	48" 52" 60" 72"	60" 72"				
Cutting Deck	TURBO FORCE®	TURBO FORCE	TURBO FORCE	TURBO FORCE				
Bull-nose Bumper	Standard	Standard	Standard	Standard				
Adjustable Discharge Baffle	Standard	—	Standard	Standard				
Rubber Discharge Chute	Standard	Standard	Standard	Standard				
Deck Lift Design	Gas Spring	Extension Spring	Torsion Spring	Torsion Spring				
1" Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard				
Spindle Bearings (Greaseable)	Ball Bearings	Ball Bearings	Tapered Roller Bearings	Tapered Roller Bearings				
Cutting Height	1.0" – 5.0"	1.0" – 5.5"	1.0" – 5.5"	1.0" – 5.5"				
Blades	1/4" heat-treated steel	1/4" heat-treated steel	1/4" heat-treated steel	1/4" heat-treated steel				
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min				
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt				
Anti-Scalp Rollers (48") Anti-Scalp Rollers (52") Anti-Scalp Rollers (60", 72")	—	3 standard, 1 optional 3 standard, 2 optional 4 standard, 2 optional	3 standard, 1 optional 3 standard, 2 optional 4 standard, 2 optional	4 standard, 2 optional				
Carrier Frame Construction	3" X 1.5" X 12 gauge	3" X 1.5" X 12 gauge	3" X 1.5" X 12 gauge	3" X 1.5" X 12 gauge				
FEATURES								
Steering Controls	Twin Lever w/ Variable Speed Control	1-5/8" diameter grips adjustable, dampened	1-5/8" diameter grips adjustable, dampened	1-5/8" diameter grips adjustable, dampened				
Operator Seat	Foldable Operator Platform w/ Operator Platform Suspension	Two-Tone Bolstered w/ 3-D Isolation	Two-Tone Bolstered w/ 3-D Isolation	Two-Tone Bolstered w/ 3-D Isolation				
Arm Rests	—	Standard	Standard	Standard				
Seat Suspension System	—	Optional	Optional	Optional				
Folding ROPS	—	Standard	Standard	Standard				
Storage Compartment	—	Standard	Standard	Standard				
Foot Pedal Deck Lift	—	Standard	Standard	Standard				
Z Stand	—	Optional	Optional	Optional				
Floor Pan	—	Pierced, extruded tread No-tools deck access	Pierced, extruded tread No-tools deck access	Pierced, extruded tread No-tools deck access				
MODELS								
	Weight	ROPS Height Folded	ROPS Height Upright	Deck Width	Deflector Width	Length	Length Platform Up	Length Platform Down
74558 GrandStand – 19 hp Kaw/48" TF Deck	838 lbs.	—	—	49.5"	63.5"	—	59"	74"
74559 GrandStand – 19 hp Kaw/52" TF Deck	849 lbs.	—	—	53.5"	67.5"	—	59"	74"
74568 GrandStand – 23 hp Kaw/48" TF Deck	855 lbs.	—	—	49.5"	63.5"	—	59"	74"
74569 GrandStand – 23 hp Kaw/52" TF Deck	866 lbs.	—	—	53.5"	67.5"	—	59"	74"
74901 Z Master G3 – 23 hp Koh/48" TF Deck	1120 lbs.	46.8"	70.5"	54"	63.6"	79.2"	—	—
74903 Z Master G3 – 25 hp Koh/52" TF Deck	1168 lbs.	46.8"	70.5"	57.5"	67.6"	79.2"	—	—
74915 Z Master G3 – 27 hp Koh/60" TF Deck	1216 lbs.	46.8"	70.5"	61.7"	75.7"	83.1"	—	—
74921 Z Master G3 – 23 hp Kaw/48" TF Deck	1158 lbs.	46.8"	70.5"	54"	63.6"	79.2"	—	—
74923 Z Master G3 – 27 hp Kaw/52" TF Deck	1206 lbs.	46.8"	70.5"	57.5"	67.6"	79.2"	—	—
74925 Z Master G3 – 29 hp Kaw/60" TF Deck	1254 lbs.	46.8"	70.5"	61.7"	75.7"	83.1"	—	—
74927 Z Master G3 – 29 hp Kaw/72" TF Deck	1334 lbs.	46.8"	70.5"	73.6"	87.6"	86.1"	—	—
74935 Z Master G3 – 34 hp Kaw/60" TF Deck	1269 lbs.	46.8"	70.5"	61.7"	75.7"	83.1"	—	—
74937 Z Master G3 – 34 hp Kaw/72" TF Deck	1349 lbs.	46.8"	70.5"	73.6"	87.6"	86.1"	—	—

The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.