

Z MASTER® G3

PERFORMANCE & HIGH-PERFORMANCE SERIES

The Toro Z Master G3 is Toro's most advanced zero-turning radius mower. Everything designed into this series was developed with the landscape contractor in mind. It's technology that refines the Z Master to make a great commercial mower even better.

OUTSTANDING PERFORMANCE

Z Master G3 models have a low center of gravity, adding more stability for greater handling on hills. And while maneuverability on Z Master mowers has always been outstanding, now it's simply superior.

IMPROVED COMFORT

Not only will you be comfortable choosing a G3, you'll be comfortable riding one. The custom seat features large bolsters, thick cushions and 3-D isolator mounts to absorb bumps and reduce operator fatigue.

TURBO FORCE® CUTTING TECHNOLOGY

For ultimate jobsite productivity, the patented TURBO FORCE adjustable front baffle lets you quickly modify the cutting chamber to deliver a superior cut regardless of the mowing conditions. Through long, wet grass, different types of turf and changing seasons, you'll get a cut you can be proud of every time - the kind that builds business and keeps it. Bottom line, you can deliver the quality customers demand with the speed you need to boost productivity.



TORO.


Z MASTER G3 ENGINE*	PERFORMANCE SERIES	HIGH PERFORMANCE SERIES
	74901 23 hp Kohler® Command 48" 74903 25 hp Kohler Command 52" 74915 27 hp Kohler Command Pro 60"	74922 24 hp Kawasaki® 48" 74923 27 hp Kawasaki 52" 74925/74927 29 hp Kawasaki 60"/72" 74926/74928 29 hp Kohler EFI 60"/72" 74935/74937 34 hp Kawasaki 60"/72"
Heavy-Duty Canister Air Cleaner	Standard	Standard
Drive Tires	23" x 9.5" - 12" (48", 52") 24" x 12" - 12" (60")	23" x 9.5" - 12" (48", 52") 24" x 12" - 12" (60", 72")
Caster Tires	13" x 5" - 6" (48") 13" x 6.5" - 6" (52", 60") Flat-free semi-pneumatic	13" x 5" - 6" (48") 13" x 6.5" - 6" (52", 60", 72") Flat-free semi-pneumatic
Fuel Capacity	12 gallons, single-point fill	12 gallons, single-point fill
Digital Fuel Gauge	Standard	Standard
Digital Hour Meter	Standard	Standard
Max Ground Speed (Fwd)	10 mph	11.5 mph (16cc); 10 mph (12cc)
Hydraulic Drive System	Unitized pumps & wheel motors	Unitized pumps & wheel motors
Pump	12cc/rev (shock valves on 60")	12cc/rev (48"/52") 16cc/rev (60"/72")
Wheel Motor	14.6 cir motor	14.6 cir motor (48"/52") 17.1 cir motor (60"/72")
Deck Widths	48" / 52" / 60"	48" / 52" / 60" / 72"
Cutting Deck	Patented TURBO FORCE®	Patented TURBO FORCE
Deck Depth	5.5" deep	5.5" deep
Deck Construction	7-gauge high-strength steel	7-gauge high-strength steel
Bull-nose Bumper	7-gauge high-strength steel	7-gauge high-strength steel
Adjustable Discharge Baffle	Standard	Standard, tools-free adjustment
Rubber Discharge Chute	Standard	Standard
1" Heavy-Duty Spindle Shaft	Standard	Standard
Spindle Bearings	Greaseable	Greaseable
Deck Lift Assist Pedal	Standard	Standard
Cutting Height	1.0" - 5.5"	1.0" - 5.5"



RELIABILITY TO THE CORE

Toro Z Master® G3 models come with a five-year/1,200-hour limited warranty, two-year commercial engine warranty and lifetime frame warranty. See your Toro dealer for details.

Z MASTER® G3 FEATURES



TOUGH SPINDLE ASSEMBLIES

Toro's rugged spindle assemblies survive impacts that would destroy lesser spindles. A stout cast iron housing with a massive base absorbs impact loads and distributes them across a broader area of the deck shell.




SMOOTH, POWERFUL RESPONSE

The unitized pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



EVERYTHING AT A GLANCE

The easy-to-see instrument panel includes a digital hour meter, fuel gauge, voltage meter and diagnostic indicators. All the information you need is available at a glance.



TURBO FORCE® DECKS – UNMATCHED DURABILITY

The fabricated deck shell of the TURBO FORCE deck is constructed of 7-gauge, high-strength steel that's 33% thicker and 32% higher in yield strength than ordinary 10-gauge commercial steel used in 7/10 decks. The combined effect is a deck shell that is 75% stronger, so it easily handles the most demanding conditions and resists damage from impacts and abrasion. The deck is further reinforced by the bull-nose front bumper, a 1/2" trim side wear guard, and a 3/8" thick plate around the discharge opening.

490-8206NA ©2010 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

* The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.