



DINGO 322, 320D SPECIFICATIONS

MODEL	DINGO 322, 22305
ENGINE	Kohler® Command PRO™ Series 22 hp
COOLING SYSTEM	Air cooled
FUEL TANK	2 tanks: 4 gallon (15 liter) capacity each
OIL CAPACITY	2 quarts (1.9 liter)
AIR FILTER	High capacity dry-type remote air cleaner
GROUND SPEED	0-3 mph forward/reverse
HYDRAULIC SYSTEM	
PRESSURE	3000 psi system relief pressure
FLOW	3.7 gpm low flow hydraulic circuit, 8.4 gpm high flow hydraulic circuit
RESERVOIR CAPACITY	14.8 gallon (56 liter)
FILTER	10-micron replaceable hydraulic filter
ELECTRIC SYSTEM	
BATTERY	12 volt, 380 cca
INTERLOCKS	Auxiliary valve neutral to start, traction valve neutral to start
INDICATORS	N/A
GLOW PLUGS	N/A
WHEELS AND TIRES	
STANDARD RIMS	10 x 6.00, 5-bolt, drop center
STANDARD TIRES	18 x 8.50-10, 8 ply, SSL-LSW, pneumatic
CONTROLS	Key, throttle, choke
STEERING	Zero turning type with two control levers, push for forward, pull back for reverse
LOADER/HYDRAULIC SYSTEM	Two control levers push forward to lower/dump, pull back to raise/curl, auxiliary lever for hydraulic attachments; high flow/ low flow selector valve lever; hydraulic flow proportioning valve lever
DIMENSIONS	
WHEELBASE	28" (71 cm)
GROUND CLEARANCE	5" (13 cm) front, 5" (13 cm) rear
OVERALL LENGTH	62" (157.5 cm); 82.2" (208.8 cm) w/bucket
OVERALL WIDTH	40.5" (109.9 cm) standard tires 35" (90 cm) narrow tires
OVERALL HEIGHT	48.7" (123.7 cm)
OPERATING HEIGHT	91.2" (231.6 cm)
HINGE PIN HEIGHT	66" (167.6 cm) std. bucket – highest position
DUMP HEIGHT	47" (119 cm) std. bucket
DUMP ANGLE	34° std. bucket
REACH – MAX	28" (71.1 cm) std. bucket
REACH – FULLY RAISED	26" (66 cm) std. bucket
TIP CAPACITY	1030 lb. (467 kg) w/ 200 lb. (91 kg) operator
RATED OPERATING CAPACITY	515 lb. (234 kg) w/ 200 lb. (91 kg) operator
WEIGHT (W/O BUCKET)	1522 lb. (690 kg)
WEIGHT (W/ STD. BUCKET)	1668 lb. (757 kg)
ENGINE WARRANTY*	Two year
PRODUCT WARRANTY*	One year

MODEL	DINGO 320D, 22303
ENGINE	Kubota D722-E 20 hp
COOLING SYSTEM	Liquid cooled
FUEL TANK	1 tank: 4 gallon (15 liter) capacity
OIL CAPACITY	.84 gallon (3.2 liter)
AIR FILTER	High capacity dry-type remote air cleaner
GROUND SPEED	0-3 mph forward/reverse
HYDRAULIC SYSTEM	
PRESSURE	3000 psi system relief pressure
FLOW	3.7 gpm low flow hydraulic circuit, 8.5 gpm high flow hydraulic circuit
RESERVOIR CAPACITY	14.8 gallon (56 liter)
FILTER	10-micron replaceable hydraulic filter
ELECTRIC SYSTEM	
BATTERY	12 volt, 435 cca
INTERLOCKS	Auxiliary valve neutral to start, traction valve neutral to start
INDICATORS	Warning lamp cluster
GLOW PLUGS	Automatic glow plug timer
WHEELS AND TIRES	
STANDARD RIMS	10 x 6.00, 5-bolt, drop center
STANDARD TIRES	18 x 8.50-10, 8 ply, SSL-LSW, pneumatic
CONTROLS	Key, throttle
STEERING	Zero turning type with two control levers, push for forward, pull back for reverse
LOADER/HYDRAULIC SYSTEM	Two control levers push forward to lower/dump, pull back to raise/curl, auxiliary lever for hydraulic attachments; high flow/ low flow selector valve lever; hydraulic flow proportioning valve lever
DIMENSIONS	
WHEELBASE	28" (71 cm)
GROUND CLEARANCE	5" (13 cm) front, 5" (13 cm) rear
OVERALL LENGTH	62" (157.5 cm); 82.2" (208.8 cm) w/bucket
OVERALL WIDTH	40.5" (109.9 cm) standard tires 35" (90 cm) narrow tires
OVERALL HEIGHT	48.7" (123.7 cm)
OPERATING HEIGHT	91.2" (231.6 cm)
HINGE PIN HEIGHT	66" (167.6 cm) std. bucket – highest position
DUMP HEIGHT	47" (119 cm) std. bucket
DUMP ANGLE	34° std. bucket
REACH – MAX	28" (71.1 cm) std. bucket
REACH – FULLY RAISED	26" (66 cm) std. bucket
TIP CAPACITY	1048 lb. (476 kg) w/ 200 lb. (91 kg) operator
RATED OPERATING CAPACITY	524 lb. (238 kg) w/ 200 lb. (91 kg) operator
WEIGHT (W/O BUCKET)	1722 lb. (781 kg)
WEIGHT (W/ STD. BUCKET)	1868 lb. (847 kg)
ENGINE WARRANTY*	Two year
PRODUCT WARRANTY*	One year