



DINGO TX 420 SPECIFICATIONS

MODEL	DINGO TX 420, 22306
ENGINE	Kohler® Command PRO™ Series 20 hp
COOLING SYSTEM	Air cooled
FUEL TANK	1 tank: 6 gallon (22.7 liter) capacity
OIL CAPACITY	2 quarts (1.9 liter)
AIR FILTER	Standard dry-type air cleaner
HYDRAULIC SYSTEM	
PRESSURE	3000 psi system relief pressure
FLOW	11.2 gpm
RESERVOIR CAPACITY	8 gallons (30.3 liters)
FILTER	10-micron replaceable hydraulic filter
ELECTRIC SYSTEM	
BATTERY	12 volt, 450 cca
INTERLOCKS	Auxiliary valve neutral to start, traction valve neutral to start
TRACK	
STANDARD	Endless Kevlar™ reinforced rubber 96.6" x 5.88", single internal tooth drive
TRACK DRIVE	
STANDARD	Sprocket – Drive, 10 uhmw road wheels per side, steel track guide
TRACTION	Dual hydrostatic pump
CONTROLS	Key, throttle, choke
STEERING	Single control with reference bar
LOADER / HYDRAULIC SYSTEM	Joystick control for all functions, raise/lower, dump/curl and float. Two step motion control for auxiliary hydraulics
PARKING BRAKE	Single lever pin in hole system
INDICATORS	Audio and visual warning with set point at 235° F for hydraulic system
DIMENSIONS	
WHEELBASE	31.1" (79 cm)
GROUND CLEARANCE	4.6" (11.7 cm)
OVERALL LENGTH	92" (233.7 cm)
OVERALL WIDTH	33.7" (85.6 cm)
OVERALL HEIGHT	46.1" (117.1 cm)
OPERATING HEIGHT	90.1" (229 cm)
HINGE PIN HEIGHT	65.8" (167.1 cm)
DUMP HEIGHT	46.1" (117.1 cm)
GROUND SPEED	0-4.5 mph forward, 0-2 mph reverse
DUMP ANGLE	34°
REACH	21.8" (54.4 cm)
TIP CAPACITY	1480 lbs. (671.3 kg)
RATED OPERATING CAPACITY	500 lbs. (226.8 kg)
WEIGHT (W/ NARROW BUCKET)	1950 lbs. (884.5 kg)
WEIGHT (W/O NARROW BUCKET)	1830 lbs. (830 kg)
ENGINE WARRANTY*	Two year
PRODUCT WARRANTY*	One year