

	TimeCutter® SS				TimeCutter® MX						
MODELS	SS3225 74710	SS4200 74711	SS4225 74726	SS5000 74731	MX3450 74750	MX4200 74766	MX4250 74760	MX5000 74775	MX5050 74776	MX5075 74768	MX6050 74777
Price	\$2,399.00	\$2,299.00	\$2,499.00	\$2,899.00	\$3,299.00	\$2,799.00	\$3,599.00	\$3,199.00	\$3,499.00	\$3,999.00	\$4,299.00
Engine¹ at 3,600 rpm	Toro 452cc	Toro 452cc	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	Toro 452cc	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	23 hp Kawasaki® V-Twin 726cc	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing
Engine Guard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Fuel Capacity	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon	3 gallon
Mowing Deck	32" - 13 ga. 1 blade	42" - 13 ga. 2 blades	42" - 13 ga. 2 blades	50" - 12 ga. 3 blades	34" fab. - 10 ga. 2 blades	42" fab. - 10 ga. 2 blades	42" fab. - 10 ga. 2 blades	50" fab. - 10 ga. 3 blades	50" fab. - 10 ga. 3 blades	50" fab. - 10 ga. 3 blades	60" fab. - 10 ga. 3 blades
Blade Tip Speed	18,959 ft/min	17,810 ft/min	17,810 ft/min	18,330 ft/min	17,810 ft/min	17,810 ft/min	17,810 ft/min	18,330 ft/min	18,330 ft/min	18,330 ft/min	18,330 ft/min
Deck Washout Ports	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Height of Cut	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"
Deck Lift Pedal	Optional	Optional	Optional	Optional	Standard	Optional	Standard	Optional	Optional	Optional	Standard
Frame	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge
Hitch	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Anti-Vibration Mat	Standard	Optional	Optional	Optional	Standard	Standard	Standard	Optional	Optional	Standard	Standard
Transmissions	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2800
Smart Speed	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Automatic Parking Brake	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Steering Levers	Standard	Standard	Standard	Standard	Pro-Control Dampers	Standard Dampers	Pro-Control Dampers	Standard Dampers	Standard Dampers	Standard Dampers	Pro-Control Dampers
Mow (F/R)	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph	Up to 7 mph / 3 mph
Tow (F/R)	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph	Up to 5.5 mph / 2.4 mph
Trim (F/R)	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph	Up to 4 mph / 1.7 mph
Tires (Rear)	18" x 6.0"	18" x 7.5"	18" x 7.5"	18" x 9.5"	18" x 6.0"	18" x 7.5"	18" x 7.5"	18" x 9.5"	20" x 10"	20" x 10"	20" x 10"
Tires (Front)	11" x 4"	11" x 4"	11" x 4"	13" x 5"	11" x 4"	11" x 4"	11" x 4"	13" x 5"	13" x 5"	13" x 6.5"	13" x 6.5"
Seat	18" Extra-Tall	18" Extra-Tall	18" Extra-Tall	18" Premium	18" Premium	18" Extra-Tall	18" Premium	18" Premium	18" Premium	18" Premium	18" Premium
Seat Suspension	N/A	N/A	N/A	N/A	Spring Under Seat	Spring Under Seat	Spring Under Seat	Spring Under Seat	Spring Under Seat	MyRIDE® Suspension System	Spring Under Seat
Armrests	Optional	Optional	Optional	Optional	Standard	Optional	Standard	Optional	Standard	Standard	Standard
Hour Meter	Standard	Optional	Optional	Optional	Standard	Optional	Standard	Optional	Optional	Optional	Standard
Storage Dimensions (W x L x H)	35.3" x 71.8" x 40.7"	45.3" x 71.8" x 37.3"	45.3" x 71.8" x 37.3"	54.6" x 72.9" x 41.5"	38.5" x 71.8" x 42.0"	45.6" x 71.8" x 39.1"	45.6" x 71.8" x 42.0"	53.5" x 72.9" x 39.1"	53.5" x 72.9" x 39.1"	53.5" x 72.9" x 43.0"	61.3" x 82.1" x 43.0"
Residential Warranty²	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours

¹The gross horsepower of this engine was laboratory rated at 3,600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of mower will be significantly lower.

²See dealer for warranty details.

	TimeCutter® HD				
MODELS	75201	75202	75211	75212	75213
Price	\$4,899.00	\$5,199.00	\$5,399.00	\$5,399.00	\$5,599.00
Engine¹ at 3,600 rpm	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing
Mowing Deck	48" Fabricated - Grade 50 High Strength 10 ga. Steel Shell	54" Fabricated - Grade 50 High Strength 10 ga. Steel Shell	48" Fabricated - Grade 50 High Strength 10 ga. Steel Shell	54" Fabricated - Grade 50 High Strength 10 ga. Steel Shell	60" Fabricated - Grade 50 High Strength 10 ga. Steel Shell
Front Axle	2.5" x 2.5" Fully Tubular	2.5" x 2.5" Fully Tubular	2.5" x 2.5" Fully Tubular	2.5" x 2.5" Fully Tubular	2.5" x 2.5" Fully Tubular
Fuel Capacity	5 gallon	5 gallon	5 gallon	5 gallon	5 gallon
Frame	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge	Heavy Duty 10-Gauge
Deck Washout Ports	2 Standard	2 Standard	2 Standard	2 Standard	2 Standard
Deck Spindles	7.75" dia. housing; 1" shaft	7.75" dia. housing; 1" shaft	7.75" dia. housing; 1" shaft	7.75" dia. housing; 1" shaft	7.75" dia. housing; 1" shaft
Blade Tip Speed	18,800+ ft/min	18,644+ ft/min	18,800+ ft/min	18,644+ ft/min	18,908+ ft/min
Anti-Scalp Rollers	3 Standard	3 Standard	3 Standard	3 Standard	3 Standard
Height of Cut / Deck Lift Pedal	1.5" - 4.5" / 13 position	1.5" - 4.5" / 13 position	1.5" - 4.5" / 13 position	1.5" - 4.5" / 13 position	1.5" - 4.5" / 13 position
Transmissions	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100
Ground Speed²	Up to 8.5 mph	Up to 8.5 mph	Up to 8.5 mph	Up to 8.5 mph	Up to 8.5 mph
Tires (Rear)	22" x 10"	22" x 10"	22" x 10"	22" x 10"	22" x 10"
Tires (Front)	13" x 6.5"	13" x 6.5"	13" x 6.5"	13" x 6.5"	13" x 6.5"
Seat	18" Premium Thickly Padded	18" Premium Thickly Padded	18" Premium Thickly Padded	18" Premium Thickly Padded	18" Premium Thickly Padded
Seat Suspension	Springs Under Seat	Springs Under Seat	MyRIDE® Suspension System	MyRIDE® Suspension System	MyRIDE® Suspension System
Armrests	Standard	Standard	Standard	Standard	Standard
Steering Levers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers
Anti-Vibration Mat	Standard	Standard	Standard	Standard	Standard
Hitch	Standard	Standard	Standard	Standard	Standard
12v Accessory Port	Standard	Standard	Standard	Standard	Standard
Rear Engine Guard	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready	Standard, Bucket Ready
Smart Speed® Control System	Standard	Standard	Standard	Standard	Standard
Storage Dimensions (W x L x H)	82" x 52.4" x 44"	82" x 57.7" x 44"	82" x 52.4" x 44"	82" x 57.7" x 44"	82" x 63" x 44"
ROPS (Foldable for Storage)	Optional	Optional	Optional	Optional	Optional
Hour Meter	Standard	Standard	Standard	Standard	Standard
Limited Warranty³	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour

Specifications subject to change without notice and without incurring obligation. Products depicted in this brochure are for demonstration purposes only.

Actual products offered for sale may vary in design, required attachments and safety features.

¹The gross torque of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine torque on these mowers will be significantly lower.

²Maximum ground speed will vary with ground conditions, tire pressure, transmission settings and engine settings.

³See dealer for warranty details.