

TIMECUTTER® ZERO TURN MOWER SPECIFICATIONS

MyRIDE® Suspension System							MyRIDE® Suspension System				
YARD SIZE	UP TO 1 ACRE		1 TO 3 ACRES				3+ ACRES				
MODEL	SS3225¹ 74710	SS4225 74726	MX5000 74773	MX5050 74774	MX5075 74768	MX6050 74777	HD Series 75201	HD Series 75202	HD Series 75211	HD Series 75212	HD Series 75213
PRICING	\$2499	\$2599	\$2999	\$3499	\$4199	\$4399	\$5099	\$5399	\$5599	\$5899	\$5999
ENGINE¹	Toro® 452cc	» 22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	» 24 hp Kohler V-Twin with Pro-Series Air Cleaner 725cc	» 24.5 hp Toro Commercial V-Twin 708cc with Self-Cleaning Air Filter Housing	» 24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc w/ Self-Cleaning Air Filter Housing	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	» 24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	22.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	» 24.5 hp Toro Commercial V-Twin 708cc w/Self-Cleaning Air Filter Housing	24.5 hp Toro Commercial V-Twin 708cc w/ Self-Cleaning Air Filter Housing
FUEL CAPACITY	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	3 gallons (11.4 liters)	5 gallons (18.9 L)	5 gallons (18.9 L)	5 gallons (18.9 L)	5 gallons (18.9 L)	5 gallons (18.9 L)
MOWING DECK	32" (81 cm) 13 ga. 1 blade	42" (107 cm) 13 ga. 2 blades	» 50" (127 cm) fab. 10 ga. 3 blades IronForged™ Cutting System	50" (127 cm) fab. 10 ga. 3 blades IronForged™ Cutting System	50" (127 cm) fab. 10 ga. 3 blades IronForged™ Cutting System	» 60" (152 cm) fab. 10 ga. 3 blades IronForged™ Cutting System	48" (121.9 cm) fab. Grade 50 High Strength 10 ga. Steel Shell IronForged™ Cutting System	» 54" (137.2 cm) fab. Grade 50 High Strength 10 ga. Steel Shell IronForged™ Cutting System	48" (121.9 cm) fab. Grade 50 High Strength 10 ga. Steel Shell IronForged™ Cutting System	» 54" (137.2 cm) fab. Grade 50 High Strength 10 ga. Steel Shell IronForged™ Cutting System	» 60" (152.4 cm) fab. Grade 50 High Strength 10 ga. Steel Shell IronForged™ Cutting System
BLADE TIP SPEED	18,959 ft/min (5,779 m/min)	17,810 ft/min (5,428 m/min)	» 18,330 ft/min (5,587 m/min)	18,330 ft/min (5,587 m/min)	18,330 ft/min (5,587 m/min)	18,330 ft/min (5,587 m/min)	» 18,880+ ft/min (5,755+ m/min)	18,644+ ft/min (5,683+ m/min)	» 18,880+ ft/min (5,755+ m/min)	18,644+ ft/min (5,683+ m/min)	» 18,908+ ft/min (5,763+ m/min)
HEIGHT OF CUT	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm)	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position	1.5" - 4.5" (3.8 - 11.4 cm) 13 position
DECK LIFT PEDAL	Optional	Optional	Optional	» Standard	N/A	» Standard	Standard	Standard	Standard	Standard	Standard
FRAME	Heavy-Duty 10-Gauge	Heavy-Duty 10-Gauge	Heavy-Duty 10-Gauge	Heavy-Duty 10-Gauge	Heavy-Duty 10-Gauge	Heavy-Duty 10-Gauge	» Fully Tubular Heavy-Duty 10-Gauge	Fully Tubular Heavy-Duty 10-Gauge	Fully Tubular Heavy-Duty 10-Gauge	Fully Tubular Heavy-Duty 10-Gauge	Fully Tubular Heavy-Duty 10-Gauge
ANTI-VIBRATION MAT	Standard	Optional	Optional	» Standard	» Standard	Standard	Standard	Standard	Standard	Standard	Standard
TRANSMISSIONS	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	Dual Hydrostatic HG-ZT2100	» Dual Hydrostatic HG-ZT2200	Dual Hydrostatic HG-ZT2200	» Dual Hydrostatic HG-ZT2800	» Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100	Dual Hydrostatic HG-ZT3100
STEERING LEVERS	Standard	Standard	Standard Dampers	» Pro-Control Dampers	» Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers	Pro-Control Dampers
TIRES (FRONT)	11" x 4" (27.9 x 10.2 cm)	11" x 4" (27.9 x 10.2 cm)	» 11" x 6" (27.9 x 12.7 cm)	» 13" x 5" (33 x 12.7 cm)	» 13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)	13" x 6.5" (33 x 16.5 cm)
TIRES (REAR)	18" x 6.0" (45.7 x 15.2cm)	18" x 7.5" (45.7 x 19.1 cm)	18" x 7.5" (45.7 x 19.1 cm)	» 20" x 10" (50.8 x 25.4 cm)	20" x 10" (50.8 x 25.4 cm)	20" x 10" (50.8 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)	22" x 10" (55.9 x 25.4 cm)
SEAT	18" (46 cm) Extra-Tall	18" (46 cm) Extra-Tall	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium	18" (46 cm) Premium
STORAGE DIMENSIONS (W x L x H)	35.3" x 71.8" x 40.7" (90 x 182 x 103 cm)	45.3" x 71.8" x 37.3" (115 x 182 x 95 cm)	53.5" x 72.9" x 39.1" (135.9 x 185 x 99.3 cm)	53.5" x 72.9" x 39.1" (135.9 x 185 x 99.3 cm)	53.5" x 72.9" x 43.0" (135.9 x 185 x 109.2 cm)	61.3" x 82.1" x 43.0" (155.7 x 208.5 x 109.2 cm)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)	82" x 57.7" x 44" (208.3 x 146.6 x 111.8 cm)	82" x 52.4" x 44" (208.3 x 133.1 x 111.8 cm)	82" x 57.7" x 44" (208.3 x 146.6 x 111.8 cm)	82" x 63" x 44" (208.3 x 160 x 111.8 cm)
RESIDENTIAL LIMITED WARRANTY²	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year Unlimited Hours	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour	3-Year / 300 Hour

» Enhanced or step-up feature



COMMERCIAL ENGINE

The Toro single cylinder and Toro Commercial V-Twin engines — the same ones found on some of our industry-leading commercial zero-turn mowers — were specifically created to deliver optimal performance in our mowers to the needs of the Toro decks they power. They respond faster with more power when you need it, so you're ready to handle your toughest outdoor tasks. With heavy-duty components and innovative features, it's the perfect match for the job you need to do.



IRONFORGED™ DECK

When we set out to make a tougher deck, we didn't mess around. We used thicker steel, heavier spindles, and unbelievably fast blade tip speeds to give you the ultimate advantage. Our new IronForged deck is built on our long heritage in making the most durable commercial cutting machines in the business. The result is a mower that powers through tall, thick, wet grass with ease — leaving behind nothing but a yard to be envied.



MAXIMUM COMFORT

Once you take hold of the controls, the rest of your body is isolated from the mower. That means you'll experience the most comfortable ride a lawn mower has to offer. Hands down. *Models 74768, 75211, 75212 and 75213.*



VERSATILITY IS STANDARD

Each TimeCutter comes standard with a hitch for pulling a variety of attachments, providing added versatility.



490-0206 ©2019 The Toro Company All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. ¹The gross horsepower of this engine was laboratory rated at 3,600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of mower will be significantly lower. We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation. ²See retailer for complete warranty details. ³Can be maneuvered through a 36" gate.