

Operator's Manual Supplement

This supplement replaces page one (1) of Operating & Maintenance Instruction Manual #810782R1. Insert supplement into Operator's Manual.

MODEL AND SERIAL NUMBER

A Model and Serial Number identifies your Toro Wheel Horse attachment (Fig.1). These numbers should always be referred to when consulting with your dealer or factory concerning service, replacement parts, or questions you may have. If plate is removed during repair operations it should always be replaced. For your reference, record numbers from Model and Serial Number plate on your attachment.

DESCRIPTION

The grass bagger covered in this manual is designed to fit 240-Series Toro Wheel Horse tractors with 38 inch side discharge mowers.

INSTALL DISCHARGE ELBOW

CAUTION

Sharp edges of mower blade can cut you during blade maintenance or adjustment. Use suitable covering over cutting edges of blade to prevent bodily harm.

Install supplied spacer on mower deck with 3/8-16 x 1 3/4 bolt, washer and E.S. nut (Fig. 2). Raise discharge chute and hook rear of discharge elbow on spacer (Fig. 3). Secure front of discharge elbow to mower deck with retainer clip and secure rear of discharge elbow to mower with rubber handle (Figs. 3 & 4).

INSTALLATION

Slide quick attach bracket into hole in rear drawbar and hook brackets over bolt spacer at each side (Fig. 5).

NOTE: There are two positions available for bracket. Use rear drawbar hole and front bracket hooks for 5-Speed tractors. Use front drawbar hole and rear bracket hooks for Hydrostatic tractors. Secure quick attach bracket with large hairpin cotter.

Remove bolts and spacers when installing rear wheel tire chains to prevent damage to tractor (244-5 Only).