


TORO



Model **21012, 21014**

43 cm

Serial-No: **210000101 & up**



Operator's Manual



General

3



Maintenance and Upkeep

15




Safety

5



Spare Parts and Troubleshooting

20



Assembly and Start-up

7



Hints on Tending the Lawn

23



Operation

11



1 General

1.1 Introduction

1.2 Regulation on Time Limits for the Operation of Lawn Mowers.

1.3 Technical Data

1.1 Introduction

The TORO lawn mower has been designed according to the latest technical and physiological aspects with due regard to the safety regulations in force.

With its special equipment the Recycler® Mower can cut up grass and leaves several times. This superfine-cut material will be sprinkled into the lawn by the mower.

Read the instructions for use carefully and familiarize yourself with the instructions on safety, assembling, operation and maintenance.

The TORO lawn mower has been designed for the private use in the garden. Lawn mowers for the private garden are units which are - as a rule - in use for not more than 50 hours per year, and which are mainly used for the tending of patches of grass and lawns; they are, however, not to be used in public gardens, parks, sports fields etc. and not on roadsides nor in the agriculture and forestry.

The observance of the instructions for use enclosed by TORO is a prerequisite for the proper use of the lawn mower. The instructions for use also enclose the conditions of operation, maintenance and upkeep.

Safety



On-the-job safety symbol. This symbol you will find with all on-the-job safety instructions dealing with danger of personal injury. It is imperative to observe these instructions. The on-the-job safety instructions should be passed on to other users as well. The general regulations for safety and prevention of accidents must also be observed.



Warning sign. This symbol marks the points which are to be taken special notice of in order to avoid damaging or destroying the unit.

1.2 Regulation on Time Limits for the Operation of Lawn Mowers.

The regulations on the operation of lawn mowers vary from one region to another. The competent authority will be pleased to inform you on regulations and regional restrictions, especially as to the protection of the period of quiet after lunch or of very sensitive areas (e. g. nature reserves),

1.3 Technical Data

width of cut:	43 cm
motor type:	4-cycle -Motor B&S Quantum
cubic capacity:	190 cc
motor speed:	3000 min ⁻¹
handle bar a : hw	15 m/sec ² (measured in accordance with pr EN 1033)
tank volume:	1.1 liters
oil volume:	0.6 liters
weight:	21012 21014 28 kg 32 kg
dimensions :	L x W x H = 83 x 45 x 50 cm (folded up)



EC Declaration of Conformity

We **The Toro Company**
8111 Lyndale Ave. So.
Bloomington, MN 55420-1196, USA

Declare that the machine

Lawnmower, walk behind with combustion engine (EN836) **Type: TORO 21020 / 21022, Cuttingwidth: 43cm**

Conforms to the specifications of the following EC directives: **98/37/EG, 89/336/EWG, 84/538/EWG**

Where appropriate applied standards: **EN 836, EN ISO 14982**

Conformity assessment procedure followed: **Annex V**

Measured sound power level: **TORO 21012 / 21014: 95 dB(A)**

Guaranteed sound power level: **TORO 21012 / 21014: 96 dB(A)**

Bloomington, MN, USA **01.03.2001**
Place Date

Jerry Patrin
Signature

VP Technical Manager
Representative



2 Safety

2.1 General Notes

2.2 Proper Use

2.3 Improper Use

2.4 Preparing the lawn mower for safe operation

2.5 Safe operation

2.6 Safe maintenance and storage

2.7 List of symbols

2.1 General notes

1. Read the instructions carefully. Familiarize yourself with the operating elements and the proper use of the unit.
2. Children as well as persons who are not familiar with the instructions for use must not operate the lawn mower. Observe the local age limits for the operation of the unit.
3. Do not start the mower in close proximity to children and pets.
4. The operator is liable for injuries of third parties and damages of their property.

2.2 Proper use

The lawn mower serves exclusively for the tending of grass patches and lawns in the private garden. Any other use is regarded as inexpedient. The Toro Company is not liable for damages resulting from this.

2.3 Improper use

The mower must not be used for the trimming of bushes, hedges and shrubs, for the cutting of creepers or grass on roof gardens or in balcony boxes, for the cleaning (by suction, blowing away; snow removal) of sidewalks nor as a chaffcutter for chopping cut-off twigs and branches of trees and hedges. Moreover, the mower must not be used as drive unit for other interchangeable equipment items and tool kits.

2.4 Preparations for safe operation

1. You should always wear sturdy shoes and trousers when mowing. Do not mow barefoot or wearing sandals.
2. First inspect the area to be mowed. Remove all objects which can be hurled away by the mower.
3. Fuel is extremely inflammable.
 - Store fuel in safe cans only.
 - Always take the mower outdoors to fill the fuel tank and do not smoke while doing so.
 - Add fuel only before starting the motor. While the motor is running or is still hot, you must not remove the cap of the tank or add fuel.
 - If some fuel has overflowed, the motor must not be started before the unit has been removed from the place where the fuel has been spilled. Do not take any risk, wait until the gasoline vapours have evaporated.
 - Close all caps of fuel cans and tanks tightly.
4. Exchange damaged sound absorbers.
5. Make a visual inspection before starting the motor and check for damages and wear on blade, blade fastening screws and cutting parts. Worn or damaged blades and screws must always be exchanged in sets to keep the balance.

2.5 Safe operation

1. Do not let the motor run indoors. Danger of carbon-monoxide poisoning.
2. Mow only in daylight or with good illumination.
3. Do not mow grass when wet.
4. Make sure to have a firm foothold when mowing on sloping ground.
5. Mow at a walking pace, do not run.
6. Always mow sideways to the slope, never up and down.
7. Be careful when changing direction on sloping ground.
8. Do not mow on extremely sloping ground.
9. Be careful when moving the lawn mower backward or pulling it.
10. Stop the engine, if you have to tilt the lawn mower when walking off the grass to cross paths. Transport the machine to the area to be mowed and back with the motor off.

11. Never operate the lawn mower without safety devices e. g. impact protection and/or grass collecting elements.
12. The adjustments on the motor are preset and must not be changed. Do not overspeed the motor.
13. Loosen all blade and drive clutches before starting the motor.
14. On starting the motor, all instructions are to be observed, and attention is to be paid that the feet are in a safe distance to the blade.
15. Do not tilt the lawn mower when starting the motor, unless the motor has to be tilted for this purpose. In this case, the unit must not be tilted more than absolutely necessary, to be more precise, the mower may only be tilted backward, so that the bottom side of the mower is not turned towards the operator.
16. Keep away from the discharge tunnel opening when starting the motor.
17. Never put your hands and feet on or under rotating parts. Keep a due distance to the ejection hole.
18. Do not lift or carry the lawn mower with the motor running.
19. In the following cases, the motor is to be stopped and the spark plug connector is to be disconnected:
 - before removing obstructions in the discharge tunnel;
 - before inspecting, cleaning or performing any other work on the lawn mower;
 - after the lawn mower has hit against a foreign matter. Check your lawn mower for damage and make the necessary repairs before further use of the lawn mower.
 - if the unit starts to vibrate heavily (immediate inspection required).
20. Always stop the motor before leaving the mower and each time before refuelling.



2.6 Safe maintenance and storage

1. Ensure that all nuts, bolts and screws are tightened to guarantee a safe operating state.
2. If there is fuel in the tank, never place the mower where there is danger that the gasoline vapours might catch fire from open flames or sparks.
3. Let the motor cool down before you put the mower into a closed room.
4. In order to avoid fire risk, keep the area of motor, exhaust, battery case and fuel tank free from grass, leaves or excessive amounts of grease/oil.
5. Check the grass collecting bag at short, regular intervals for wear and damages.
6. For safety reasons, worn or damaged parts are to be exchanged.
7. If the fuel tank has to be emptied, this has to be done outdoors.

2.7 List of symbols



Warning

Read the instructions for use before starting



Third parties have to be kept out of the hazardous area



Warning! Rotating blade!
Keep hands and feet off

Disconnect spark plug before service!



Electrical shock / electrocution
Keep dry



Disconnect main plug before
servicing the cutting tool



Always keep connecting cable away from blade.
If the blade catches or cuts the cord, immediately
unplug the cable from the outlet.



high motor speed



low motor speed (idle)



cold start injection (starting aid)



push starting aid 3 times



pull up lever for starting up



pull starter rope



"Adjustment of cutting height"



electro start (motor on)



motor stop



clutch disengaged




clutch engaged



wheel



wheel drive








3 Assembly and start-up

- 3.1 Become acquainted with your lawn mower
- 3.2 Setting the lawn mower up
- 3.3 Mounting the handlebar
- 3.4 Attaching the grass collecting device
- 3.5 Adjusting the cutting height
- 3.6 Proper cutting height for recycling
- 3.7 Filling in the motor oil
- 3.8 Filling up the tank

3.1 Become acquainted with your lawn mower

- 1 Safety lever for motor start/stop**
Function - refer to chapter start-up
- 2 Vario-Handle for self propel (only on mowers with AutoMatic Drive)**
This handle selects self propelling on-off operation, as well the mowing speed.
- 3 cutting height adjusting handle (6 steps)**
- 4 Cutting height scale**
Scale indicating the adjusted cutting height
- 5 "Smart Wheel" scale**
Scale for adjusting the proper cutting height
- 6 Ejection door**
Guard for the ejection opening which must not be removed. It also serves as a stacker for the cut grass when mowing without collecting device.
- 7 Grass-collecting device**
- 8 Recycler - plug**
refer to chapter operation
- 9 Handlebar start**
- 10 Fuel tank**
Contents: approx. 1.1 liters, operating time: approx. 1 h / tank filling
- 11 Oil filling pipe and oil measuring stick**
refer to chapter start-up
- 12 Air filter**
Cleaning refer to chapter maintenance and upkeep
- 13 Spark plug connector**
plug on spark plug before start-up
- 14 Wash-out Port**



3.2 Setting the lawn mower up

1. Open the straps and lift the upper part of the carton (Fig. 2).
2. Take out the components and put them down (Fig. 2).
3. Check completeness of contents.
Contents: (1) mower with handle (divided into two with AutoMatic Drive), (2) rack for grass collecting bag, (3) grass collecting bag, (4) grass guiding profile, (5) recycler plug, (6) user's manual (fig. 2).
4. Dispose packaging according to the local regulations.

3.3 Mounting the handlebar

1. Assemble upper and lower handle (only AutoMatic Drive). Watch out, that upwards bent portion of the lower handle points upward (fig.3)
2. Slacken knobs at the lateral mower rear and turn handle receptacle until openings point up (fig. 3).
3. Insert handle into receptacle up to the limit, cables must run outside along the handle.






Do not bend, squeeze or damage cable.

4. Swing handle back until receptacles snap into housing, then tighten knobs by hand.



If you should not succeed in reassembling the handle as described above, insert handle only somewhat, swing back, tighten knobs so that the receptacles snap into the housing. In this working position, push mower with the front wheels against an obstacle, push against handle, push in up to the limit stop, and tighten knobs by hand (fig. 4).

5. Attach starter rope to the eye bolt at the handle (fig. 5).
6. Attach cable with velcro fasteners or cable binders to the handle (fig. 6).



3.4 Attaching the grass-collecting device

1. Put the fabric of the collecting bag from behind onto the frame (Fig. 7).
Slide the upper plastic profile underneath the handle to the front and clip it there.
2. Clip the other plastic profiles around the frame.
3. Clip the plastic profile

3.5 Adjusting the cutting height



Adjust cutting height only when the motor is turned off.

The cutting height is adjustable with a six-step central height adjustment.

1. Push adjusting handle up until it hits the limit stop.
2. Adjust the cutting height by means of the scale keeping the adjusting handle pressed and moving the mower up and down (Fig. 8).
3. Release adjusting handle. The mower is locked in the desired position.

The letters on the scale correspond to:

A = 2,2 cm	B = 3,2 cm	C = 4,2 cm
D = 5,3 cm	E = 6,6 cm	F = 7,6 cm

3.6 Proper cutting height for recycling

The left rear wheel bears a scale (Smart Wheel) for reading the appropriate cutting height (Fig. 9).

Left scale = normal grass

Right scale = dense grass


Never use position "A" for recycling.

In easy and suitable conditions, position "B" is possible to use, recommended for recycling is "C", "D" or "E".


During the warm summer months, adjust cutting height according to the scale "normal".

For dense, thicker or damp grass e. g. in spring, use the scale "dense".

1. First push the mower onto the lawn - the scale must be parallel to the ground.
2. Now you can read the length of the uncut grass on the scale and choose the recommended adjustment.



10



11

3.7 Refilling the motor oil (Fig. 10)



With outside temperatures above 4°C, use SAE 10 W-30 HD or 10 W-40 HD. With temperatures below 4°C, use SAE 5 W-20 or 5 W-30 HD.

1. Place mower on a horizontal surface.
2. Open cover and fill in approx. 0.6 liters of motor oil and insert oil measuring stick up to its limit stop (do not screw in).
3. Take out oil measuring stick and check oil level.



Oil level may not be above the "Full" mark and not below the "ADD" mark. If required, drain some of the oil.

4. Screw cover on oil filling pipe and tighten with manual force.



First oil exchange after 5 operating hours. After that, every 50 operating hours. Check the oil level before each start-up.

3.8 Filling up the tank (Fig. 11)



Fill in regular grade unleaded petrol only. Do not mix fuel with oil. Do not use any fuel that has been stored for a long period of time.




Only store reserve fuel in containers approved for this. To fill up the tank, turn off motor. Only open tank while motor is turned off. Only fill up the tank outdoors. Do not inhale fuel vapors.


Remove any overflowed fuel before starting.

No smoking, no open fire, no open light.


After sufficient fuel has been filled in, close the tank cover with manual force and wipe off spilled fuel, if any. Do not fill up fuel up to the filling pipe, but leave an "expansion space" of approx. 1 cm.




12



13



14



15

4 Operation

4.1 Starting and turning off the motor and operation of wheel drive (only for mowers with wheel drive)

4.2 Recycling

4.3 Mowing with grass-collecting device

4.4 Mowing without grass-collecting device

4.1 Starting and turning off the motor and operation of wheel drive (only for mowers with wheel drive)

1. Plug spark plug connector on the spark plug (fig. 12).
2. Place mower on a flat surface without high grass.
3. If the motor is cold, press the primer button three times (Fig.13). If the motor is warm start without pressing the primer button.
4. Pull up lever to the handlebar and pull up starter rope until resistance can be felt. Pull up starter rope evenly approx. 1 arm length until the motor starts (fig. 14).



Do not pull starter rope up to the limit stop or let go abruptly, but let it slide back slowly to avoid damage to the recoil mechanism.

Using the Self Propel System

Press automatic drive: Use the vario-handle to push the mower forwards. The handle will move forwards when you move off and it will then activate the self-propel system. The mower will adapt to the moving speed. (Fig. 15)




The mower must never be used to pull other objects. It is forbidden for anyone to ride on the mower.

Note: Maximum speed is realized by pushing the handle fully in. Reduce the speed by moving slower. Just stand still to turn the drive system off (Fig.15).


Important! Pull the handle up to the rear stop in order to pull the mower backwards.

Please note: A grip-bar can be fitted on the handle to support the wheel-drive when going up slopes. (Accessory-No.: 00036)

Note: If the mower becomes blocked when pulling the mower backwards after mowing using self-propel, gently push the handle forwards and then pull it straight back to the rear stop.



16



17

Turning the motor off

Release handle-type safety bow.
For mowers with wheel drive, release handle-type bow for wheel drive and handle-type safety bow.



The blade will coast for a short time.
Do not touch underneath the mower.

Turn the mower off when driving off the lawn.
Wait until the blade stands still and remove the spark plug connector before transporting or lifting the mower.

4.2 Recycling

For recycling the Recycler plug must be inside the discharge tunnel.


1. Ensure that the motor and the blade are stopped.
2. Open the ejection door.
3. Push the Recycler plug into the discharge tunnel. The Recycler plug must lock (Fig.16).
4. Close the ejection door.




To remove the Recycler plug, stop the motor and wait until the blade stops turning.

Open the ejection door and pull the Recycler plug out. Close the ejection door.


- Ensure that the blade is always sharp. Notches may be removed by means of a file (keep the blade balanced).
- After each mowing, grass clippings must be removed from the bottom side of the mower, from the deflectors and from the Recycler plug (Fig. 17).
- With grass heights greater than or equal to 15 cm, the lawn should be mowed in two steps.
- In hot summers, adjust the cutting height on C, D, E or F. Do not cut off more than a third of the grass leaf.




18



19



20



21

When mowing in high grass, you should select a higher cutting adjustment first. Then mow with the usual adjustment. Lumpy grass and chockings inside the discharge tunnel effect a throttling or stop of the motor. In such cases, you should mow at least one step higher. Should the motor have stopped due to the conditions inside the mower housing and stall when restarting, it is absolutely necessary to clear grass clippings from the mowing tunnel (Fig. 18).



To clean the mower, remove the spark plug connector.

Change the mowing direction frequently (Fig. 19).

In case of an unsatisfactory mowing result:

1. Resharpener the blade (be sure to keep the blade balanced).
2. Mow at a slower pace.
3. Increase the cutting height by one or two steps.
4. Mow your lawn in shorter intervals.
5. Mow only 2/3 or half the mowing width, in order to give the mower the opportunity to discharge the clippings.

4.3 Mowing with the grass-collecting device





Never remove the grass-collecting device while the motor is running - danger of injury!

1. **Ensure that the motor and the blade stand still. Remove the Recycler-plug!**
2. Clean the grass ejection area from grass rests (Fig. 18).
3. Hang the grass-collecting device into the mounting on the mower housing (Fig. 20).
4. Close the ejection door up to the grass-collecting device.

To empty the grass-collecting device, turn the motor off and wait until the blade stands still. Disconnect the spark plug connector when leaving the mower.

Remove the grass-collecting device and tilt it a bit to the back so that no grass will fall out.

Dump the full grass-collecting device by shaking it slightly (fig. 21).




4.4 Mowing without the grass-collecting device




Never remove the grass-collecting device while the motor is running - danger of injury!


Mowing without the grass-collecting device is recommended for mowing high grass or if no grass collection is desired. Remove the grass-collecting device and the Recycler-plug (Fig. 22 + 23).



24



25



19363	Blade retainer
20007	Blade
19364	Washer
19365	Bolt

26

5 Maintenance and upkeep

- 5.1 Checking the blade for damage
- 5.2 Cleaning the mower
- 5.3 Servicing the air filter
- 5.4 Exchanging the motor oil
- 5.5 Exchanging the spark plug
- 5.6 Adjusting the Bowden cable for the wheel drive
- 5.7 Adjusting the Bowden cable for the motor start/stop
- 5.8 Storing the mower

5.1 Checking the blade for damage



Stop the motor, wait until the blade stands still and remove the spark plug connector when working on the mower. Danger of injury! If you are going to lay the mower on its side for a longer time, empty fuel tank fully first.

After the mower has hit against a hard object as e. g. a stone, proceed as follows:

- Turn the mower off and remove the spark plug connector
- Lay mower on the correct side (carburetor on top) (Fig. 24).
- Carefully check the cutting edge of the blade for defects.

Bent or damaged blades must not be used any longer. They have to be replaced.


Use only original TORO blades. They have been designed especially for this unit and guarantee a perfect performance, safety and a long service life.

Have dull blades sharpened. For safety reasons a resharpening may be executed only up to the mark (Fig. 25).




If the same blade is in use for too long, this might lead to wear and changes of the blade section. A broken blade can be the consequence, and parts of the blade can be hurled away.


Operate the mower only with perfect blades!
Only use original TORO spare parts or parts released by TORO (reference numbers see fig. 26).




27



28



29



30

5.2 Cleaning the mower



Before cleaning the mower, stop the motor, wait until the blade stands still and disconnect the spark plug connector. Danger of injury! (fig. 27)



Do not wash the motor down with water. Danger of motor breakdown! Before tilting the mower, fully empty the fuel tank. Only tilt mower far enough that the carburetor is on top.

Wipe off dirt and grass rests with a rag. Lay mower on its side and clean the bottom side of the mower (fig. 28).

For quick and easy cleaning, the mower offers a wash-out port (fig. 29). There you can attach a water hose and clean underneath the deck while the engine is running.

5.3 Servicing the air filter

Clean air filter every 20 - 25 operating hours or after 3 months. Clean more often if mower is used in dusty and dirty environment.




Ensure that the motor is standing still and the spark plug connector has been pulled off.

1. Slacken screw and fold cover down (fig.30).
2. Carefully remove air filter insert.
3. If only slightly soiled, knock it out carefully on a smooth surface; if heavily soiled, replace insert.




Do not start motor without air filter. Dust or dirt may cause serious damage to the motor.

4. Insert cleaned or new air filter insert, close cover and fasten with screw (reference number see fig. 30).



31



32

5.4 Exchanging the motor oil



Stop the motor, wait until the blade stands still and remove the spark plug connector, when working on the mower. Danger of injury!

first oil exchange: after 5 operating hours.
all other oil exchanges: after 50 operating hours each, but at least once a year.

Let motor run for a few minutes before exchanging the oil.

Oil brands: with outside temperatures of above 4°C , use SAE 10W30 HD or 10W40 HD. With temperatures of below 4°C , use SAE 5W20 HD or 5W30 HD.

1. Drain fuel or and fully empty tank.
2. Place a flat tray or bowl under the oil filling pipe.
3. Unscrew the oil sealing plug and let the old oil drain in the tray (Fig. 31).





When exchanging oil, be careful to avoid that oil drips on the floor!

4. After all of the oil has been drained, place mower back on all four wheels and fill with new motor oil (approx. 0.6 liters). Check oil level (Fig. 32).
5. Screw sealing plug back on.



Old oil may not seep into the ground or get in the sewerage system. Collect the old oil in a larger container and deliver it to an old oil collecting place.



5.5 Exchanging the spark plug



Stop the motor, wait until the blade stands still and remove the spark plug connector, when working on the mower. Danger of injury!

Persons with cardiac pacemakers may not work on the running motor and on live parts of the ignition system when the motor is started. It must be ensured that the motor is at standstill. Only then may the spark plug connector be pulled off.

1. Pull spark plug connector off the spark plug (Fig. 33).
2. Clean area around the spark plug
3. Unscrew spark plug


Replace spark plug by an equivalent spark plug if it is broken, of bad quality or dirty.

Recommended: Champion RJ 19 LM or equivalent
Adjust electrode gap to 0.75 mm (Fig. 34).


Insert spark plug with packing and tighten.

Tightening torque: 20 Nm


If a torque wrench is not available, screw spark plug tight.



35



36



37

5.6 Adjusting the Bowden cable for the wheel drive (only for mowers with wheel drive)



Stop the motor, wait until the blade stands still and remove the spark plug connector when working on the mower. Danger of injury! (Fig. 35)

The Bowden cable needs to be adjusted if the rear wheels become blocked when pulling backwards or if there is insufficient drive power.

1. Check to see if the Bowden cable is kinked or is too tight.

Rear wheels blocking when pulling backwards (see P. 11)

2. Undo the locking nut (1) and then turn the adjustment nut (2) **clockwise (+)** by 1 - 3 turns (Fig. 36).

Drive power is insufficient:

2. Undo the locking nut (1) and then turn the adjustment nut (2) **counter-clockwise (-)** by 1 - 3 turns (Fig. 36).
3. Check the setting.
4. Relock the locking nut (1) when you have the optimum setting.



Contact your authorized TORO customer service if you are unable to realize an optimum setting by following these adjustment procedures.

5.7 Adjusting the Bowden cable for the motor start/stop



Stop Bowden cable for the motor start/stop may only be adjusted or exchanged in an authorised TORO service station.



5.8 Storing the mower

Remove the spark plug connector (Fig. 35).

Clean the mower.
Check all bolts, screws and nuts.
Replace damaged parts.

Use only original TORO spare parts which you can obtain from an authorized TORO dealer.

Before longer storage, empty fuel tank and let the motor run to fully consume all the fuel.
Store the mower in a clean, dry place.
The handlebar may be folded down for this purpose (Fig. 37).



6 Spare parts and troubleshooting

6.1 Hints on spare parts ordering

6.2 Customer service address

6.3 Troubleshooting

6.1 Hints on spare parts ordering

Use only original TORO spare parts or parts released by the manufacturer.

This is the only way to guarantee for your safety and the safety of others.

The nameplate bears model and serial number of your TORO lawn mower (Fig. 38).

Always give both numbers when ordering spare parts or corresponding.

Insert the model and serial number of your TORO lawn mower here:


Model number: _____

Serial number: _____

Spare parts can be purchased at any TORO customer service by giving the model and serial number.


6.2 Customer service address

Insert here the address of your nearest TORO customer service:



TROUBLESHOOTING

Problem	Possible cause	Remedial measures
Motor does not start.	<ol style="list-style-type: none"> 1. Starting aid was not pushed. 2. Fuel tank is empty. 3. Air filter element is dirty. 4. Spark plug is loose. 5. Ignition cable is loose or has come off the spark plug. 6. Electrode gap is not correct. 7. Spark plug is defective. 8. The carburetor is flooded. 9. Ignition system defective (no ignition spark). 10. Blade is loose. 11. Motor stop is active. 	<ol style="list-style-type: none"> 1. Push starting aid 3 times. 2. Refill fuel tank. 3. Clean air filter element. 4. Tighten spark plug. Torque: 20 Nm. 5. Attach ignition cable to the spark plug. 6. Adjust electrode gap to 0.75 mm. 7. Mount new spark plug. 8. Remove air filter element. Pull starter rope several times until the carburetor is empty and the motor starts. As soon as the motor starts, turn it off and mount the air filter element. 9. Consult TORO customer service. 10. Consult TORO customer service. 11. Pull back safety lever.
Motor starts with difficulty, is not running smoothly or loses power.	<ol style="list-style-type: none"> 1. Dirt or water in fuel tank. 2. Vent hole in fuel tank cover is blocked. 3. Air filter is soiled. 4. Blade screw is loose. 5. Spark plug is defective. 6. Vent openings in motor hood blocked. 7. Cooling fins and vent holes below the fan housing are blocked. 	<ol style="list-style-type: none"> 1. Drain fuel and clean tank, refill tank with fresh, clean fuel. 2. Clean or replace tank cover. 3. Clean air filter element. 4. Consult TORO customer service. 5. Adjust electrode gap to 0.75 mm or mount new spark plug. 6. Clean vent openings. 7. Clean cooling fins and vent holes.



TROUBLESHOOTING

Problem	Possible cause	Remedial measures
Motor has spark failures at high speed.	1. Electrode gap of spark plug too small.	1. Adjust electrode gap to 0.75 mm.
Motor overheated.	1. Cooling air flow is obstructed. 2. Electrode gap of spark plug incorrect. 3. Wrong spark plug.	1. Clean vent openings in the hood, in the fan housing and the cooling fins on the motor. 2. Adjust electrode gap to 0.75 mm. 3. Mount correct spark plug with an electrode gap of 0.75 mm.
Motor has irregular vibrations.	1. Blade screw is loose. 2. Blade has not been balanced. 3. There is too much grass in the discharge tunnel.	1. Consult TORO customer service. 2. Consult TORO customer service. 3. Clean mower.
Only mower with wheel drive Wheel drive turned not off or mower moves forward in jolts	1. Bowden cable for wheel drive is misadjusted. 2. Clutch release fork lever has wrong adjustment or is defective. 3. Clutch is defective.	1. Adjust the bowden cable for wheel drive (see Page 19) 2. Consult TORO customer service. 3. Consult TORO customer service.
Wheel drive turned in but mower does not move.	1. V belt defective. 2. Free-wheel defective.	1. Consult TORO customer service. 2. Consult TORO customer service.



7 Hints on tending the lawn

- 7.1 Spring
- 7.2 Summer
- 7.3 Autumn
- 7.4 Winter

7.1 Spring

Cleaning: The first cut and the cleaning should be done two or three weeks before the normal growth starts. To mow, the cutting height should be adjusted in such way that approx. 1.5 cm of the resting grass will be cut off. Thus an early greening of the lawn will be effected. In using the grass-collecting bag available as accessory, the winter litter can be removed. First, however, metal objects, stones, broken glass etc. which can damage the grass-collecting bag must be gathered.

Mellowing: The soil should be treated with a mechanical mellowing device. Thus air, water and fertilizer may enter more easily and a deep rooting is stimulated.

Fertilization: For the fertilization of the lawn, a special lawn fertilizer is to be spread on the latter in early spring. This fertilization is to be repeated according to the demands you make on your lawn. If you want to have a lush green, dense lawn till into the winter, spread the last dose in late summer. In any case it is advisable to have the fertilizer get soaked thoroughly shortly after the spreading - by rain or sprinkling. Make sure that the fertilizer will not paste up (e. g. on uneven ground or when watering with a hose with a too strong jet of water). Moreover, you should not fertilize on new-mown grass, but some days before or after mowing. Each fertilization leads to a denser turf, and growth will be hastened at the same time.

Therefore you should pay special attention to mowing in good time, otherwise new grass will be suppressed. Do not cut high grass too short in one mowing. Especially in case of dryness, your lawn will get brown spots if you cut the grass too short, which is often falsely referred to as damage caused by fertilization.

Watering: Sufficient watering is important if you want to get a healthy lawn. Deep watering, when the grass needs it the most (shortly before withering), stimulates a deep rooting. Frequent and shallow watering effects a concentration of the roots near the surface and stimulates the weed growth.

Mowing: Frequent mowing is imperative for keeping your lawn healthy. It would be best to mow with such frequency that each time not more than 1/3 of the grass leaf is being cut. Thin or newly-sown lawns should be cut to 3.5 cm. This is to be repeated for about four or five weeks, so that the lawn will grow and become more dense.

Weed, insect and disease control: Most specialized dealers sell special chemicals for the control of the most different weeds, insects and diseases. The manufacturers' instructions as to the frequency of application, environmental effects and use of the specified means are to be observed in any case.

Sowing: Although the autumn is the most favourable season for this work, you can sow lawn in the course of the usual spring treatment.

7.2 Summer

Mowing: During the hot and dry summer months the lawn should not be cut too short, because this would let the grass get too dry and withered. When mowing with the grass-collecting device, weeds, seeds of weed and any other undesired plants can be removed with it.

Mellowing: According to the condition of the soil, a mellowing is due from time to time, especially if it is a dry summer.

Watering: In the hot summer months, withered grass is an indication for water demand. Deep watering is advisable during these months. Besides the common way of sprinkling by means of garden hoses, sprinkling systems to be installed into the soil are available, which are also manufactured by TORO. These sprinkling systems work automatically, however, they are also available for manual operation.

7.3 Autumn

Mowing: In autumn you should mow according to the same rules as have been said for the summer months. In autumn you should mow as long as the grass growth demands it. When using the grass-collecting device, the leaves will gather in the sack automatically and slightly cut up, and thus appropriate for composting.

Hints on cutting the leaves: You can also use the recycler for cutting the fallen leaves or other garden waste. If you want to store the leaves in plastic sacks, however, the number sacks to be filled will be smaller, since the leaves have been cut up before and thus they are reduced in volume. When working with the grass collecting device, part of the cut material will still get onto the lawn, where it can serve as fertilizer giving the soil important and precious nutrients until the next spring.

- Ensure before mowing that the leaves are dry.
- Before you stop to recycle ensure yourself that approx. 50 % of the lawn is still to be seen on the mown area.
- In order to collect all the leaves and cut them up very finely, it is useful to walk slower and thus mix all the particles into the lawn.
- In case of lots of oak leaves, it is recommended to spread some lime onto the lawn in spring, in order to absorb the folic acid.

Watering: Since the soil should be damp at the beginning of the winter months, a regular watering in autumn is as important as in the summer months.

Sowing: This is the most suitable season for laying a lawn and for the resowing of existing lawn of thin growth.

7.4 Winter

Preparing the lawn for the winter: If you want to have a beautiful, lush-green and hard-wearing lawn, cover it every two to three years with compost or humous soil before the break of winter. After spreading the fine-crumbled humous soil, it should be raked into the sod thoroughly.



The Toro Company, 8111 Lyndale Ave. So. , Bloomington, MN 55420 - 1196, USA