

TORO®

Compact Hose/Reel System



- Compact
- Light Weight
- High Strength
- Non-Toxic
- Full One-Year Warranty

Haven't you done without a Toro long enough?®

TORO FULL ONE YEAR WARRANTY

The Toro Company promises to repair or replace at our option, any Toro Hose/Reel System used residentially if defective in materials or workmanship one year from the date of purchase. The cost of the replacement unit is included, but the customer is responsible for the return of the product to the selling dealer. This product is not warranted if used commercially. This warranty gives you specific rights, and you may have other rights which vary from country to country.

SPECIAL INSTRUCTIONS

Your Toro Hose/Reel System is designed to prevent many of the inconveniences normally associated with hose products. The following instructions provide tips for handling your new hose in the simplest and most effective way.

To Use:

1. Remove reel knob shipped on back side of reel case. Pressing firmly, slide knob into mounting tabs on front side of reel until it locks into position.
2. Roll out hose keeping it flat without sharp bends or kinks. Remove end fitting from reel. Connect and use as you would any other hose.



To Rewind:

1. Disconnect both ends of hose. Lay hose straight without bends or kinks to allow for easy water exit.
2. Place either end of hose in center of reel. Thread hose through slot in reel and squeegees in reel case.
3. Rewind, walking toward end of hose as you turn knob.



NOTE: Lay hose completely flat to allow drainage when rewinding.

Hose/Reel Care

Avoid leaving hose in hot sunlight for long periods when not in use.

Avoid dragging hose over rough areas such as sharp stones, rocks, building corners, rough dock edges or sidewalk and driveway edgings.

Avoid running over hose with automobiles, bicycles, lawnmowers or other equipment.

Store hose in reel, never hang hose on a nail or other sharp object or near a heater or hot pipe.

If hose is not wound on reel before storage, make sure all water is drained from hose to prevent freezing and possible damage.

Hand tighten couplings only. Do not use a wrench or pliers, as damage may occur to hose or faucet.