

HAYTER

MAKERS OF THE FINEST MOWERS

HARRIER

56

CODE

340S	•	341S
(Auto Drive)		(Electric Start)

OWNER'S HANDBOOK

REFERENCE COPY ONLY

PART NO: 34022S REV: 8

UP REV FROM:

SUPERSEDED BY:

AMENDMENT SHEET:

CERTIFICATE OF CONFORMITY

I, the undersigned M.A. Wright, of:

HAYTER LIMITED, Spellbrook, Bishop's Stortford
Herts CM23 4BU
ENGLAND

certify that the lawnmowers:


1. Machine Type No.	CODE 340S	CODE 341S
2. Category.	Combustion Engine	Combustion Engine
3. Make.	Hayter	Hayter
4. Type.	Rotary	Rotary
5. Engine - Manufacturer.	Briggs & Stratton	Briggs & Stratton
- Type.	111682-0165-E1	111687-0166-E9
- Speed of rotation during test.	2900 rpm	2900 rpm

Conforms to the specifications of Directive 84/538/EEC as adapted to technical progress by Directive 87/252/EEC and amended by Directive 88/180/EEC.

Guaranteed maximum sound power level.	100 dB(A)	100 dB(A)
- Type of cutting device	Cutterbar	Cutterbar
- Width of cutting device	56 cm	56 cm
- Speed of rotation of the cutting device	2900 rpm	2900 rpm

TESTED AT SUDBURY, SUFFOLK, ENGLAND 11/10/99 11/10/99

Signed



M.A. Wright
(Technical Director)

EC DECLARATION OF CONFORMITY

Company Name HAYTER LIMITED

Company Address Spellbrook
Bishop's Stortford
Herts. CM23 4BU
ENGLAND


Machine Type No..	CODE 340S	CODE 341S
Models	Harrier 56	Harrier 56 Electric Start

Directives complied with:
98/37/EC Essential Health & Safety Requirements Relating to the Design & Construction of Machinery and Safety Components.
84/538/EEC amended by 87/252/EEC and 88/180/EEC Permissible Sound Power Levels of Lawn Mowers
89/336/EEC amended by 92/31/EEC Electromagnetic Compatibility

Standards Used: EN292, EN836, ENISO14982

I declare on behalf of Hayter Limited that these machines conform to the EC Essential Health & Safety Requirements.

Signed



Date: 12.10.99 12.10.98

M.A. Wright
(Technical Director)

VIBRATION INFORMATION

Lawnmower vibration information, RMS acceleration measured in 3 - axes at operators contact position on the handlebars. **CODE 340S = 10.6 ms⁻² CODE 341S = 10.6 ms⁻²**

1.1

CONTENTS

1.1

CONTENTS

Page No.

INTRODUCTION

1.3

WARRANTY

1.4

Limited Warranty

1.4

SAFETY PRECAUTIONS

1.5 - 1.9

Decals

1.9

SPECIFICATIONS

1.10

ASSEMBLY INSTRUCTIONS

1.11 - 1.13

General Assembly

1.11

Assembling the Mower for the First Time

1.12 - 1.13

STARTING THE ENGINE

1.14 - 1.17

Before Starting the Engine

1.14 - 1.15

To Start the Engine

1.16 - 1.17

STOPPING THE ENGINE

1.18

OPERATING THE MOWER

1.19 - 1.24

Height of Cut

1.19

Travel

1.20

Turning the Mower

1.20

Mowing with Grass Collection

1.21

Mowing without Grass Collection

1.22

Heavy Growth

1.22

Moving the Mower across Non-Grassed Areas

1.22

Cutterbar Operation

1.23

Mowing and Grass Care Tips

1.23 - 1.24

MAINTENANCE

1.25 - 1.34

Engine

1.25

Throttle Cable Adjustment

1.25

Carburettor Adjustments

1.26

Oil Service

1.26

Air Cleaner Service

1.27

Spark Plug Service

1.27

Keeping the Engine Clean

1.28

Grassbag

1.28

Deck Housing

1.28

CONTENTS

Page No.

MAINTENANCE Continued.

Securing Nuts and Bolts	1.29
Lubrication	1.29
Clutch Cable Adjustment	1.29
Cutterbar	1.30 - 1.31
Battery Charging (Electric Start Model Only)	1.32
Maintenance Schedule	1.33 - 1.34
- After First 5 Hours	1.33
- Every 5 Hours or Daily	1.33
- Every 25 Hours or Every Season	1.33
- Every 50 Hours or Every Season	1.34
- Every 100 Hours or Every Season	1.34
- Every Season	1.34

PREPARING THE MOWER FOR STORAGE 1.35**FAULT FINDING 1.36 - 1.38****340S & 341S PARTS LIST 2.1 - 2.3****340S & 341S PARTS DIAGRAM 2.4****ENGINE ANCILLARY PARTS 2.5****WARRANTY ENGINE 2.6****NOTES 2.7****CUSTOMER INFORMATION 2.8**

INTRODUCTION

Thank you for purchasing a **Hayter** mower. The following pages are designed to help you gain safe and efficient service from your machine.

IMPORTANT: This 'Owners Handbook' should be regarded as part of the machine as it gives essential information regarding machine safety, operation, maintenance and specifications. Read and understand this handbook prior to operating your machine for the first time. Make sure you are familiar with all the controls and points of regular maintenance. If you have any doubts, consult your **Hayter** authorised dealer who will be pleased to give you assistance.

IMPORTANT: This machine is designed solely for use in a domestic grass cutting environment. Use in any other way is considered as contrary to the intended use. Compliance with and strict adherence to the conditions of operation, service and repair as specified in this handbook also constitute essential elements of the intended use.

This machine should be operated, serviced and repaired only by persons who are familiar with its particular characteristics and who are acquainted with the relevant safety procedures.

The safety precautions listed here in and all other generally recognised regulations on safety must be observed at all times.

Any arbitrary modifications carried out to this machine may relieve Hayter Limited of liability for any resulting damage or injury.

All **Hayter** mowers are robustly constructed and designed for efficient economical performance under normal mowing conditions. Correct operation and maintenance will ensure a long and satisfactory service life. Prior to despatch from our factory every effort is made to ensure your machine arrives in perfect condition. Your dealer will carry out a pre-delivery inspection to ensure that there has been no transit damage prior to installation. **Please allow your dealer to familiarise you with the controls and safety features of the machine during installation.**

Throughout this handbook all references to left hand and right hand are as viewed from behind the handlebar, facing in the direction of forward travel.

This handbook is based on information available at the time of publication. **HAYTER LIMITED** reserve the right to make changes at any time without notice.

LIMITED WARRANTY

Hayter Limited warrants to the original user/purchaser that this unit shall be free from defects in material and workmanship under normal use and service for a period of **three years** from the date of purchase. The manufacturers of the engine and battery pack system (where applicable) furnish their own warranty and services are provided through their authorised network (Refer to "Engine/Battery Pack Warranty Statement"). To qualify for the full benefit of the warranty, the warranty registration card must be returned within 60 days of purchase. Subject to the conditions and exclusions noted in this limited warranty, we shall at our option, repair or replace any warranted part during the applicable period. If you are in doubt or experience any difficulty, please consult a Hayter Authorised Service Dealer for clarification.

To qualify for the extended warranty (second and third year) of the three year limited warranty the machine must have annual services carried out by an Authorised Hayter Service Dealer. These chargeable services should be carried out within 12 and 24 months of the date of purchase.

Excluded from the extended warranty period are those items which are subject to normal wear and tear e.g. tyres, wheels, cutterbars, cables, batteries and other consumable wearing parts.

All consumer machines which are fitted with a **genuine** Hayter friction disc as original equipment before use, are covered by a **Lifetime Warranty** against the engine crankshaft bending. **Note:** friction washers, blade brake units and other such devices are not applicable. Only machines fitted with a **genuine** Hayter friction disc, which are used in accordance with the recommended operating and maintenance procedures, are covered.

This warranty does not apply to any unit that has been tampered with, altered, misused, abused or used for hire, and will become invalid if non genuine Hayter parts are fitted. This warranty does not cover minor mechanical adjustments unless they are due to defective material or workmanship. Consult the Owner's Handbook or a Hayter Authorised Service Dealer for assistance when making these adjustments.


A warranty period of 90 days applies to machines used for commercial purposes.

To make a warranty claim, return the unit to a Hayter authorised dealer along with proof of purchase stating the machine serial number and date of purchase. The service receipt(s) or this Owners Handbook with the 1st/2nd year service boxes fully completed, must be produced as proof of entitlement to the extended warranty period. Subject to the conditions and exclusions in this limited warranty, the authorised dealer will, at our option, repair or replace any warranted part within the duration of the warranty period.

This limited warranty gives you specific legal rights and is in addition to any statutory rights to which you may be entitled and your statutory rights are not affected by this warranty. If you need additional information concerning this written warranty, or assistance in obtaining services, please write to : **HAYTER LIMITED, Service Department, Spellbrook, Bishop's Cleeve, Hertfordshire CM23 4BU**

UK ONLY: Details of your local **Hayter** authorised dealer are contained in Yellow Pages or contact:- Freephone 0800 616298.

1st Year
Service
Record



2nd Year
Service
Record



Date.....

Date.....

Signed.....

Signed.....

SAFETY PRECAUTIONS



THIS SYMBOL MEANS BE ALERT! YOUR SAFETY IS INVOLVED. WHEN YOU SEE THIS SYMBOL BE ALERT TO THE POSSIBILITY OF INJURY. CAREFULLY READ THE MESSAGE THAT FOLLOWS AND INFORM OTHERS. EXERCISE GREAT CARE AND FOLLOW THE ADVICE GIVEN TO AVOID POTENTIALLY HAZARDOUS SITUATIONS.

The Harrier 56 is perfectly safe if used correctly. Failure to observe the following simple precautions may result in serious injury.

Training:



Read the instructions carefully. Ensure that you are familiar with the controls and the proper use of the equipment. Learn how to stop the mower quickly in an emergency.



Never allow children or people unfamiliar with these instructions to use the mower.



Never mow while people, especially children, or pets are nearby.



Keep in mind that the user is responsible for accidents or hazards occurring to other people or their property.

Preparation:



While mowing, always wear substantial footwear and long trousers. Do not operate the equipment when barefoot or wearing sandals.



Thoroughly inspect the area where the mower is to be used and remove all objects which may be thrown by the machine.



WARNING: Petrol is highly flammable.

- Store fuel in containers specifically designed for this purpose.

- Refuel outdoors only and do not smoke while refuelling.

- Add fuel before starting the engine. Never remove the cap from the fuel tank or add petrol while the engine is running or when the engine is hot. Allow the engine to cool for at least 2 minutes before refuelling.

- Do not attempt to start the engine if petrol is spilled or a smell of petrol is present. Move the mower away from the area of spillage and avoid creating any source of ignition until petrol vapours have dissipated.

SAFETY PRECAUTIONS

Continued.

- Always use fresh fuel. Stale fuel can block the carburettor and cause leakage.

- Replace fuel tank and container caps securely.



- Replace faulty exhaust mufflers.



Always ensure that the mower is in a safe operating condition. Frequently check all nuts, bolts and screws for tightness. Use only genuine **Hayter** replacement parts.



A damaged cutterbar or loose fixing bolt are major hazards. Before use, visually inspect the cutting mechanism to ensure that it is in good condition. A damaged cutterbar must be replaced immediately with a genuine **Hayter** replacement part. A cutterbar which is slightly worn can be re-sharpened. Ensure that both cutting edges are re-sharpened equally to maintain balance. An unbalanced cutterbar may cause serious damage to your machine. Refer to "Maintenance".

Operation:

Do not operate the engine in a confined space where dangerous carbon monoxide fumes can collect.



Always pull the starter cord slowly until resistance is felt. Then pull the cord rapidly to avoid kickback and prevent hand or arm injury.



Mow only in daylight or good artificial light.



Avoid using the mower on wet grass, where feasible.



Always be sure of your footing on slopes.



Walk, never run.



Mow across the face of slopes, never up and down.



Exercise extreme caution when changing direction on slopes.



Do not mow excessively steep slopes.



Use extreme caution when reversing or pulling the mower towards you.



Stop the engine if the mower has to be tilted for transportation when crossing surfaces other than grass and when transporting the mower to and from the area to be mowed.



Never operate the mower unless the guards are securely in position and in good condition.

SAFETY PRECAUTIONS

Continued.



Do not change the engine governor settings or overspeed the engine.



Disengage the rear roller drive clutch before starting the engine.



Start the engine carefully, with feet well away from the cutterbar.



Do not tilt the mower when starting the engine.



Do not put hands or feet near or under rotating parts.



Never pick up or carry a mower while the engine is running.



Stop the engine and disconnect the spark plug lead. (Also disconnect the negative battery lead on electric start models):

- Before clearing blockages or unclogging the discharge chute.

- Before cleaning / checking or working on the mower.

- After striking a foreign object. Inspect the mower for damage and make repairs before restarting and operating the mower.

- If the mower starts to vibrate abnormally (check immediately).



Stop the engine:

- Whenever you leave the mower.

- Before refuelling.



When using the machine without the grassbag, do not lift the deflector plate whilst the mower is in operation.



Never touch the engine muffler / muffler guard or cooling fins when the engine is hot.



WARNING: THE CUTTERBAR CAN CONTINUE TO ROTATE AFTER THE ENGINE IS SWITCHED OFF

SAFETY PRECAUTIONS


Continued.

Maintenance and Storage:

- ⚠ Keep all nuts, bolts and screws tight to ensure that the equipment is in safe operating condition.
- ⚠ Frequently check fuel lines and fittings for cracks or leaks and replace if necessary.
- ⚠ Never check for a spark with the spark plug removed. (Use an approved tester).
- ⚠ Never crank the engine with the spark plug removed. If the engine is flooded, move the throttle to the 'fast' position and crank the engine until it starts.
- ⚠ Never strike the flywheel with a hammer or hard object as this may cause the flywheel to shatter in operation. Always use the correct tools to service the engine.
- ⚠ Never operate the engine without a muffler guard. Inspect the muffler periodically and replace if worn or leaking.
- ⚠ Never start the engine with the air-cleaner or air-cleaner cover removed.
- ⚠ Never store the mower with petrol in the tank within an enclosed area where fumes may reach an open flame or spark.
- ⚠ Allow the engine to cool before storing in any enclosure.
- ⚠ To reduce the fire hazard, keep the engine, muffler, cooling fins, battery compartment and petrol storage area free of grass, leaves, or excessive grease.
- ⚠ Check the grassbag frequently for wear or deterioration.
- ⚠ Replace worn or damaged parts for safety.
- ⚠ If the fuel tank has to be drained, it is essential that this be done outdoors.

DECALS

WARNING DECAL: Part No. 219189




ENGINE STOP DECAL: Part No. 331046



CUT HEIGHT ADJUSTMENT DECAL:



THROTTLE CONTROL:



SPECIFICATIONS

MODELS	CODE 340S Self Propelled	CODE 341S Self Propelled/Electric Start
Engine	Briggs & Stratton INTEK-55	Briggs & Stratton INTEK-55
Engine Type	111682-0165-E1	111687-0166-E1
Engine / Cutterbar Speed	2900 rpm	2900 rpm
Fuel Type	Unleaded Petrol	
Fuel Capacity	1.5 litres	
Oil Type	SAE 30 engine oil	
Oil Sump Capacity	0.6 litres	
Cutting Width	560mm	
Cutting Height	10 - 60mm	
Overall Dimensions	1,511 x 591 x 1,156mm	
Dry Weight	50.5 Kg	53.5 Kg

ASSEMBLY INSTRUCTIONS

SAFETY NOTICE




Before using the mower, read the owner's handbook carefully.
Pay particular attention to the safety precautions.



GENERAL ASSEMBLY

1. Spark Plug lead
2. Engine Cover
3. Air Cleaner
4. Fuel Cap
5. Oil Filler Cap & Dip Stick
6. Handle Securing Knob
7. Engine Start Grip
8. Engine Stop Lever
9. Handlebar
10. Ground Drive Clutch Lever
11. Key (341S Only)
12. Throttle Control
13. Grassbag Assembly
14. Rear Deflector
15. Serial No. Label
16. Height of Cut Lever
17. Battery (341S Only)
18. Muffler Guard



2D340S1


ASSEMBLING THE MOWER FOR THE FIRST TIME

Check that parts are delivered correctly: Remove the mower from the packaging and check that all loose items have been supplied correctly. Refer to the delivery checklist opposite and the general assembly. If any items are missing contact, your local Hayter dealer.


DELIVERY CHECKLIST		
DESCRIPTION	QTY	
	440S	341S
Grassbag	1	1
Owner's Handbook	1	1
Charger	0	1
Ignition Key	0	1
Warranty Registration Card	1	1

Assemble the handlebar: Unscrew the knobs securing the handlebar sufficiently to allow it to be pivoted. Move the engine stop lever away from the engine to avoid damage and unfold the handlebar to its operating position. Tighten the two knobs to secure the handlebar.

IMPORTANT - PREVENT DAMAGE : When unfolding the handlebar, take care to ensure that the controls and cables do not become damaged. Always replace damaged controls and cables before using the mower.




Assemble the grassbag: Remove the long ribbon label (when fitted) by cutting it off close to the grassbag. Discard the ribbon label.



! WARNING - AVOID ENTANGLEMENT : Completely remove this ribbon before using the mower


Raise the rear deflector and hook the grassbag over the raised lip at rear of the mower deck. Lower the grassbag to rest against the rear of the mower. Finally lower the rear deflector to rest against the top of the grassbag.




ASSEMBLING THE MOWER FOR THE FIRST TIME

Continued.


Check that all fasteners are secure.




Check engine stop lever operation: Operate the engine stop lever several times. Ensure that the cable moves freely and that the lever returns automatically to the engine stop position when released.



Check throttle lever operation: Operate the throttle lever several times and ensure that the cable moves freely whilst operating the engine throttle mechanism. Slight resistance should be felt when the lever moves to the 'choke' position.



Check clutch lever operation: Operate the clutch lever several times and ensure that the cable moves freely.




Charge the battery: (Electric start model only)
Refer to "Maintenance".

BEFORE STARTING THE ENGINE

IMPORTANT - PREVENT ENGINE DAMAGE: The engine is shipped without oil or petrol. The engine must be filled with the correct grade of oil and petrol before starting the engine.

Oil recommendations: Always use high quality detergent oil classified "For service SE, SF, SG" SAE 30 oil. Never use additives with recommended oils. SAE 10W-30 multigrade oil may be used, but this will result in higher engine operating temperatures with consequential high oil consumption. It is imperative that the oil level is checked more frequently if this grade of oil is used in order to guard against serious engine damage.




Check oil level: Clean around the oil filler cap before removing. With the mower on a level surface, unscrew and remove the oil filler - dipstick. Wipe oil from it with a clean cloth. Screw the oil filler - dipstick back in place, then unscrew and remove it to check the oil level.

The oil level is correct when it is at the **full** mark on the dipstick. **DO NOT OVERFILL.**

Slowly fill with engine oil as necessary and replace the oil filler - dipstick.

IMPORTANT: The oil filler dipstick must be secured to prevent oil leakage during operation.



BEFORE STARTING THE ENGINE


Continued.

Fuel Recommendations: Always use clean, fresh unleaded petrol. Purchase fuel in quantities which can be used within 30 days. Never mix oil with petrol. For added engine protection Briggs & Stratton recommend the use of their fuel additive which is available from an authorised Briggs & Stratton service dealer.

Check fuel level: Clean around the fuel filler cap before removing and fill the fuel tank with clean unleaded petrol.

Do not overfill the fuel tank. Allow 6mm minimum of tank space for fuel expansion.


IMPORTANT: The fuel filler cap must be secured to prevent fuel leakage during operation.



WARNING - PREVENT ACCIDENTS: The cutterbar rotates when the engine is operating.


ALWAYS operate the engine stop lever several times and ensure the engine stop cable moves freely before starting the engine.

ALWAYS position the mower on a level stone free grass surface before starting the engine. Ensure that the cutterbar is set above grass height to prevent the engine being started under load.




TO START THE ENGINE


Operate the throttle control lever: Push the lever to 'choke' position before starting a cold engine. It should only be necessary to push the lever to the 'fast' position before starting a warm engine.



Operate the engine stop lever: Use one hand to hold the engine stop lever in the operating position firmly against the handlebar. To start and operate the engine the engine stop lever must be held in the operating position. If the engine stop lever is released the engine will stop.



Operate the engine start - grip: Stand behind the mower and maintain a firm hold on the handlebar and the engine stop lever to prevent the mower moving towards you. Use your right hand to hold the engine start - grip and pull slowly until resistance is felt, then pull rapidly to crank the engine. When the engine starts carefully return the engine start - grip to the storage position. If the engine does not start after 5 attempts - refer to "Fault Finding".



Allow the engine to warm up and return the throttle lever to the 'fast' position after starting a cold engine.

IMPORTANT - PREVENT ENGINE DAMAGE: Never pull the engine start - grip when the engine is running.

TO START THE ENGINE

Continued.

Operate the key switch: (Code 341S only). Stand behind the mower and maintain a firm hold on the handlebar and the engine stop lever to prevent the mower from moving. Using your left hand turn the ignition key clockwise and hold in position to crank the engine. When the engine starts release the key.

NOTE: Engine starter motor life is prolonged by using short start cycles of several seconds. Cranking the engine for more than 15 seconds every minute can damage the starter motor.

If the engine does not start - refer to "Fault Finding".


Allow the engine to warm up and return the throttle lever to the 'fast' position after starting a cold engine.

NOTE: If necessary the engine can be started manually without using the key switch - refer to "**Operate the engine start - grip**".

IMPORTANT - PREVENT ENGINE DAMAGE: Do not operate the ignition key when the engine is running.


STOPPING THE ENGINE

Stopping the engine: Reduce the throttle setting and disengage the engine stop lever by releasing the lever.



CS259

Emergency stop: If the engine stop lever fails, move the throttle lever to the 'slow' position and disconnect the spark plug lead to stop the engine.




CS229

1. Engine
2. Spark Plug Lead
3. Spark plug

SAFETY NOTICE



WARNING - PREVENT ACCIDENTAL STARTING : Always stop the engine and disconnect the spark plug lead before cleaning, inspecting or working on the machine. Also disconnect the negative battery lead if the mower is equipped with electric start.




1. Engine
2. Spark Plug Lead
3. Spark plug

SAFETY NOTICE



WARNING - PREVENT ACCIDENTS: Before mowing, thoroughly inspect the area where the mower is to be used and remove all objects which when contacted by the mower cutterbar could become dangerous projectiles.

Inspect the area for hidden obstructions which when contacted by the cutterbar could risk health and safety. Remember the location of these obstructions and ensure that you mow around them.



CS031


IMPORTANT - PREVENT ENGINE DAMAGE : DO NOT use the mower on a slope greater than 20 degrees.



CS083

HEIGHT OF CUT

To adjust the height of cut: Grip the lever and pull sideways to disengage it from the locking notch, then push forwards to lower or pull backwards to raise the height of cut. Finally release the lever at the required position and ensure it locks firmly into one of the nine setting notches.



CS088

Always select a height of cut to suit operating conditions. Aim to prevent engine overloading and blockages by avoiding low cuts in long grass conditions. Be prepared to make two cuts when the grass is long.

TRAVEL

Forward travel: Hold the handlebar and operate the clutch lever to power the mower in a forward direction.

Travel speed is controlled by engine speed. Use the throttle control to increase forward travel speed.

Release the clutch lever to stop the mower from travelling in a forward direction.



When the clutch lever is disengaged the mower can be operated as a push model. This feature is useful when mowing in confined areas.

Reverse travel: Release the clutch lever. Hold and pull against the handlebar with both hands to reverse the mower towards you.



WARNING - PREVENT ACCIDENTS: Always reverse the mower carefully towards you. Always switch off the engine before walking backwards with the mower.

The travel speed can be reduced, if desired, by using an optional 'Kit Speed Reduction' - Part No. 219207 which is available through your Hayter dealer.



TURNING THE MOWER

To make a wide turn: Steer the mower with the handlebar in the direction required.

To make a tight turn: Stop and apply downward pressure on the handlebar to raise the front wheels of the mower just above ground level and steer the mower using the handlebar in the required direction.



WARNING - PREVENT ACCIDENTS: DO NOT raise the front of the mower excessively when making a turn. NEVER raise the rear of the mower when the engine is running.



MOWING WITH GRASS COLLECTION

The grassbag is designed to collect grass clippings. For optimum performance, mow in dry conditions with the throttle control set at 'fast'.





WARNING - PREVENT ACCIDENTS: ALWAYS check the condition of the grassbag for signs of damage. Replace a damaged grassbag immediately. DO NOT operate the mower with a damaged grassbag. ALWAYS stop the engine and disconnect the spark plug lead before attempting to remove a grass blockage.

Grassbag attachment: Raise the rear deflector and hook the grassbag over the raised lip at the rear of the mower deck. Lower the grassbag to rest against the rear of the mower. Finally lower the rear deflector to rest against the top of the grassbag.




Grassbag removal: Raise the rear deflector and lift the grassbag away from the mower. Finally lower the rear deflector to rest against the rear of the mower.



Grassbag emptying: To empty the grassbag, pour out the grass clippings and shake the grassbag vigorously to clean the airways. Good grass collection depends on good air flow through the grassbag. When collecting grass clippings it is important that the grassbag is emptied regularly to prevent blockages and engine overloading.

MOWING WITHOUT GRASS COLLECTION

To mow without collecting the grass clippings, remove the grassbag and operate the mower with the rear deflector in its lowest position.



WARNING - PREVENT ACCIDENTS: ALWAYS check the condition of the rear deflector for signs of damage. Replace a damaged rear deflector immediately. never operate the mower with a damaged rear deflector.

HEAVY GROWTH

Areas of heavy growth should be mown without grass collection. If grass collection is required, first mow the area without grass collection at the maximum height of cut setting. Allow the grass clippings to dry out and then mow the area at the maximum height of cut setting with the grassbag fitted. Reduce the height of cut and mow the area again as necessary until the required finish is obtained.

MOVING THE MOWER ACROSS NON-GRASSED AREAS

Set the mower to its maximum height of cut to protect the cutting mechanism when moving the mower over surfaces other than grass.



WARNING - PREVENT ACCIDENTS : Push the mower carefully at slow walking speed with the engine switched off.


CUTTERBAR OPERATION

The cutterbar rotates at the same speed as the engine. The cutterbar will stop within three seconds of the engine being switched off.



WARNING - PREVENT ACCIDENTS : DO NOT operate the mower if the cutterbar fails to stop within three seconds. Return the mower to your Hayter dealer for examination and repair.

The cutterbar is driven by the engine via a friction device to help prevent damage occurring to the cutting mechanism when a hidden obstruction or overload is encountered. When the obstruction or overload is removed the friction device will automatically reset.



WARNING - PREVENT ACCIDENTS: ALWAYS stop the engine when a hidden obstruction or excessive vibration is encountered. Disconnect the spark plug lead (also disconnect the negative battery lead if the mower is equipped with electric start) and examine the cutting mechanism. ALWAYS replace a damaged cutterbar - refer to "Maintenance".

MOWING AND GRASS CARE TIPS

In dry weather conditions leave the grass long to help retain ground moisture.

Aerate the lawn to stimulate soil organisms and root growth. In spring and late summer remove dead grass and aerate the lawn by raking or similar means.

Keep the cutterbar sharp. A blunt cutterbar will tear the grass and cause the tips to turn brown.

MOWING AND GRASS CARE TIPS

Continued.

Prevent scalping. Plan your direction of travel to mow across hollows and humps.

Prevent grass damage. Take care when turning the mower.

Prevent grass damage. **DO NOT** mow in wet conditions.

Brush the lawn surface to disperse worm casts before mowing.

Spike compacted lawn areas with a fork. Fill the holes with sand to improve aeration and drainage.

Mow lawns in a different direction to the previous cut.


As a general rule the grass clippings should be removed each time you mow. If weather conditions are dry and hot and the grass is weed free, leave the clippings on the lawn to help maintain ground moisture.

Mow lawns twice a week when the grass is growing vigorously in the summer.

Mow lawns once a week in spring, autumn and during prolonged dry weather in the summer.

Prevent grass damage - DO NOT remove more than one third of the grass height in one cut.

Recommended grass heights for lawns:



340225BD150100A


MAINTENANCE



WARNING - PREVENT ACCIDENTS: Stop the engine and disconnect the spark plug lead (also disconnect the negative battery lead on electric start models) before attempting to carry out maintenance procedures on the mower.

ENGINE


1. Engine
2. Spark Plug / Lead
3. Carburettor
4. Muffler Guard
5. Choke Lever
6. Air Cleaner
7. Fuel Tank
8. Fuel Filler
9. Start Grip
10. Finger Guard
11. Oil Fill/ Dipstick



3405FIG1

THROTTLE CABLE ADJUSTMENT

Loosen casing clamp screw (2). Move the governor control lever (3) in direction of the arrow as far as possible. Move the throttle control to the **FAST** position. Tighten the casing using the clamp screw.



340225BD150100A

CARBURETTOR ADJUSTMENTS

Carburettor adjustments should only be made by an authorised Briggs & Stratton dealer. Under no circumstances should the engine be adjusted to run at a speed in excess of 3,000 r.p.m.


OIL SERVICE

Refer to the Maintenance Schedule at the end of this section and ensure that the recommendations are followed. More frequent service is required when operating in adverse conditions.

- Check the oil level every 5 hours or daily and ensure that the correct oil level is maintained. Refer to 'Before Starting the Engine Oil Recommendations' for oil checking procedure and filling instructions.
- Drain the engine oil after the first 5 hours of operation and thereafter at the end of every grass cutting season.
- Change the oil while the engine is warm. Refill with fresh clean oil of the recommended SAE viscosity grade. Refer to 'Before Starting the Engine: Oil Recommendations'.


! WARNING - PREVENT ACCIDENTS: Drain fuel from the tank by running the engine until the fuel tank is empty before attempting to tip the mower for oil draining purposes.

- Remove the spark plug lead (also disconnect the negative battery lead if the mower is equipped with electric start) and allow the engine to cool. Tip the mower over on to its left hand side thus ensuring that the air cleaner is kept uppermost to prevent engine damage. Remove the oil filler dipstick and drain the oil into a suitable container.

**AIR CLEANER SERVICE**

Refer to the Maintenance Schedule at the end of this section and ensure that the recommendations are followed. More frequent service is required when operating in adverse conditions.

- Gain access to the pre-cleaner (4) by loosening screw (2) and lifting cover (3).
- To service the pre-cleaner, carefully remove and wash in a solution of liquid detergent and water. Allow to air dry thoroughly before replacing. Do not oil the pre-cleaner.
- Clean the cartridge (5) by tapping gently on a flat surface. If very dirty, replace or wash in a solution of non-foaming detergent and warm water. Rinse thoroughly with running water from the mesh side until the water is clear. Allow the cartridge to stand and air dry thoroughly before replacing. Do not use petroleum solvents during cleaning as this will cause the cartridge to deteriorate. Do not use pressurised air as this may damage the cartridge. Do not oil the cartridge.
- After servicing, install the pre-cleaner and cartridge in the cover. Insert the tabs on the bottom of the cover into the slots in the bottom of the base. Tilt the cover upwards and securely tighten the screw to the base (6).





2. Screw
3. Cover
4. Pre-cleaner
5. Cartridge
6. Base

SPARK PLUG SERVICE

Use only Briggs & Stratton spark tester (2) to check for a spark as shown in the diagram.

Replace the spark plug every 100 hours or every season, whichever occurs first. A spark plug wrench is available from any authorised Briggs & Stratton service dealer.

The spark plug gap (1) should be checked with a feeler gauge and set at 0.76mm (0.030").



KEEPING THE ENGINE CLEAN

WARNING - PREVENT ACCIDENTS : Accumulation of debris around the muffler could cause a fire. Inspect and clean the engine after every use.

Remove all grass and debris from the engine including the muffler / muffler guard, the air ways in the top cowl and the surrounding deck areas on a daily basis after use. To ensure smooth operation keep the governor linkage springs and controls free of debris.

IMPORTANT - PREVENT ENGINE DAMAGE: Never spray the engine with water during cleaning. Water can contaminate the fuel. Always clean with a brush or compressed air.

NOTE: Grass and debris may clog the engine's air cooling system especially after prolonged operation while cutting tall, dry grass. The internal cooling fins and surfaces may require cleaning to prevent overheating and engine damage. We would recommend that this service be carried out by an authorised Briggs & Stratton dealer.

GRASSBAG

Remove grass debris from the grassbag immediately after use and check its condition for signs of damage.



WARNING - PREVENT ACCIDENTS: Replace a damaged grassbag immediately.



CS110


DECK HOUSING

Remove grass debris from the top and underside of the deck housing immediately after use.

IMPORTANT - PREVENT DAMAGE: Fertilisers and top dressings are particularly corrosive. Thoroughly clean the mower deck immediately after use on treated grass and store well away from corrosive materials.

SECURING NUTS AND BOLTS

Regularly check that all securing nuts and bolts are tight. Replace missing or damaged items immediately.




CS015

LUBRICATION

Lubricate the wheels, pivot points and linkages with engine oil every 25 operating hours.


Apply a good quality medium grease to the inner control cables at the point of entry and exit from their outer casings.



CS022


CLUTCH CABLE ADJUSTMENT

Check the clutch cable operation every 25 operating hours and adjust if necessary. The clutch cable is adjusted correctly when the belt drive just engages with the clutch lever positioned 32-38mm from the handlebar.



CS012

Set the plastic adjuster (A) as necessary.



CS122

If further adjustment is required, unscrew the lock nut (1) and screw the adjuster (2) in or out as necessary. Tighten the locknut (1) when correctly adjusted.



IMPORTANT - PREVENT DAMAGE: ALWAYS operate the mower with the clutch cable correctly adjusted. **ALWAYS** replace damaged cables.

CUTTERBAR



WARNING - PREVENT ACCIDENTS: Never work on the cutterbar unless the spark plug lead has been removed (also disconnect the negative battery lead on mowers equipped with electric start). The cutterbar has sharp edges. ALWAYS wear strong gloves to protect your hands when working on the cutterbar. DO NOT rotate tools towards the cutting edges to avoid the risk of injury should the tool slip. ALWAYS use genuine Hayter replacement parts.

The condition of the cutterbar and its mounting arrangement should be checked regularly for signs of wear or damage. Ensure that the cutterbar is not bent or cracked.

A damaged cutterbar that is out of balance will vibrate excessively and may break. DO NOT use an unbalanced cutterbar.

Regularly check that the bolt securing the cutterbar is tightened to the specified torque of 54Nm.

Replace the cutterbar every 2 years or sooner if excessively worn or damaged.


How to remove the cutterbar: Drain the fuel by operating the engine until the fuel tank is empty and the engine stops. Remove the spark plug lead and allow the engine to cool. Turn the mower on its left hand side and ensure that the air cleaner side of the engine is uppermost.



WARNING - PREVENT INJURY: It is wise to seek assistance when turning the mower on its side.

Firmly grip the end of the cutterbar with the gloved hand and remove the bolt, spring washer and distance piece securing the cutterbar with a 9/16" A/F spanner.


How to assemble the cutterbar: Assemble the cutterbar with the turned up edges facing towards the engine. Secure the cutterbar using the original bolt, spring washer and distance piece and tighten to a torque of 54Nm.



CUTTERBAR


Continued.

How to sharpen and balance the cutterbar: A slightly worn cutterbar may be re-sharpened. Both cutting edges must be sharpened equally to ensure balance. Sharpen the cutterbar every 25 mowing hours or more frequently if conditions require. Remove the cutterbar from the mower and clean using a brush and water. Inspect the cutterbar for signs of damage.




WARNING - PREVENT ACCIDENTS : DO NOT use a damaged or excessively worn cutterbar.

Sharpen both cutting edges with a flat file to restore the original cutting edge.



Ensure that the cutterbar is balanced. Use a screw driver with a round shaft to support the cutterbar through its centre hole. Hold the cutterbar horizontal and then release. A balanced cutterbar will remain horizontal. If the cutterbar is not balanced the heavy end will rotate downwards. Sharpen the heavy end until the cutterbar is correctly balanced.



BATTERY CHARGING

(Electric Start Model Only)



WARNING - PREVENT ACCIDENTS : ALWAYS charge the battery in a well ventilated area.

NEVER charge the battery near naked flames or direct heat.

ALWAYS switch off the mains electricity supply before disconnecting the charger from the battery.

ALWAYS use the battery charger supplied with the mower.

Battery charging should not be necessary during normal use. The engine operation will automatically charge the battery. If the mower is stored for a long period, recharging the battery may be necessary to permit electric starting.

Charge the battery only when necessary.

To recharge the battery:

Disconnect the battery lead from the mower lead and then connect the battery lead to the charger.


Connect the charger plug to the mains electricity supply and switch on to charge the battery for a six hour period.

Switch off the mains electricity supply and disconnect the charger plug.


Disconnect the battery lead from the charger and then connect the battery lead to the mower lead.

IMPORTANT - PREVENT DAMAGE: NEVER connect the battery charger to the engine lead as this will cause the charger to be permanently damaged. Chargers damaged in this manner will not be replaced under warranty.


CAUTION - PREVENT ENVIRONMENTAL DAMAGE: The battery has a separate collection mark. This indicates that the battery must be taken to an authorised disposal site. It must not be disposed of with general waste.



CS150



CS205

**MAINTENANCE SCHEDULE**

Follow the hourly or calendar intervals, whichever occurs first. More frequent service will be required if working for prolonged periods under dusty, dry conditions, or when airborne debris is present or after extensive operation cutting tall, dry grass.

AFTER FIRST 5 HOURS

- Change engine oil

EVERY 5 HOURS OR DAILY

- Check oil level
- Remove grass debris from around engine, muffler/muffler guard and air ways in the top cowl.
- Remove grass debris from top and underside of deck housing.
- Remove grass debris from the grassbag and check for signs of damage.
- Check condition of guards and safety devices.
- Check condition of cutterbar.

EVERY 25 HOURS OR EVERY SEASON

- Change engine oil if continuously operating under heavy load or high ambient temperature.
- Service the dual element air cleaner - pre cleaner.
- Lubricate wheels, pivot points and linkages.
- Grease inner control cables at point of entry and exit from their outer casings.
- Check clutch cable adjustment.
- Sharpen cutterbar.

EVERY 50 HOURS OR EVERY SEASON

- Change engine oil.

EVERY 100 HOURS OR EVERY SEASON


- Clean engine cooling system. Clean more often under dusty conditions or when airborne debris is present or after prolonged operation whilst cutting tall, dry grass.
- Service the dual element air cleaner cartridge.
- Replace spark plug.

EVERY SEASON

- Check valve clearance.

PREPARING THE MOWER FOR STORAGE

Handlebar storage: To lower the handlebar unscrew the 2 securing knobs sufficiently to allow it to be pivoted forwards to rest against the mower. Take care to ensure that the control cables do not become snagged at the pivot point and depress the engine stop lever to prevent it being damaged through contact with the engine spark plug.



Storage for periods in excess of 30 days: Engines stored in excess of 30 days need to be protected with Briggs & Stratton fuel additive or drained of fuel to prevent gum from forming in the fuel system or on essential carburettor parts. To ensure your mower is maintained in good working order it is important that the following procedure is adopted. Refer to the Maintenance section as necessary.

Drain fuel from the engine by operating the engine until it stops.

Disconnect the spark plug lead.

Change the engine oil.

Remove the engine spark plug and pour 15ml of engine oil into the engine cylinder and replace the spark plug. Do not exceed the stated volume of oil as engine damage may occur on re-starting. **Do not replace the spark plug lead.** Slowly pull the engine start - grip once to crank the engine. This will distribute the oil and help prevent engine corrosion.

Clean grass and debris from the engine cylinder, cylinder head cooling fins, under top cowl, and around and behind muffler/muffler guard.

Clean all other areas of the mower and ensure that the grassbag is clean.

Charge the battery (Electric start models only)

Lubricate the mower.

Treat metal parts with a water repellent anti-corrosion product.

Lower the handlebar, if desired.

Disconnect the battery leads (electric start models only).

Rest the mower deck on wooden blocks to remove the mower from its wheels / roller.

Cover the mower with a protective sheet and store it in a dry, ventilated area.

FAULT FINDING

PROBLEM	POSSIBLE FAULT	REMEDY
Engine will not turn over	Engine stop lever released	Operate engine stop lever
	Incorrect oil level	Check oil level
	Obstruction under deck	Remove obstruction
	Battery discharged (electric start models)	Charge battery
Engine smokes	Excess oil level	Check oil level
	Air cleaner cartridge oil soaked or plugged	Service air cleaner
Engine runs then stops	Fuel starvation	Fill fuel tank
	Fuel cap vent blocked	Clean fuel cap vent

FAULT FINDING

Continued.

PROBLEM	POSSIBLE FAULT	REMEDY
Engine will not start	Engine under load	Raise height of cut
	Fuel starvation	Fill fuel tank
	Engine cold	Set throttle to 'choke' position
	Incorrect/contaminated fuel	Drain fuel tank and fill with correct fuel
	Spark plug lead disconnected	Connect spark plug lead
	Throttle setting incorrect	Set throttle to 'fast' position
	Engine brake not released	Operate engine brake lever
	Faulty spark plug	Clean and adjust gap or replace
	Battery discharged (electric start models)	Charge battery
	Wiring fault (electric start models)	Check wiring
Engine runs rough	Spark plug lead becoming disconnected in use	Connect spark plug lead
	Faulty spark plug	Clean and adjust gap or replace
	Air cleaner blocked	Service air cleaner
	Incorrect/contaminated fuel	Drain fuel tank and fill with correct fuel
Engine vibrates excessively	Mounting bolts loose	Tighten bolts
	Cutterbar bolt loose	Tighten bolt
	Cutterbar out of balance	Balance cutterbar
	Bent crankshaft	Consult your dealer

FAULT FINDING

Continued.

PROBLEM	POSSIBLE FAULT	REMEDY
Uneven cut	Undulating ground conditions	Change direction of travel
	Cutterbar worn	Sharpen the cutterbar
	Cutterbar out of balance	Balance the cutterbar
	Wheels / roller damaged	Inspect and replace as necessary
Discharge chute blocks	Grass is wet	Mow dry grass
	Cut height too low	Increase cut height
	Grassbag full	Empty grassbag
	Slow engine speed	Increase engine speed
	Airflow through the grassbag is restricted	Clean the grassbag
Mower is hard to push	Cut height too low	Increase cut height
	Wheels / roller damaged	Inspect and lubricate or replace as necessary
Mower will not self propel	Clutch out of adjustment	Adjust clutch cable
	Drive belt damaged	Replace drive belt
Poor grass collection	Airflow through the grassbag is restricted	Clean the grassbag
	Discharge chute blocked	Remove blockage
	Slow engine speed	Increase engine speed
	Wet grass	Mow dry grass
	Grassbag full	Empty grassbag

340225BD150100A

PARTS LIST

ITEM NO.	DESCRIPTION	PART NO.	340S QTY	341S QTY
1	Belt	340049	1	1
2	5/8" Circlip	1428	1	1
3	Woodruff Key	1662	1	1
4	3/16" Washer	09257	4	4
5	Spring	5421	2	2
6	Cutterbar	340015	1	1
7	5/8" Plain Washer	09286	1	1
8	5/16" Spring Clip	04020	1	1
9	1/2" x 5/8" x 3/4" Bush	4452	1	1
10	M6 x 12 Csk. Pozi Taptite Screw	09545	4	4
11	Wheel	5218	2	2
12	Hub Cap	219143	2	2
13	M6 Nut - Nylon Insert 'T' Type	09544	1	1
14	M6 x 20 Hex Hd. Taptite Screw	09575	2	2
15	1/2" Plain Washer	02575	1	1
16	Friction Disc	219203W	1	1
17	5/16" Plain Washer	09266	1	1
18	1/2" Plain Washer	09280	2	2
19	M6 Plain Washer	09472	5	5
20	Handlebar Clamp	340028	2	2
21	3/4" Circlip	02708	2	2
22	1/2" Circlip	03096	1	1
23	3/16" x 3/4" Roll Pin	03997	4	4
24	3/8" UNC x 1.1/4" Taptite Screw	09349	3	3
25	3/8" UNF x 1.1/4" Hex Hd. Setscrew	09116	1	1
26	1/2" UNF Nylon Insert Nut	4486	2	2
27	5/16" Starloc Washer	0201086	2	2
28	Height Adjuster Knob	330053	1	1
29	3/8" Spring Washer	09273	1	1
30	Pulley	219111	1	1
31	Spring	1246	1	1
32	Pozi Pan Screw	09780	1	1
33	M6 x 16 Hex Hd. Taptite Screw	09365	23	23
34	Frame Rear Roller	340044	1	1
35	M8 x 40 Coach Bolt	09379	2	2
36	M6 x 12 Washer Head Taptite Screw	09546	2	2
37	M8 Nut Nylon Insert 'T' Type	09441	2	2
38	Rivet	09320	4	4
39	M6 x 20 Coach Bolt	09668	2	2
40	M6 x 30 Hex. Head Bolt	09547	1	1
41	6mm x 20 Screw	09687	2	2
42	M8 x 45 Coach Bolt	226024	2	2

340225BD150100A

PARTS LIST


ITEM NO.	DESCRIPTION	PART NO.	340S	341S
			QTY	
43	Distance Piece	4014	1	1
44	19mm Nylon Washer	09688	2	2
45	Mainframe Assembly	340205V	1	1
46	Throwplate	340011	1	1
47	Idler Sprocket Sleeve Assembly	219095	1	1
48	Ratchet Plate	340102	1	1
49	Engine Brake Cable	341031	1	1
50	Nut Cap	234051	2	2
51	Lower Handlebar - Nearside	340103	1	1
52	Jockey Lever	219023	1	1
53	Sprocket - 10 Teeth	219106	1	1
54	Securing Plate	219028	1	1
55	Woodruff Key	5321	1	1
56	Connecting Rod	340014	1	1
57	Front Axle Assembly	340020	1	1
58	Bearing Moulding	219036	2	2
59	Securing Plate	219037	2	2
60	Jockey Pulley	219156	1	1
61	Sprocket - 17 Teeth	219051	1	1
62	Lower Handlebar - Offside	340104	1	1
63	Engine - Compliance A.P.T.O.	340221	1	0
	Engine - Compliance A.P.T.O.	341027	0	1
64	Spacer	219053	1	1
65	Electric Start	341032	0	1
66	Transmission Cover	219055	1	1
67	Coupling	340109	1	1
68	Bearing Housing Moulding	219060	1	1
69	Pulley Assembly	340105	1	1
70	Belt Guide Bracket	219064	1	1
71	Chain	219054	1	1
72	Transmission Cover	340050	1	1
73	Underguard	340051	1	1
74	Rear Deflector	340022	1	1
75	Pivot Rod	340024	1	1
76	Deflector Spring	340052	2	2
77	M6 Plain Nut	09437	3	3
78	Front Fin Insert	340190	1	1
79	Rope Guide	305093	1	1
80	Clutch Lever	306094W	1	1
81	Nut - M6 Nyloc Insert	09438	1	1
82	M6 Spring Washer	09474	3	3

340225BD150100A


PARTS LIST

ITEM NO.	DESCRIPTION	PART NO.	340S	341S
			QTY	
83	Caution Decal	219189	1	1
84	Handwheel	226013	2	2
85	Grassbag Fabric	340071	1	1
86	Clutch Cable	341030	1	1
87	Tube Plug	300160	2	2
88	Roller Bearing Housing	219102	2	2
89	Grassbag Cover	340072	1	1
90	Grassbag Assembly (Includes Items 4, 38, 85, 89, 93, 94 & 95)	340070	1	1
91	Cable Tie	3966	3	3
92	Brush Seal	340082	1	1
93	Grassbag Handle	340073	1	1
94	Grassbag Frame Assembly	340075	1	1
95	'U' Tube	340078	1	1
96	Decal - Hayter & Royal Warrant	219186	1	1
97	Oilite Bush - Roller	340129	2	2
98	Roller Assembly	340139	2	2
99	Spacer - Nylon	340149	2	2
100	Roller Free Wheel	340150	2	2
101	Bush	340154	2	2
102	Locknut	340163	1	1
103	Roller Shaft	340162	1	1
104	Shroud Freewheel	340168	1	1
105	Rope Stop	MU42189	1	1
106	Engine Lever	340179	1	1
107	Pivot Pin	340182	2	2
108	Upper Handlebar	341029W	1	1
109	Decal - Engine Stop	331046	1	1
110	Charger	226006	0	1
111	Decal - Engine	340224	1	1
112	Throttle Control & Cable	341028	1	1
113	Battery 12V	220015	0	1
114	Battery Clip	220014	0	1
115	Avdel Rivet	09318	0	2
116	Battery Bracket	220013	0	1
117	Ignition Key	6426	0	1
118	Drive fasteners	300144	2	2

340225BD150100A



These parts are available through an authorised Briggs & Stratton dealer.



FUEL ADDITIVE

P/N 5041
999005E




992030

AIR CLEANER CARTRIDGE

690610

273356



SPARK PLUG




991095

SPARK PLUG WRENCH



19374

SPARK PLUG TESTER



19368

About Your Engine Warranty

Briggs & Stratton welcomes warranty repair and apologizes to you for being inconvenienced. Any Authorized Service Dealer may perform warranty repairs. Most warranty repairs are handled routinely, but sometimes requests for warranty service may not be appropriate. For example, warranty would not apply if engine damage occurred because of misuse, lack of routine maintenance, shipping, handling, warehousing or improper installation. Similarly, warranty is void if the serial number of the engine has been removed or the engine has been altered or modified.

If a customer differs with the decision of the Service Dealer, an investigation will be made to determine whether the warranty applies. Ask the Service Dealer to submit all supporting tests to the Distributor or the Factory for review. If the Distributor or the Factory decides that the claim is justified, the customer will be fully reimbursed for those items that are defective. To avoid misunderstanding which might occur between the customer and the Dealer, listed below are some of the causes of engine failure that the warranty does not cover.

Improper maintenance:

The life of an engine depends upon the conditions under which it operates, and the care it receives. Some applications, such as tillers, pumps and rotary mowers, are very often used in dusty or dirty conditions, which can cause what appears to be premature wear. Such wear, when caused by dirt, dust, spark plug cleaning grit, or other abrasive material that has entered the engine because of improper maintenance, is not covered by warranty.

This warranty covers engine related defective material and/or workmanship only, and not replacement or refund of the equipment to which the engine may be mounted. Nor does the warranty extend to repairs required because of:

1. PROBLEMS CAUSED BY PARTS THAT ARE NOT ORIGINAL BRIGGS & STRATTON PARTS.
2. Equipment controls or installations that prevent starting, cause unsatisfactory engine performance, or shorten engine life. (Contact equipment manufacturer.)
3. Leaking carburetors, clogged fuel pipes, sticking valves, or other damage, caused by using contaminated or stale fuel. (Use clean, fresh, lead-free gasoline and Briggs & Stratton gasoline stabilizer, Part No. 5041.)
4. Parts which are scored or broken because an engine was operated with insufficient or contaminated lubricating oil, or an incorrect grade of lubricating oil (check oil level daily or after every 8 hours of operation. Refill when necessary and change at recommended intervals.) Read "Owner's Manual".
5. Repair or adjustment of associated parts or assemblies such as clutches, transmissions, remote controls, etc., which are not manufactured by Briggs & Stratton.
6. Damage or wear to parts caused by dirt, which entered the engine because of improper air cleaner maintenance, re-assembly, or use of a non-original air cleaner element or cartridge. (At recommended intervals, clean and re-oil the Oil

Foam® element or the foam pre-cleaner, and replace the cartridge.) Read "Owner's Manual."

7. Parts damaged by over-speeding, or overheating caused by glass, debris, or dirt, which plugs or stops the cooling fins, or flywheel area, or damage caused by operating the engine in a confined area without sufficient ventilation. (Clean fins on the cylinder, cylinder head and flywheel at recommended intervals.) Read "Owner's Manual."
8. Engine or equipment parts broken by excessive vibration caused by a loose engine mounting, loose cutter blades, unbalanced blades or loose or unbalanced load impellers, improper attachment of equipment to engine cranshaft, over-speeding or other abuse in operation.
9. A bent or broken crankshaft, caused by striking a solid object with the cutter blade of a rotary lawn mower, or excessive vibration.
10. Routine tune-up or adjustment of the engine.
11. Engine or engine component failure, i.e., combustion chamber, valves, valve seats, valve guides, or burned starter motor windings, caused by the use of alternate fuels such as, liquefied petroleum, natural gas, altered gasolines, etc.

Warranty is available only through service dealers which have been authorized by Briggs & Stratton Corporation, your nearest Authorized Service Dealer is listed in the "Yellow Pages" of your telephone directory under "Engines, Gasoline" or "Gasoline Engines," "Lawn Mowers," or similar category.

Briggs & Stratton Engine Owner Warranty Policy

Effective February 1, 1994, replaces all undated Warranties and all Warranties dated before February 1, 1994.

LIMITED WARRANTY

Briggs & Stratton Corporation will repair or replace, free of charge, any part or parts of the engine that are defective in material or workmanship or both. Transportation charges on parts submitted for repair or replacement under this Warranty must be borne by purchaser. This warranty is effective for the time periods and subject to the conditions provided for in this policy. For warranty service contact your nearest Authorized Service Dealer as listed in the "Yellow Pages" under "Engines, Gasoline," "Gasoline Engines," "Lawn Mowers" or similar category. THERE IS NO OTHER EXPRESS WARRANTY. IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED TO ONE YEAR FROM PURCHASE, OR TO THE EXTENT PERMITTED BY LAW AND ALL IMPLIED WARRANTIES ARE EXCLUDED. LIABILITY FOR CONSEQUENTIAL DAMAGES UNDER ANY AND ALL WARRANTIES ARE EXCLUDED TO THE EXTENT EXCLUSION IS PERMITTED BY LAW. Some states do not allow limitations on how long an implied warranty lasts, and some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation and exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

Briggs & Stratton Corporation

F. P. Stratton, Jr.
F. P. Stratton, Jr.
Chairman and Chief Executive Officer

WARRANTY PERIOD

ENGINES	WITHIN U.S.A. AND CANADA		OUTSIDE U.S.A. AND CANADA	
	CONSUMER USE*	COMMERCIAL USE*	CONSUMER USE*	COMMERCIAL USE*
All Vanguard® engines	2 year - engine / Lifetime** - Magnetron® Ignition			
All Diamond Plus®, Europa™, Industrial Plus™ and all UC®	2 year	1 year	2 year	1 year
Quantum® and Diamond Power®	2 year	90 days	2 year†	90 days
All standard 2 through 18 HP engines installed on lawn mowers, riders, edgers, chippers, shredders, tillers, and all Sno-Gard engines.	2 year	90 days	1 year	90 days
All other standard 2 through 18 HP engines	1 year	90 days	1 year	90 days

* For purposes of this warranty policy, "consumer use" means personal residential household use by the original retail consumer. "Commercial use" means all other uses, including use for commercial, income producing or rental purposes. Once an engine has experienced commercial use, it shall thereafter be considered as a commercial use engine for purposes of this warranty. Engines used in competitive racing or on commercial or rental tracks are not warranted.

** Lifetime limited warranty of the Magnetron® ignition covers parts and labor for the first five (5) years from the date of purchase; thereafter only parts. "Lifetime" means lifetime of the engine in the hands of the original purchaser.

† One (1) year in Australia, New Zealand, Middle East and Africa.

NO WARRANTY REGISTRATION CARD IS NECESSARY TO OBTAIN WARRANTY ON BRIGGS & STRATTON ENGINES. YOU MUST SAVE THE PURCHASE RECEIPT. A PROOF OF PURCHASE DATE WILL BE REQUIRED TO OBTAIN WARRANTY.

Briggs & Stratton Engines Are Made Under One Or More Of The Following Patents: Design D-247,177 (Other Patents Pending)									
5,320,795	5,265,700	5,197,422	5,105,331	5,040,593	4,995,357	4,895,119	4,920,288	4,335,253	4,168,268
5,271,368	5,249,878	5,181,854	5,068,890	5,016,598	4,971,879	4,818,593	4,453,507	4,270,509	DES. 309,458
5,263,719	5,187,425	5,150,674	5,040,644	4,998,956	4,971,219	4,894,792	4,430,594	4,233,534	DES. 309,457

Machine Serial Number:

.....

Engine Serial Number:

.....