


Original Version: EN
Issue: 24.10.12
From Serial No: 313000001 onwards
Part No: 111-6701 A

Main Assembly



Item No	Description	Part No.	QTY	Item Note	Item No	Description	Part No.	QTY	Item Note
02	ENGINE B&S SERIES 650 XVB COVE	111-6624	1		37	STARLUX END CAP 6MM	100.000.967	2	
03	DECAL ENGINE MOTIF 48(RS)	111-6687	1		38	DEFLECTOR PIN 6*385	433007	1	
04	CABLE ENGINE BRAKE	111-3342	1		43	KEY WOODRUFF 3/16**5/8"	1662	1	
05	FITTING HANDLEBAR	411035	1		44	CLIP BELT COVER	100.000.801	2	
06	KNOB M8 HANDLEBAR	480088	2		45	BELT COVER 48	100.000.800	1	
07	PLUG TUBE 7/8**16g E	300160	2		46	KNOB HOC-GRIF	100.000.828	1	
08	BOLT HANDLEBAR M8*45	HY226024	2		47	CONNECTING ROD 48 PUSH	433011W	1	
09	NUT M6 NYLOC 'P' TYPE GD 8	09544	1		48	AXLE REAR 48 PUSH W/A	433016W	1	
10	WASHER PLAIN M6*12*1.6	09472	1		49	WHEEL REAR 200 WAFFEL	100.000.401	2	
11	GUIDE ROPE	305093	1		50	M12 NYLOC EXTRA THIN	100.000.604	4	
12	UPPER HANDLEBAR	305145W	1		51	TRIM WHEEL 180 BLACK(RADCAPPE)	100.033.691	2	
13	FASTENER DRIVE 6.5	341033	3		52	WHEEL FRONT 180 WAFFEL	100.022.836	2	
14	PIN PIVOT	340182	2		53	AXLE SPACER	100.000.792	4	
15	LEVER ENGINE	340179	1		54	AXLE RETAINER	100.000.897	4	
16	SCREW DIA 6*20 PT PAN FLANGE	09687	2		55	M6*6 SHOULDER SCREW	100.000.576	2	
18	FASTENER DRIVE	300144	4		56	BOLT UNF	09118	1	
19	WASHER NYLON 19*11*1.6	09688	6		57	WASHER SPRING 3/8 SC	09273	1	
20	NUT M6 NYLOC 'T' TYPE	09438	4		58	DISTANCE PIECE CUTTERBAR	HY4014	1	
21	BOLT M6*40	ZBH1F040U	1		59	WASHER M6	100.000.630	2	
22	GUIDE CABLE	410037	2		60	PLATE RATCHET HOC	432020W	1	
23	CABLE TIE	HY3966	1		61	AXLE FRONT 48 W/A	433014W	1	
24	DECAL - SAFETY PETROL	111-0083	1		62	CUTTERBAR 19"	480149	1	
25	HANDLEBAR LOWER	432001W	2		63	FRICTION DISC W/A (BLACK)	397042W	1	
26	SETSCREW M8*20	09368	4		65	DECK (GREEN)	111-0962-08	1	
27	NUT M8 NYL INSERT T TYPE	09441	4		66	SCREW TAPTITE UNC 3/8**1 1/4"	09349	3	
29	LABEL HEIGHT OF CUT	320006	1		67	AXLE SUPPORT	100.000.895	4	
30	SPRING TORSION REAR DEFL. RH	100.000.826	1		68	DECAL (HAYTER, LOGO 03)	410087	1	
31	SPRING TORSION REAR DEFL. LH	100.000.825	1		69	TRIM WHEEL 200 BLACK(RADCAPPE)	100.033.711	2	
32	REAR DEFLECTOR 48	100.000.077	1		80	RIVET, POP .187DIA	MU710259	4	
33	FRAME GRASSBAG 48/53	433010W	1		83	WASHER 10.5 DIA * 30 O/D * 2.5	100.000.632	1	
34	FABRIC GRASSBAG	433003	1		85	SCREW TAPTITE M10*25 HEX W.HD	111-6759	4	
35	SCREW PAN HEAD M5*12 TAPTITE	10-11-029	2		86	BRACKET HANDLEBAR LH	111-0964-03	1	
36	PLATE DISCHARGE	432021W	1		87	BRACKET HANDLEBAR RH	111-0965-03	1	
					89	DECAL - MADE IN BRITAIN	111-6625	1	

Motif 48 - Declaration Of Conformity

EC DECLARATION OF CONFORMITY

Manufactured by: HAYTER LIMITED,
Address: Spellbrook, Bishop's Stortford, Herts. CM23 4BU. ENGLAND
declare that the lawnmower :

Model name: Motif 48
Push

Type: Pedestrian rotary
Model No: CODE 433
Cutting width: 48 cm
Speed of rotation of the
cutting device: 2750 rpm
Engine manufacturer: Briggs & Stratton
Speed of rotation of engine: 2750 rpm
Serial No. Range: 313000001 - 313999999

Complies with the provisions of Directive: 2006/42/EC Essential Health & Safety Requirements Relating to the Design & Construction of Machinery and Safety Components and the regulations transposed into national law.
Also Directive 2004/108/EEC Electromagnetic Compatibility and the regulations transposed into national law.
Also Directive 2000/14/EC Noise emission in the environment by equipment for use outdoors, as amended and the regulations transposed into national law.
Procedure applied for the conformity assessment: ANNEX VI, procedure 1.
Notified Body: Sound Research Laboratories Ltd, Holbrook House, Little Waldingfield,
Sudbury, Suffolk. CO10 0TH. ENGLAND
Notified body identification No: 1088

Measured sound power level: 95 dB(A)
Guaranteed sound power level: 96 dB(A)
Signed

Date: 28.09.12
Declaration done and technical documentation kept at:
HAYTER LIMITED
Spellbrook, Bishop's Stortford,
Herts. CM23 4BU ENGLAND

S. A Maryniak
(Technical Director)



VIBRATION INFORMATION

Hand / Arm Vibration Level at the Operator Position measured in accordance with European Standard EN 836:
433
Measured Vibration Level a_{hv} = 6 ms^{-2}
Uncertainty of measurement K = 1.5 ms^{-2}

SOUND PRESSURE INFORMATION
Sound Pressure Level at the Operator Position measured in accordance with European Standard EN 836:
Measured Sound Pressure Level L_{PA} = 84.5 dB(A)
Uncertainty of measurement K = 2 dB(A)

Serial No.

Original Version: EN
Issue: 24.10.12
From Serial No: 313000001 onwards
Part No: 111-6701 A

Hayter Limited, Spellbrook, Bishop's Stortford, Herts, England, CM23 4BU TEL:- +44 (0)1279 723444