

TORO

MODEL NO. 30779

INSTALLATION INSTRUCTIONS

MULCHER KIT

(for 72" Cutting unit, Model 30575)

1. Remove cutting unit from traction unit as instructed in operators manual.
 2. Release and unhook latches securing center and left covers to top of cutting unit. Remove covers.
 3. Locate and remove (2) capscrews and flange nuts plugging mounting holes in deck. Retain all fasteners for further use.
 4. Turn cutting unit upside down and block up ends, to ease in the installation of the mulcher kit components.
 5. Position mulcher screen on cutting unit, aligning it with (2) mounting holes in deck and (1) mounting hole in deflector stop.
 6. Secure mulcher screen to cutting unit with (2) 3/8 - 16 x 3/4" lg. capscrews, lockwashers and flange locknuts. Secure end of mulcher screen to deflector stop with a 5/16 x 1" lg. carriage bolt and flange locknut.
 7. Rotate the cutter blades to assure there is enough clearance between blades and mulcher screen. There should be approximately 1" clearance.
 8. Using mulcher screen as a template, mark remaining (4) mounting hole locations in top of cutting unit.
 9. Remove mulcher screen from cutting unit and drill (4) 13/32" (.406) dia. holes at positions marked.
 10. Reinstall mulcher screen to cutting unit with (6) 3/8 - 16 x 3/4" lg. capscrews, lockwashers and flange locknuts.
 11. Secure mulcher screen to deflector stop with 5/16 x 1" lg. carriage bolt and flange nut.
 12. Align mounting holes in cutting unit with support tubes on rear shelf. Secure rear shelf to cutting unit with (4) 3/8 - 16 x 3/4" lg. capscrews and lockwashers.
 13. Reinstall cutting unit covers and latch.
 14. Reinstall cutting unit to traction unit as instructed in operators manual.
- NOTE: When mulcher is removed, plug mounting holes in top of cutting unit with fasteners supplied in kit.

