2026-2027 CATALOG

SNOW BLOWERS

60V[MAX*] BATTERY / GAS POWERED

#1 AMERICA'S SNOW BLOWER BRAND

TORO®

SINGLE-STAGE POWER CLEAR® | SNOWMASTER®
TWO-STAGE POWER MAX® | POWER MAX® HD | POWER TRX HD®

Count on it.

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load. ◊Based on average OpenBrand dollar share for snow blower market as of March 2026.

CORDED ELECTRIC SNOW BLOWERS

Ideal for sidewalks, steps, decks and small driveways. Corded Power Shovel also available.

CORDED ELECTRIC

SMOOTH SURFACE

SMOOTH SURFACE

POWER CLEAR® SINGLE-STAGE SNOW BLOWERS

Driveways that can hold up to 9 cars and 2-9" / 5-23 cm of snow with limited garage storage.

AVAILABLE IN

GAS POWERED

60V MAX BATTERY

SMOOTH SURFACE

SMOOTH SURFACE

SNOWMASTER® SINGLE-STAGE SNOW BLOWERS

Driveways that can hold up to 12 cars and 2-9" / 5-23 cm of snow.

AVAILABLE IN

GAS POWERED

60V MAX BATTERY

SMOOTH SURFACE

SMOOTH SURFACE

POWER MAX® AND POWER MAX® HD TWO-STAGE SNOW BLOWERS

Larger driveways that can hold up to 20 parked cars and 9-21" / 23-53 cm of snow at a time.

AVAILABLE IN

GAS POWERED

60V MAX BATTERY

MULTI SURFACE

SMOOTH OR GRAVEL SURFACE

POWER TRX HD® TRACKED TWO-STAGE SNOW BLOWERS

Extra-large driveways, heavy accumulation and making quick work of 10"+ / 25.4 cm+ of snow.

GAS POWERED

MULTI SURFACE

SMOOTH OR GRAVEL SURFACE

60V MAX* BATTERY SNOW BLOWERS

FEAR NO STORM

No gas. No oil. Just 60V battery power that's ready when you need it.

	CORE					PREMIUM		
	60V POWER SHOVEL®	SINGLE-STAGE POWER CLEAR® 60V E21	SINGLE-STAGE SNOWMASTER® 60V E24	TWO-STAGE POWER MAX® 60V E24	TWO-STAGE POWER MAX® 60V E24	SINGLE-STAGE POWER CLEAR® 60V E21	SINGLE-STAGE SNOWMASTER® 60V E24	TWO-STAGE POWER MAX® 60V E26®
MODEL	**39909**	**39901**	**39914**	**39924**	**39925**	**39921**	**39915**	**39926**
CLEARING WIDTH	12" / 31 cm	21" / 53 cm	24" / 61 cm	24" / 61 cm	24" / 61 cm	21" / 53 cm	24" / 61 cm	26" / 66 cm
CLEARING CAPACITY**	Decks, patios and up to 4 parked cars	Up to 12 parked cars	Up to 20 parked cars	Up to 24 parked cars (12 cars per battery) Up to 15 cars more with additional 3rd battery	Up to 20 parked cars	Up to 15 parked cars	Up to 30 parked cars	Up to 30 parked cars (15 cars per battery) Up to 15 cars more with additional 3rd battery
SNOW CUT DEPTH	6" / 15.2 cm	12" / 30.5 cm	18" / 45.7 cm	20" / 50.8 cm	20" / 50.8 cm	12" / 30.5 cm	18" / 45.7 cm	20" / 50.8 cm
BATTERY	1 x2.5 Ah	1 x 7.5 Ah	1 x 10.0 Ah	2 x 6.0 Ah	1 x 10.0 Ah	1 x 10.0 Ah	1 x 10.0 ah + 1 x 5.0 Ah	2 x 7.5 Ah
CHARGE TIME	60 min	155 min	215 min	150 min	215 min	215 min	215 min	155 min
THROWING DISTANCE**	Up to 25' / 7.6 m	Up to 40' / 12.2 m	Up to 34' / 10.4 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 30' / 9.1 m	Up to 34' / 10.4 m	Up to 45' / 13.7 m
AUGER SYSTEM	Power Curve®	Patent Pending Power Edge™	Single-Stage	Power Max Anti-Clogging System	Power Max Anti-Clogging System	Power Curve® Self-Propel	Single-Stage	Power Max Anti-Clogging System
AUGER DIAMETER	6.5" / 16.5 cm	7" / 17.8 cm	10" / 25.4 cm	11" / 27.9 cm	11" / 27.9 cm	8.5" / 21.6 cm	10" / 25.4 cm	11" / 27.9 cm
IMPELLER DIAMETER	-	-	-	11" / 27.9 cm	11" / 27.9 cm	-	-	11" / 27.9 cm
AUGER GEARBOX	-	-	-	Hardened Gears, No Shear Pins	Hardened Gears, No Shear Pins	-	-	Hardened Gears, No Shear Pins
HANDLE	-	Adjustable	Personal Pace®	Standard	Standard	Ergonomic	Personal Pace®	Heavy-Duty
DEFLECTOR	-	Locking	Single	Single	Single	Locking	Single	Single
CHUTE CONTROL	-	Quick Turn	Quick Stick®	Quick Stick®	Quick Stick®	Chute Mounted	Quick Stick®	Quick Stick®
CHUTE CONSTRUCTION	-	Sub Zero Curved Chute	High Capacity Chute	Steel	Steel	High Capacity Chute	High Capacity Chute	Steel
TIRES	-	6 7/8" x 2" 17.5 cm x 5.1 cm	11" / 27.9 cm	15" / 38.1 cm	15" / 38.1 cm	7" / 17.8 cm	11" / 27.9 cm	15" / 38.1 cm
HAND WARMERS	-	-	-	-	-	-	-	Standard
LIGHT	-	Panoramic LED	-	LED	LED	Panoramic LED	Panoramic LED	LED
WARRANTY***	3-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery
BARE TOOL MODEL #	**39909T**	**39901T**	-	-	-	**39921T**	**39915T**	**39926T**

*Battery manufacturer rating = 60V maximum and 54V typical usage. Actual voltage varies with load. **Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.

POWER CLEAR® SINGLE-STAGE SNOW BLOWERS

GET THE JOB DONE FASTER.

Trusted by professionals perfectly blending power and efficiency, the Power Clear® makes quick work of small driveways, walkways and patios.

IDEAL FOR Driveways that can hold up to 9 cars and 2-9" / 5-23 cm of snow with limited garage storage

	CORE				PREMIUM		COMMERCIAL-GRADE	
	POWER CLEAR® 518 ZR	POWER CLEAR® 518 ZE	POWER CLEAR® 721 R	POWER CLEAR® 721 E	POWER CLEAR® 721 QZE	POWER CLEAR® 821 QZE	POWER CLEAR® 721 R-C	POWER CLEAR® 821 R-C
MODEL	**38474**	**38475**	**38752**	**38753**	**38756**	**38757**	**38754**	**38755**
CLEARING WIDTH	18" / 46 cm	18" / 46 cm	21" / 53 cm	21" / 53 cm	21" / 53 cm	21" / 53 cm	21" / 53cm w/ Extended Life Paddles	21" / 53 cm w/ Extended Life Paddles
SNOW CUT DEPTH	12" / 30.5 cm	12" / 30.5 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm
ENGINE	99cc Toro Premium OHV	99cc Toro Premium OHV	212cc Toro Premium OHV	212cc Toro Premium OHV	212cc Toro Premium OHV	252cc Toro Premium OHV	212cc Toro Premium OHV	252cc Toro Premium OHV
DRIVE SYSTEM	Rotor Propelled	Rotor Propelled	Power Propel® Self-Propel	Power Propel® Self-Propel	Power Propel® Self-Propel	Power Propel® Self-Propel	Power Propel® Self-Propel	Power Propel® Self-Propel
STARTING	Recoil	Electric	Recoil	Electric	Electric	Electric	Recoil	Recoil
THROWING DISTANCE*	Up to 25' / 7.6 m	Up to 25' / 7.6 m	Up to 35' / 10.7 m	Up to 35' / 10.7 m	Up to 35' / 10.7 m	Up to 40' / 12.2 m	Up to 35' / 10.7 m	Up to 40' / 12.2 m
AUGER SYSTEM	Power Curve®	Power Curve®	Power Curve®	Power Curve®	Power Curve®	Power Curve®	Power Curve®	Power Curve®
HANDLE	Standard	Standard	Ergonomic	Ergonomic	Ergonomic	Ergonomic	Reinforced & Ergonomic Handle	Reinforced & Ergonomic Handle
DEFLECTOR	Locking	Locking	Locking	Locking	Locking	Locking	Locking	Locking
CHUTE CONTROL	Chute Mounted	Chute Mounted	Chute Mounted	Chute Mounted	Quick Chute	Quick Chute	Chute Mounted	Chute Mounted
TIRES	6" x 1.5" / 15.2 x 3.8 cm	6" x 1.5" / 15.2 x 3.8 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm
WARRANTY**	2-Year Limited 2-Year Guaranteed to Start				2-Year Limited 2-Year Guaranteed to Start		2-Year Limited Residential, 1-Year Limited Commercial 2-Year Guaranteed to Start Residential Only	

***Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.*

Power Clear® 721 QZE

- 212cc Toro Premium OHV Engine
- Power Propel® Self-Propel
- 21" / 53 cm Clearing Width

Power Clear® 821 QZE

- 252cc Toro Premium OHV Engine
- Power Propel® Self-Propel
- 21" / 53 cm Clearing Width

POWER TO BLAST THROUGH SNOW
Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time and throw it up to 40 feet/12 meters.

GET A MOVE ON
Keep moving to get done faster with Power Propel® self-propel system. The unique scraper pulls you through the snow.
Select models.

SHREDS SNOW FAST
Efficiently shreds through snow while reducing clogging with the curved rubber paddles and housing of Power Curve® technology.

BUILT TOUGH AND DEPENDABLE FOR EVEN THE MOST EXTREME CONDITIONS.

Take control of big snow jobs this winter with the speed and ease of Power Max® and Power Max® HD.

IDEAL FOR Larger driveways that can hold 6-14 parked cars and 6-20" / 15-50 cm of snow at a time

	CORE		PREMIUM	
	POWER MAX® 724 OE	POWER MAX® 824 OE	POWER MAX® 826 OAE	POWER MAX® 826 OHAE
MODEL	**37807**	**37798**	**37799**	**37805**
CLEARING WIDTH	24" / 61.0 cm	24" / 61.0 cm	26" / 66.0 cm	26" / 66.0 cm
SNOW CUT DEPTH	20" / 50.8 cm	20" / 50.8 cm	20" / 50.8 cm	20" / 50.8 cm
ENGINE	212cc Toro Premium OHV	252cc Toro Premium OHV	252cc Toro Premium OHV	252cc Toro Premium OHV
DRIVE SYSTEM	Self-Propelled	Self-Propelled	Triggerless Steering	Triggerless Steering
STARTING	Electric	Electric	Electric	Electric
THROWING DISTANCE*	Up to 40' / 12.2 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m
AUGER SYSTEM	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging
AUGER DIAMETER	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm
IMPELLER DIAMETER	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm
AUGER GEARBOX	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required
HANDLE	Standard	Standard	Standard	Heavy-Duty
DEFLECTOR	Single	Single	Single	Single
CHUTE CONTROL	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®
TIRES	15" / 38.1 cm	15" / 38.1 cm	15" / 38.1 cm	15" / 38.1 cm
HAND WARMERS	–	–	–	✓
LED LIGHT	–	–	✓	✓
WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited

***Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.*

POWER MAX® HD 828

- 28" / 71 cm Clearing Width
- 252cc Toro Premium OHV Engine
- Commercial-Grade Auger Gear Box
- All-Steel Construction
- Anti-Clogging System
- 16" / 40.6 cm Never-Flat Tires

POWER MAX® HD 1230

- 30" / 76 cm Clearing Width
- 302cc Toro Premium OHV Engine
- Commercial-Grade Auger Gear Box
- All-Steel Construction
- Hand Warmers Standard
- Anti-Clogging System
- 16" / 40.6 cm Never-Flat Tires

POWER MAX® 826 OAE

- 26" / 66 cm Clearing Width
- 252cc Toro Premium OHV Engine
- Triggerless Steering
- Anti-Clogging System

POWER UP
Optimal performance and years of dependable use with the 252cc Toro premium 4-cycle OHV engine.

TRIGGERLESS STEERING
No triggers to pull or levers to break! Turn the machine and the wheel intelligently disengages to assist you through for effortless turns.

CHUTE CONTROL
Quickly change the chute and deflector direction with a single, smooth motion thanks to the Quick Stick® chute control.

IDEAL FOR Larger driveways that can hold up to 20 parked cars and 9-21" / 23-53 cm of snow at a time

	PREMIUM		COMMERCIAL-GRADE			
	POWER MAX® HD 824	POWER MAX® HD 828	POWER MAX® HD 1230	POWER MAX® HD 1232	POWER MAX® HD 1428 OHXE	POWER MAX® HD 1432 OHXE
MODEL	**39960**	**39961**	**39962**	**39963**	**38843**	**38844**
CLEARING WIDTH	24" / 61 cm	28" / 71 cm	30" / 76 cm	32" / 81 cm	28" / 71 cm	32" / 81 cm
SNOW CUT DEPTH	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm
ENGINE	252cc Toro Premium OHV	252cc Toro Premium OHV	302cc Toro Premium OHV	375cc Toro Premium OHV	420cc Toro Premium OHV	420cc Toro Premium OHV
DRIVE SYSTEM	Triggerless Steering	Triggerless Steering	Triggerless Steering	Triggerless Steering	Power Steering	Power Steering
STARTING	Electric	Electric	Electric	Electric	Electric	Electric
THROWING DISTANCE*	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 49' / 14.9 m	Up to 57' / 17.4 m	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+
AUGER SYSTEM	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging
AUGER DIAMETER	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm
IMPELLER DIAMETER	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm
AUGER GEARBOX	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required
HANDLE	Heavy-Duty	Heavy-Duty	Heavy-Duty	Heavy-Duty	Commercial	Commercial
DEFLECTOR	Single	Single	Single	Double	Double	Double
CHUTE CONTROL	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®
TIRES	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm	16" / 40.6 cm
HAND WARMERS	–	–	✓	✓	✓	✓
LED LIGHT	✓	✓	✓	✓	✓	✓
WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	5-Year Limited / 1-Year Commercial	5-Year Limited / 1-Year Commercial

***Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.*

NO SHEAR PINS!
No need to replace shear pins in the cold with Toro's hardened gears and commercial-grade auger gearbox.

PRECISION MOVES
Smooth, tight turns are a snap with power steering.

DOUBLE CHUTE DEFLECTOR
Place the snow with greater precision, such as right next to your fence line, or throw the distance with a double deflector.

POWER TRX HD® TRACKED TWO-STAGE SNOW BLOWERS

WHEN A MONSTER STORM ROARS IN, ROAR BACK.

Featuring our biggest engine, the Power TRX HD is built for your snowiest jobs, toughest terrain and steepest slopes.

IDEAL FOR Extra-large driveways, heavy accumulation and making quick work of 10"+ / 25.4 cm+ of snow

	COMMERCIAL-GRADE	
	POWER TRX HD® 1428 OHXE	POWER TRX HD® 1432 OHXE
MODEL	38890	38891
CLEARING WIDTH	28" / 71 cm	32" / 81 cm
SNOW CUT DEPTH	21" / 53.3 cm	21" / 53.3 cm
ENGINE	420cc Toro Premium OHV	420cc Toro Premium OHV
DRIVE SYSTEM	Self-Propelled Hydrostatic Transmission and Power Steering	Self-Propelled Hydrostatic Transmission and Power Steering
STARTING	Electric	Electric
THROWING DISTANCE*	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+
AUGER SYSTEM	Power Max Anti-Clogging	Power Max Anti-Clogging
AUGER DIAMETER	14" / 35.6 cm	14" / 35.6 cm
IMPELLER DIAMETER	14" / 35.6 cm	14" / 35.6 cm
AUGER GEARBOX	Commercial-Grade, No Shear Pins	Commercial-Grade, No Shear Pins
HANDLE	Commercial	Commercial
DEFLECTOR	Double	Double
CHUTE CONTROL	Quick Stick®	Quick Stick®
TIRES	Tracked	Tracked
HAND WARMERS	✓	✓
LED LIGHT	✓	✓
WARRANTY**	5-Year Limited, 1-Year Commercial	5-Year Limited, 1-Year Commercial

***Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.*

Power TRX HD® 1428 OHXE / 1432 OHXE

- Self-Propelled Hydrostatic Transmission
- Tracked Driven for Ultimate Performance
- Commercial Grade All-Steel Construction
- 420cc Toro Premium OHV Engine

Choose Toro Total Care for Ultimate Peace of Mind

Benefit from an extended warranty, maintenance reimbursement, and more.

UNMATCHED STABILITY
Track driven allows you to handle the steepest slopes or dig into hard packed snow.

SMOOTH HANDLING AND LOW MAINTENANCE
Hydrostatic transmission allows for self-propelled operation with infinitely variable speed.

TORO®

SNOWMASTER® SINGLE-STAGE SNOW BLOWERS

THE ONE MADE FOR MORE.

Built for those who expects more: more power, more control, more snow cleared.

CORDED ELECTRIC SNOW BLOWERS

MAKE SMALL SNOW CLEARING JOBS A SNAP.

An ideal choice for sidewalks, steps, decks and small driveways.

	CORE	PREMIUM
	SNOWMASTER® 724 QXE	SNOWMASTER® 824 QXE
MODEL	36002	36003
CLEARING WIDTH	24" / 61.0 cm	24" / 61.0 cm
SNOW CUT DEPTH	18" / 45.7 cm	18" / 45.7 cm
ENGINE	212cc Toro Premium OHV	252cc Toro Premium OHV
DRIVE SYSTEM	Personal Pace® Self-Propel	Personal Pace® Self-Propel
STARTING	Electric	Electric
THROWING DISTANCE**	Up to 40' / 12.2 m	Up to 45' / 13.7 m
AUGER SYSTEM	Single-Stage	Single-Stage
AUGER DIAMETER	10" / 25.4 cm	10" / 25.4 cm
IMPELLER DIAMETER	10" / 25.4 cm	10" / 25.4 cm
CHUTE CONTROL	Quick Stick®	Quick Stick®
TIRES	11" / 27.9 cm	11" / 27.9 cm
WARRANTY***	3-Year Limited	3-Year Limited

	POWER SHOVEL®	1800 POWER CURVE®
MODEL	38361	38381
CLEARING WIDTH	12" / 30.5 cm	18" / 45.7 cm
WEIGHT	13 lbs / 5.9 kg	26 lbs / 11.8 kg
THROWING DISTANCE**	Up to 20' / 6.1 m	Up to 30' / 9.1 m
CHUTE CONTROL	–	Quick Lever
DEFLECTOR	–	Locking
DEPTH OF SNOW CUT, ONE PASS	6" / 15.2 cm	10" / 25.4 cm
WARRANTY***	2-Year Limited	2-Year Limited

***Throw distance and clearing capacity will vary with conditions.*
****See retailer for complete warranty details.*

Choose Toro Total Care for Ultimate Peace of Mind

Benefit from an extended warranty, maintenance reimbursement, and more.

©2026 The Toro Company All Rights Reserved.
Specifications subject to change without notice and without incurring obligation. Products depicted are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

ToroBR004ENG