

	POWER MAX®			POWER MAX® HD			
	724 OE 37779	826 OE 37780	826 OXE 37781	826 OXE 38805	928 OHXE 38801	1028 OHXE 38802	1128 OHXE 38803
<b>PERFORMANCE</b>							
<b>THROW DISTANCE*</b>	Up to 40' / 12 m	Up to 40' / 12 m	Up to 40' / 12 m	» Up to 45' / 13.5 m	Up to 45' / 13.5 m	Up to 45' / 13.5 m	Up to 45' / 13.5 m
<b>CLEARING WIDTH</b>	24"	» 26"	26"	26"	» 28"	28"	28"
<b>POWER STEERING</b>	N/A	N/A	» Automatic Steering	» Power Steering	Power Steering	Power Steering	Power Steering
<b>SPEEDS</b>	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.	6 Fwd. / 2 Rev.
<b>SNOW CUT DEPTH – 1 PASS</b>	20"	20"	20"	» 21.5"	21.5"	21.5"	21.5"
<b>AUGER SYSTEM</b>	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)	Anti-Clogging System (ACS)
<b>AUGER DIAMETER</b>	11"	11"	11"	» 14"	14"	14"	14"
<b>AUGER GEARBOX</b>	Hardened Gears	Hardened Gears	Hardened Gears	» Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed	Commercial-Grade; No shear pins needed
<b>ENGINE</b>							
<b>ENGINE</b>	212cc Toro® Premium OHV 4-cycle	» 252cc Toro Premium OHV 4-cycle	252cc Toro Premium OHV 4-cycle	252cc Toro Premium OHV 4-cycle	» 265cc Toro Premium OHV 4-cycle	» 302cc Toro Premium OHV 4-cycle	» 342cc B&S OHV 4-cycle
<b>STARTER</b>	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start	Electric Start
<b>FUEL CAPACITY</b>	2.3 Quarts (2.2 L)	» 3.2 Quarts (3.0 L)	3.2 Quarts (3.0 L)	3.2 Quarts (3.0 L)	3.7 Quarts (3.5 L)	3.7 Quarts (3.5 L)	3.2 Quarts (3.0 L)
<b>USER-FRIENDLY FEATURES</b>							
<b>CHUTE CONTROL</b>	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick	Quick Stick
<b>SKIDS</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>ONE-HAND INTERLOCK</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>HAND WARMERS</b>	N/A	N/A	N/A	N/A	» Standard	Standard	Standard
<b>SCRAPER</b>	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	» Pivoting
<b>TIRES</b>	13" Deep Lug, Directional	13" Deep Lug, Directional	13" Deep Lug, Directional	» 16" Deep Lug, Directional	16" Deep Lug, Directional	16" Deep Lug, Directional	16" Deep Lug, Directional
<b>HEADLIGHT</b>	N/A	N/A	» Yes	Yes	Yes	Yes	Yes
<b>WEIGHT</b>	171 lbs. / 78 kg	175 lbs. / 79 kg	176 lbs. / 79 kg	243 lbs. / 110 kg	262 lbs. / 119 kg	267 lbs. / 121 kg	269 lbs. / 122 kg
<b>STORAGE DIMENSIONS</b>	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	56" x 27.8" x 43.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"	62" x 29.5" x 44.5"
<b>MACHINE WARRANTY**</b>	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited
<b>DEFLECTOR, BYPASS, CHUTE WARRANTY**</b>	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life	Guaranteed for Life

» = Enhanced or Step-up feature

**POWER MAX®**



**ANTI-CLOG SYSTEM (ACS)**  
Prevents clogging and maximizes impeller speed and snowblowing velocity.



**QUICK STICK® CHUTE CONTROL**  
An innovative joystick control allows you to change the chute direction quickly and easily, even on the go.



**MAXIMUM STRENGTH**  
The unique one-piece frame offers maximum strength for years of dependable use.



**SUB ZERO MATERIAL**  
The chute, deflector, and ACS are made out of a special cold-weather material durable to -104°F. Guaranteed for Life\*.


**POWER MAX® HD**



**HAND WARMERS**  
Keep warm in subzero temperatures for added comfort.



**14" SERRATED AUGER**  
Extra-large auger designed to chew through even the toughest snow.



**FREEWHEEL POWER STEERING**  
Handle-mounted triggers allow you to disengage one or both wheels for effortless maneuverability.



**COMMERCIAL-GRADE GEARBOX**  
Unlike others, this gearbox is tough enough not to need shear pins so you never need to worry about replacing them.

**TORO®**

\*See retailer for warranty details.

490-9161 ©2015 The Toro Company. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \*Throw distance will vary with conditions. \*\*See toro.com (US), toro.ca (Canada) or your dealer for warranty details.